Linköping Studies in Science and Technology
Dissertation No. 2201

Visual Odometry in Principle and Practice

Mikael Persson

Linköping Studies in Science and Technology
Dissertations, No. 2201

Visual Odometry in Principle and Practice

Mikael Persson

Linköping University
Department of Electrical Engineering
Computer Vision Laboratory
SE-581 83 Linköping, Sweden

Linköping 2022

This work is licensed under a Creative Commons Attribution-NonCommercial 4.0 International License.

<https://creativecommons.org/licenses/by-nc/4.0/>

Edition 1:1

ISBN 978-91-7929-168-6 (Print) 978-91-7929-169-3 (PDF)

ISSN 0345-7524

URL <https://urn.kb.se/resolve?urn=urn:nbn:se:liu:diva-182731>

Published articles have been reprinted with permission from the respective copyright holders.

Typeset using X_YT_EX

Printed by LiU-Tryck, Linköping 2022

Till min familj

POPULÄRVETENSKAPLIG SAMMANFATTNING

Syn är det främsta sinnet genom vilket vi vet var vi är, vad som finns i närheten och hur vi rör oss. Motsvarande datorseendeuppgift är den simultana kartläggningen av omgivningen och lokaliseringen av kameran. Detta går under många namn varav jag använder visuell odometri, vilket innebär att bilderna är sekventiella och betonar noggrannheten i positioneringen och realtidskraven. Detta område har sett avsevärda förbättringar under det senaste decenniet och visuell odometri används flitigt inom robotik för lokalisering, navigering och hinderdetektion.

Avhandlingens huvudsakliga syfte är att studera och utveckla visuella odometrisystem och ger flera bidrag. Det första är ett högpresterande stereo visuellt odometrisystem, som använde geometriskt stödd spårning för att uppnå högsta rank på KITTI:s odometri tävling.

Det andra är den ledande trepunktperspektivlösaren. Lösaren hittar orientering och position för en kamera givet projektionerna av tre kända 3D-punkter och är en central del av många visuella odometrisystem. Genom att omformulera det underliggande problemet så undvek vi det problematiska fjärdegradspolynomet andra lösare lider av. Detta resulterade i avsevärt högre beräkningsprestanda och numerisk noggrannhet.

Det tredje är ett system som generaliserar stereo visuell odometri till den samtidiga skattningen av flera oberoende rörliga objekt. Det huvudsakliga bidraget är ett realtidssystem som tillåter identifiering av rörliga stela objekt och skattning av deras banor i realtid, med tillämpningar inom robotnavigering i dynamiska miljöer.

Det fjärde är ett förbättrad ramverk för skattning av kontinuerliga positioneringstrajektorier av splinetyp. Ramverket förenklar integrering av dynamiska modeller, och används för att visa att visuella odometrisystem baserade på kontinuerliga positioneringstrajektorier är både praktiska och kan köras i realtid.

Visuella odometripipelinerna betraktas både från ett teoretiskt och ett praktiskt perspektiv, och de designade systemen har testats på benchmarks och sensorplattformar. Den här avhandlingen placerar det publicerade arbetet i ett sammanhang och lyfter fram viktiga insikter och praktiska observationer.

ABSTRACT

Vision is the primary means by which we know where we are, what is nearby, and how we are moving. The corresponding computer-vision task is the simultaneous mapping of the surroundings and the localization of the camera. This goes by many names of which this thesis uses Visual Odometry. This name implies the images are sequential and emphasizes the accuracy of the pose and the real time requirements. This field has seen substantial improvements over the past decade and visual odometry is used extensively in robotics for localization, navigation and obstacle detection.

The main purpose of this thesis is the study and advancement of visual odometry systems, and makes several contributions. The first of which is a high performance stereo visual odometry system, which through geometrically supported tracking achieved top rank on the KITTI odometry benchmark.

The second is the state-of-the-art perspective three point solver. Such solvers find the pose of a camera given the projections of three known 3d points and are a core part of many visual odometry systems. By reformulating the underlying problem we avoided a problematic quartic polynomial. As a result we achieved substantially higher computational performance and numerical accuracy.

The third is a system which generalizes stereo visual odometry to the simultaneous estimation of multiple independently moving objects. The main contribution is a real time system which allows the identification of generic moving rigid objects and the prediction of their trajectories in real time, with applications to robotic navigation in dynamic environments.

The fourth is an improved spline type continuous pose trajectory estimation framework, which simplifies the integration of general dynamic models. The framework is used to show that visual odometry systems based on continuous pose trajectories are both practical and can operate in real time.

The visual odometry pipeline is considered from both a theoretical and a practical perspective. The systems described have been tested both on benchmarks and real vehicles. This thesis places the published work into context, highlighting key insights and practical observations.

ACKNOWLEDGMENTS

This thesis is the culmination of a long journey. An adventure filled with challenges to overcome and rewards aplenty, but also a miserable slog at times. More than anything it has been an amazing opportunity to learn. Forcing me to address long neglected skills and letting me dive deep in esoteric topics, returning months later with new perspective. Looking back, I am astonished by how far I have come and for this I am grateful. There were easier paths I could have followed, but to do so is not in my nature.

No adventure would be the same without the party, or in this case the many colleagues I have collaborated with, and the friends who have supported me. Marcus and Hedborg for showing me what CVL is, and why it is good. I'm grateful to Zahra, Felix, Goutam, Joakim, Oliver, Mårten and Emil for fun discussions and for making this time about more than just work. Pavlo and Johan for helping me proof this thesis. Maria and Lasse, for giving me not just the opportunity to teach, but to grow and experiment as a teacher. I thank Martin, Abdo, Gustav and Hannes, for fun collaborations which reignited my passion for the work. My family, for their good advice and, their relentless support despite my obstinate refusal to follow such. I thank Andreas especially, for endless discussions and tremendous support in trying times.

I thank my many supervisors: Michael Felsberg for his belief in me and the freedom he provided. Klas Nordberg, for awakening my love of mathematics and his endless patience. Per-Erik Forssén, for taking me in and seeing this through to the end.

*Mikael Persson
Linköping, March 2022*

CONTENTS

Abstract	V
Acknowledgments	VII
I Background	1
1 Introduction	3
1.1 Contributions	4
1.2 Outline	5
1.3 Included publications	6
2 Visual Odometry	15
2.1 Notation	16
2.2 Measurement Model	17
2.3 Perspective Three Point	18
2.4 Measurement Noise	18
2.5 Marker-based Perspective N Point Visual Odometry (PNP-VO)	19
2.6 Bundle Adjustment Visual Odometry	20
2.7 Multi Camera Visual Odometry	23
2.8 Bootstrap Stereo Visual Odometry	23
2.9 Sequential Hierarchical Ransac (Shire)	25
3 Geometry	29
3.1 The Map Representation	29
3.2 Lambda Twist P3P	30
3.3 Improved Lambda Twist Results	33

4	Pose Trajectories	35
4.1	Spline Based Pose Trajectories	35
4.2	Uniform Basis Splines (B-splines)	36
4.3	B-Spline Integrals	39
4.4	B-Spline Endpoints and Extrapolation	40
4.5	Motion Models	41
4.6	Representation Power	43
4.7	Frame-Wise Discrete Pose Trajectories	46
5	Tracking	47
5.1	Feature Types	47
5.2	Feature Description and Matching	48
5.3	Image Pyramids	49
5.4	Geometrically Supported Tracking	49
5.5	Tracking in Practice	49
5.6	Symmetric Noise Induced Bias	50
5.7	Good Edgels To Track - Proper Derivation	51
6	Concluding Remarks	53
	Bibliography	55
II	Publications	59
	Paper A	
	Robust Stereo Visual Odometry from Monocular Techniques	61
	Paper B	
	Lambda Twist: An Accurate Fast Robust Perspective Three Point (P3P) Solver	71
	Paper C	
	Independently Moving Object Trajectories from Sequential Hierarchical Ransac	89
	Paper D	
	Practical Pose Trajectory Splines with Explicit Regularization	103
	Paper E	
	Good Edgels to Track: Beating the Aperture Problem with Epipolar Geometry	117
	Paper F	
	Robust Accurate Extrinsic Calibration of Static Non-overlapping Cameras	133

PART I

BACKGROUND

1

INTRODUCTION

Vision is the primary means by which we know where we are, what is nearby, and how things are moving. The corresponding computer-vision task is the simultaneous mapping of the surroundings and the localization of the camera. This goes by many names, such as Structure From Motion (SFM) and Visual Simultaneous Localization and Mapping (VSLAM) each with their own connotations. This thesis will use Visual Odometry (VO) which emphasizes that the system processes sequential images to provide accurate pose trajectories with low latency.

The field has advanced rapidly in the past decade, from early successes like the Augmented Reality (AR) system Parallel Tracking And Mapping (PTAM) [1] to modern systems, eg Paper A and [2]–[7] which target a wide range of AR, Virtual Reality (VR), autonomous driving, and robotics applications. Powerful structure aware optimization frameworks with automatic differentiation such as ceres-solver [8] have been designed for the task, further accelerating development. Datasets and benchmarks such as the 2012 KITTI visual odometry benchmark [9] allowed direct competition and public comparison further enhancing progress. Visual odometry systems are often modular, with several different components designed to solve various challenges. From low level components, such as the Perspective three Point (P3P) solver of Paper B and generic tracking, to high level optimization, map refinement, and loop closure. Numerous fundamentally different approaches still compete, each with their advantages, providing trade-offs suitable for different tasks, scenes and sequences. The degree of temporal correlation between images is a key property, in particular the frame rate to dynamic, *i.e.* in relation to the motion of the camera over the distance to the scene. Essentially, the goal of visual odometry, is to turn cameras into pose sensors.

Visual Odometry systems, such as the one of Paper A, provides accurate trajectory estimates for robotic navigation. Such systems can also be used

for static obstacle detection, and extended to identify and estimate the trajectories of other moving objects as shown in Paper C. Compared to large scale offline reconstruction from collections of images, the maps generated are sufficient for the task, rather than aiming to allow full scene reconstruction. However, given the pose trajectory for a video, it is straightforward to densify the reconstruction, as shown in Paper E. This allows the estimation of a dense map to be separated from the estimation of the pose trajectory. Visual odometry systems use one or more cameras, but can also include other sensors such as Inertial Measurement Units (IMU), and often use motion models for regularization and prediction, such as in Paper D. Synchronizing and calibrating the sensor rig in advance increases robustness and reduce latency. Non-overlapping camera calibration is shown in Paper F, and visual inertial calibration in Paper D.

1.1 Contributions

This thesis primarily studies and advances the class of visual odometry systems called point feature visual odometry. Their advantages include accuracy and computational performance, but the main advantage is versatility. Point feature visual odometry can be applied to any camera-lens configuration, to global as well as rolling shutter, use pre-existing maps, or generate their own. They benefit from geometrical supported tracking, but are not reliant on it to the same extent as the photometric semi-dense methods are. As a result, they are particularly well suited to be extended to find and estimate the trajectories of independently moving rigid objects, and this is the main contribution of Paper C.

The main contribution of Paper A, beyond the state-of-the-art of the art VO system, is the bootstrap tracking, which combines the advantages of geometrically supported tracking with the advantages of generic tracking.

The main contribution of Paper B is the state-of-the-art Perspective three Point solver (P3P) Lambda Twist. The reason for the method's excellent performance is the way the dual conic problem is solved, an approach which could potentially be applied to similar problems.

The main contribution of Paper C is the generalization of VO to real time simultaneous identification and estimation of moving objects, and to a lesser extent the public dataset and benchmark used in its evaluation.

The main contribution of Paper D is the method proposed for the integration of non-linear differential motion models with visual observations.

The visual odometry systems have been tested on real vehicles and benchmarks.

1.2 Outline

The introductory chapters of this thesis provide the background theory, highlights the key contributions, and motivates the reasoning behind system design choices, with a particular eye toward the kind of practical details or hard learned lessons required to successfully implement VO systems.

Chapter 2 describes the visual odometry from the perspective of the measurements and loss optimized in Papers A, C, and D, along with common approximations and optimization strategies.

Chapter 3 discusses the geometric representation of the map and the point features, and provides an important improvement made to the Lambda Twist P3P solver since publication.

Chapter 4 discusses pose trajectory representation, and how motion models are incorporated in the optimization problem.

Chapter 5 introduces the key trade-offs for visual trackers for VO, and provides a better derivation of the 1D KLT introduced by Paper E.

The thesis concludes with a few thoughts regarding the future of visual odometry, in Chapter 6

1.3 Included publications

Part II consists of the publications included in the thesis:

- Paper A: Robust Stereo Visual Odometry from Monocular Techniques
- Paper B: Lambda Twist: An Accurate Fast Robust Perspective Three Point (P3P) Solver
- Paper C: Independently Moving Object Trajectories from Sequential Hierarchical Ransac
- Paper D: Practical Pose Trajectory Splines With Explicit Regularization
- Paper E: Good Edgels to Track: Beating the Aperture Problem with Epipolar Geometry
- Paper F: Robust Accurate Extrinsic Calibration of Static Non-overlapping Cameras

I am the first author of papers A, B, C and D, and second author of E and F. The included publications are ordered by first author, then chronologically. The abstracts and details of my contributions to each publication are provided below. The included publications all share visual odometry as the primary topic, and the introduction concludes with my (non-included) publications.

Paper A: Robust Stereo Visual Odometry from Monocular Techniques

M. Persson, T. Piccini, M. Felsberg, and R. Mester, “Robust stereo visual odometry from monocular techniques”, in *IEEE Intelligent Vehicles Symposium 2015, Seoul, South Korea*, Jun. 2015, pp. 686–691 . The system achieved top rank on the KITTI VO benchmark.

Abstract

Visual odometry is one of the most active topics in computer vision. The automotive industry is particularly interested in this field due to the appeal of achieving a high degree of accuracy with inexpensive sensors such as cameras. The best results on this task are currently achieved by systems based on a calibrated stereo camera rig, whereas monocular systems are generally lagging behind in terms of performance. We hypothesize that this is due to stereo visual odometry being an inherently easier problem, rather than due to higher quality of the state of the art stereo based algorithms. Under this hypothesis, techniques developed for monocular visual odometry systems would be, in general, more refined and robust since they have to deal with an intrinsically more difficult problem. In this work we present a novel stereo visual odometry system for automotive applications based on advanced monocular techniques. We show that the generalization of these techniques to the stereo case result in a significant improvement of the robustness and accuracy of stereo based visual odometry. We support our claims by the system results on the well known KITTI benchmark, achieving the top rank for visual only systems.

Author Contributions

The author designed the system, wrote the software, and did the majority of the writing.

Paper B: Lambda Twist: An Accurate Fast Robust Perspective Three Point (P3P) Solver

M. Persson and K. Nordberg, “Lambda twist: An accurate fast robust perspective three point (P3P) solver”, in *The European Conference on Computer Vision (ECCV)*, Sep. 2018, pp. 334–349 . Lambda twist remains the state of the art P3P solver to this day.

Abstract

We present *Lambda Twist*; a novel *P3P* solver which is accurate, fast and robust. Current state-of-the-art *P3P* solvers find all roots to a quartic and discard geometrically invalid and duplicate solutions in a post-processing step. Instead of solving a quartic, the proposed *P3P* solver exploits the underlying elliptic equations which can be solved by a fast and numerically accurate diagonalization. This diagonalization requires a single real root of a cubic which is then used to find the, up to four, *P3P* solutions. Unlike the direct quartic solvers our method never computes geometrically invalid or duplicate solutions. Extensive evaluation on synthetic data shows that the new solver has better numerical accuracy and is faster compared to the state-of-the-art *P3P* implementations. Implementation and benchmark are available on [github](#).

Contributions

The author implemented the solver, the benchmark and did the majority of the writing. The method was jointly derived by the author and co-author Klas Nordberg, whom both contributed key insights.

Paper C: Independently Moving Object Trajectories from Sequential Hierarchical Ransac

M. Persson and P.-E. Forssén, “Independently moving object trajectories from sequential hierarchical ransac”, in *SCITEPRESS VISAPP 2021: Joint conference on computer vision, imaging and computer graphics theory and applications*, vol. 5, 2021, pp. 722–731 . Selected for oral presentation, nominated for best paper.

Abstract

Safe robot navigation in a dynamic environment, requires the trajectories of each independently moving object (IMO). We present the novel and effective system Sequential Hierarchical Ransac Estimation (Shire) designed for this purpose. The system uses a stereo camera stream to find the objects and trajectories in real time. Shire detects moving objects using geometric consistency and finds their trajectories using bundle adjustment. Relying on geometric consistency allows the system to handle objects regardless of semantic class, unlike approaches based on semantic segmentation. Most Visual Odometry (VO) systems are inherently limited to single motion by the choice of tracker. This limitation allows for efficient and robust ego-motion estimation in real time, but precludes tracking the multiple motions sought. Shire instead uses a generic tracker and achieves accurate VO and IMO estimates using track analysis. This removes the restriction to a single motion while retaining the real-time performance required for live navigation. We evaluate the system by bounding box intersection over union and ID persistence on a public dataset, collected from an autonomous test vehicle driving in real traffic. We also show the velocities of estimated IMOs. We investigate variations of the system that provide trade offs between accuracy, performance and limitations

Contributions

The author designed the system, designed, recorded and annotated the benchmark, wrote the software for both, and did the majority of the writing.

Paper D: Practical Pose Trajectory Splines With Explicit Regularization

M. Persson, G. Häger, H. Ovren, and P.-E. Forssén, “Practical pose trajectory splines with explicit regularization”, in *International Conference on 3D Vision 2021*, Dec. 2021 . Selected for oral presentation.

Abstract

We investigate spline-based continuous-time pose trajectory estimation using non-linear explicit motion priors. Current regularization priors either linearize the orientation, rely on the implicit regularization obtained from the used spline basis function, or use sampling based regularization schemes. The latter is a special case of a Riemann sum approximation, and we demonstrate when and why this can fail, and propose a way to avoid these issues. In addition we provide a number of novel practically useful theoretical contributions, including requirements on knot spacing for orientation splines, new basis functions for constant velocity extrapolation, and a generalization of the popular P-Spline penalty to orientation. We analyze the properties of the proposed approach using synthetic data. We validate our system using the standard task of visual-inertial calibration, and apply it to stereo visual odometry where we demonstrate real-time performance on KITTI.

Contributions

The author derived the theory, designed the experiments and VO system, wrote the software, and did the majority of the writing.

Paper E: Good Edgels to Track: Beating the Aperture Problem with Epipolar Geometry

T. Piccini, M. Persson, K. Nordberg, M. Felsberg, and R. Mester, “Good edgels to track: Beating the aperture problem with epipolar geometry”, in *Computer Vision - ECCV 2014 Workshops*, 2014, pp. 652–664, ISBN: 978-3-319-16181-5

Abstract

An open issue in multiple view geometry and structure from motion, applied to real life scenarios, is the sparsity of the matched key-points and of the reconstructed point cloud. We present an approach that can significantly improve the density of measured displacement vectors in a sparse matching or tracking setting, exploiting the partial information of the motion field provided by linear oriented image patches (edgels). Our approach assumes that the epipolar geometry of an image pair already has been computed, either in an earlier feature-based matching step, or by a robustified differential tracker. We exploit key-points of a lower order, edgels, which cannot provide a unique 2D matching, but can be employed if a constraint on the motion is already given. We present a method to extract edgels, which can be effectively tracked given a known camera motion scenario, and show how a constrained version of the Lucas-Kanade tracking procedure can efficiently exploit epipolar geometry to reduce the classical KLT optimization to a 1D search problem. The potential of the proposed methods is shown by experiments performed on real driving sequences.

Contributions

The author contributed substantially to the implementation, experiments and assisted with the writing. The author also derived the optimization iteration, though a different derivation was presented in the paper. The authors proposed version will be in the thesis Section 5.7.

Paper F: Robust Accurate Extrinsic Calibration of Static Non-overlapping Cameras

A. Robinson, M. Persson, and M. Felsberg, “Robust accurate extrinsic calibration of static non-overlapping cameras”, in *CAIP*, 2017

Abstract

An increasing number of robots and autonomous vehicles are equipped with multiple cameras to achieve surround-view sensing. The estimation of their relative poses, also known as extrinsic parameter calibration, is a challenging problem, particularly in the non-overlapping case. We present a simple and novel extrinsic calibration method based on standard components that performs favorably to existing approaches. We further propose a framework for predicting the performance of different calibration configurations and intuitive error metrics. This makes selecting a good camera configuration straightforward. We evaluate on rendered synthetic images and show good results as measured by angular and absolute pose differences, as well as the reprojection error distributions.

Contributions

The author proposed to use an additional camera in lieu of more complicated approaches, and assisted with evaluation, implementation and writing.

Other publications

Other notable publications to which I have contributed, but which are not included in this thesis.

- A. Eldesokey, M. Persson, M. Felsberg, and F. Shahbaz Khan, “Uncertainty-aware cnns for depth completion: Uncertainty from beginning to end”, *ICCV 2019 Workshop: Statistical Deep Learning in Computer Vision*, 2019
- A. Eldesokey, M. Felsberg, K. Holmquist, and M. Persson, “Uncertainty-aware cnns for depth completion: Uncertainty from beginning to end”, *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 12 011–12 020, 2020
- G. Häger, M. Persson, and M. Felsberg, “Predicting disparity distributions”, in *2021 IEEE International Conference on Robotics and Automation (ICRA)*, 2021, pp. 4363–4369

VISUAL ODOMETRY

Visual odometry (VO) systems estimate the pose trajectory $\mathbf{P}_\theta(t)$ of a sensor platform with one or more cameras. Point feature visual odometry systems estimate the pose trajectory from the image observations of 3D points on the rigid reference of interest, typically the world. In order to be able to do so, the observations must be sufficient for the trajectory to be observable, *i.e.* constrain the trajectory to an unique optimum.

Unlike structure-from-motion systems in general, visual odometry systems are expected to process the video stream live, generally cannot store many images, and should provide low latency pose estimates. Requiring that the system completes the processing of each new frame before the next one arrives ensures this, and has been the goal of each system in this thesis. The low latency poses in particular are important for the target applications, and as such any time a pose estimate is provided, or a pose trajectory shown, it will always be the poses available before the next frame. This does not prevent the use of parallel processes which improves the map or trajectory. However, any improvements to *e.g.* a benchmark result, would then only be due to improved future frame poses estimates.

This chapter introduces point feature visual odometry from the perspective of the measurement model, and the corresponding loss component, from basic P3P to the loss minimized in Paper A, C and D.

Map representation is discussed in chapter 3, pose trajectories in chapter 4, and tracking in chapter 5.

2.1 Notation

For any symbol f :

- Lowercase f is a scalar,
- f_{NAME} is a named type of f
- $\mathbf{f}$ is a vector
- f_i is the i -th element of the vector $\mathbf{f}$
- $\mathbf{F}$ is a matrix or operator
- $\mathbf{f}(x)$ is a function or operator on x
- $\mathbf{f}^2(x)$ is $\mathbf{f}(x)\mathbf{f}(x)$ if $\mathbf{f}$ is a function, or $\mathbf{f}(\mathbf{f}(x))$ if $\mathbf{f}$ is an operator.
- For any index $i, \dots, f_{i, \dots}$ indexes f by i .
- $\lfloor f \rfloor$ is f rounded down to the nearest integer.

Reserved names:

- $\mathbf{x}$ is a 3d point.
- $\mathbf{x}_{a, \dots}$ is the 3d point of index a .
- $\mathbf{x}_a$ is a 3d point in coordinate system $\mathbf{a}$.
- $\mathbf{P}_{ab}$ is a pose operator such that $\mathbf{x}_a = \mathbf{P}_{ab}\mathbf{x}_b$.
- $\mathbf{p}$ is a camera projection operator *e.g.* (2.2)
- $\mathbf{y}$ is an image observation

2.2 Measurement Model

The projection operator $\mathfrak{p}$ is the function which takes a 3D point $\mathbf{x}$, to image position *i.e.* the observations $\mathbf{y}$. A simple example of which is the ideal pinhole camera model $\mathfrak{p}_{\text{PINHOLE}}$:

$$\mathfrak{p}_{\text{PINHOLE}}(\mathbf{x}) = x_2^{-1} \begin{pmatrix} x_0 \\ x_1 \end{pmatrix} \quad (2.1)$$

where x_i is the i th element of $\mathbf{x}$. Notably $\mathfrak{p}_{\text{PINHOLE}}(\mathbf{x})$ applies to both $\mathbb{R}^3$ and homogeneous 3D point representations. The projection is also limited to points which lie in front of the camera, and typically further restricted to a known Field of View (FOV).

More generally the $\mathfrak{p}$ accounts for the image sensor and lens, as well as the transform from the common sensor platform/device to camera coordinates.

A typical form for $\mathfrak{p}$ used in my work is:

$$\mathbf{y} = \begin{pmatrix} \text{row} \\ \text{column} \end{pmatrix} = \mathfrak{p}(\mathbf{x}_d) = \begin{pmatrix} f_{\text{ROW}}y_{d,1} + p_{\text{ROW}} \\ f_{\text{COL}}y_{d,0} + p_{\text{COL}} \end{pmatrix} \quad (2.2)$$

where

$$\mathbf{y}_d = \mathbf{y}_p(1 + k_0|\mathbf{y}_p|^2 + k_1|\mathbf{y}_p|^4) \quad (2.3)$$

$$\mathbf{y}_p = \mathfrak{p}_{\text{PINHOLE}}(\mathbf{P}_{cd}\mathbf{x}_d) \quad (2.4)$$

The non-linear distortion model *i.e.* (2.3) is lens specific and can be quite complex but is continuous and bijective for the camera-lens configurations of interest. This allows an estimate to be computed of how the image would have looked without the distortion, essentially computing what the corresponding pinhole camera picture would have looked like. This reduces measurement model complexity, and simplify tracking, but requires a trade-off between loss of information and the resolution of the undistorted image. Undistortion is practical for low distortion acute angle lenses but should be avoided for wide angle lenses.

The projection operator parameters $\theta_{\mathfrak{p}}$, here $\{\mathbf{P}_{cd}, f_{\text{ROW}}, f_{\text{COL}}, p_{\text{ROW}}, p_{\text{COL}}, k_0, k_1\}$ in (2.2), can be estimated as part of the VO system. However, they are commonly estimated in advance, with this separate optimization called calibration. Calibrating the camera intrinsics means finding the coefficients of the sensor and lens, while calibrating the extrinsics means finding the transform $\mathbf{P}_{cd}$. Extrinsics are generally found by using a calibration object simultaneously viewed by two cameras. For non-overlapping FOV, this often requires custom, expensive calibration objects. Paper F instead proposes to use a standard chessboard pattern which is moved around, and a third camera.

2.3 Perspective Three Point

The pose can be computed analytically from three or more noise free $\mathfrak{p}_{\text{PINHOLE}}$ observations $\mathbf{y}_i$ of known 3D points $\mathbf{x}_i$, by solving:

$$\mathbf{y}_i = \mathfrak{p}_{\text{PINHOLE}}(\mathbf{P}_\theta \mathbf{x}_i). \quad (2.5)$$

This is known as the Perspective from N Points (PNP) problem. The minimal case of which is the Perspective 3 Point (P3P). P3P is a key component in many VO systems as way to compute an initial pose estimate. The Lambda Twist P3P solver introduced by Paper B is discussed in chapter 3, and substantially improves on the earlier P3P solvers.

P3P has multiple solutions in general, but a fourth point allows us to select an unique correct alternative. We can therefore create a VO system using P3P and four points with known 3D position as follows: In each image, localize the 3D points, and compute the pose using the first three correspondences in P3P, selecting the solution using the fourth point.

P3P assumes pinhole camera measurements, thus, in practice, the observations must first be converted to their pinhole equivalents. This means the camera must be calibrated for P3P to be used.

2.4 Measurement Noise

Tracking, *i.e.* localizing features in an image, is a crucial aspect of any VO system, and will be discussed further in chapter 5. For now, suffice to say the results are noisy, and that this noise must be accounted for. A notable peculiarity of visual odometry is that tracking generally produces a mixture of inliers which can be used in estimation, and outliers, which must be excluded. This leads to the coarse, yet widely applicable, model of Gaussian inliers:

$$\mathbf{y} = \begin{pmatrix} \mathbf{y}_0 + \mathbf{n} & \text{if } \textit{inlier} \\ \mathbf{m} & \text{otherwise} \end{pmatrix} \quad (2.6)$$

where $\mathbf{y}_0$ is the ideal observed position and $\mathbf{n}$ is Independent Identically Distributed (i.i.d) noise $n_i \sim N(0, \sigma_i)$ for σ_i which can be roughly determined given the tracker, camera-lens configuration and target scene. The track is randomly an inlier with a frame specific probability p , and of $\mathbf{m}$ we can say little. This models tracking failures, as well as a wide range of common error sources, including moving objects, reflections and perceptual aliasing.

Unlike inliers, outliers cannot be relied upon to be i.i.d. , in particular with regards to other outliers. Worse still, they are often internally consistent with a different motion. As a result, *e.g.* a moving object covering a significant part of the image, is difficult to account for using per track robust losses.

This motivates a two stage approach, outliers which are inconsistent with the expected motion are discarded, typically by testing their reprojection error against a threshold. This threshold must be selected to avoid discarding inliers which contradict the current estimate, and will therefore have a high false negative rate. Fortunately, the most severe outliers are often easier to identify, but the remainder should still be accounted for. As a result, the use of a well chosen robust loss function [19], in addition to identifying and discarding outliers, is often beneficial. Robust losses are particularly important if the trajectory is uncertain, *e.g.* during initialization.

For notational convenience this thesis will use $\rho(\mathbf{a} - \mathbf{b}) = \sum_i \rho_i(a_i - b_i)$ which both removes outliers, and applies the chosen robust loss. If the inliers elements are not i.i.d. with identical distributions, ρ will also perform the appropriate whitening, and weighting.

2.5 Marker-based Perspective N Point Visual Odometry (PNP-VO)

The noise model allows us to expand the simple P3P-VO system into a marker-based, *i.e.* with known 3D points only, PNP-VO, which accounts for the noise by minimizing the loss:

$$\mathcal{L}(\theta) = \sum_i \rho(y_i - \mathfrak{p}_\theta(\mathbf{P}_\theta \mathbf{x}_i)) \quad (2.7)$$

over the trajectory parameters θ , anew with each frame. This non-convex problem requires a good initialization, *i.e.* one in the convergence basin of the global optimum, to eliminate severe outliers, and converge.

There are two common approaches to finding the initialization. The first approach relies on predicting the pose *e.g.* using an Extended Kalman Filter (EKF) [1] or the motion model regularization approach used in Paper D. The second approach is one based on random sampling consensus *i.e.* a Ransac variant [20]. Ransac finds a good initialization by randomly sampling many minimal subsets of the correspondences, and applying the minimal solver to each. The resulting solutions are scored based on the rest of the correspondences. The top scoring solution is chosen as the initialization and refined over its inlier set using a standard non-linear optimizer. A full discussion of Ransac variants is beyond this work, but suffice to say that it benefits from a good minimal case solver, such as Lambda Twist of Paper B.

Both approaches have their advantages, with the former being more robust against low observability, while the latter relies less on trajectory predictions and is often faster. In practice, most systems use both, either combined, or in different situations, *e.g.* the prediction based PTAM falling back to the

Ransac approach, if localization fails [1]. Another example would be Paper A which uses a coarse motion prediction to eliminate dominant but fast moving objects and equivalent perceptual aliasing, after which Ransac is applied.

The extent to which a VO system relies on temporal correlation significantly changes how the system is designed. On one extreme, reconstruction from a collection of images makes no assumptions, whereas high framerate to dynamic video reconstruction can exploit the strong temporal correlations to significantly improve robustness and accuracy, while reducing computational costs.

Marker-based PNP-VO works quite well, but is limited by the requirement that the 3D points are known in advance. Nevertheless it is used in a number of settings from AR to VR and motion capture to maintenance robots. The 3D points may be specifically placed landmarks, but it is common that the map is generated using either a collection-of-images structure-from-motion, or variations of the method outlined in the next section. The advantage of separating the mapping and localization is that marker-based PNP-VO is more robust and requires substantially less computational resources.

2.6 Bundle Adjustment Visual Odometry

We can triangulate the position of a point found in two or more images if the corresponding camera poses are known. Therefore, by identifying new point features and tracking them the map can be extended into new regions.

This leads us to Bundle Adjustment Visual Odometry (BA-VO): which jointly minimizes:

$$\mathcal{L} = \sum_{i,k} \rho(\mathbf{y}_{i,k} - \mathbf{p}(P_{\theta}(t_k)\mathbf{x}_i)) \quad (2.8)$$

over the trajectory parameters θ and points $\mathbf{x}_i$. The optimization problem is non-linear, and non-convex, and as such, convergence requires a decent initialization of the poses and points.

When the system is running, the pose of a new frame is initialized in the same way as for PNP-VO after which the new points are triangulated using *e.g.* [21]. In the monocular case, the first two frame poses can be found using essential-matrix-Ransac [22].

BA-VO provides accurate trajectories in typical environments, but the map created is usually quite sparse. This can be addressed by strict geometrically supported tracking as done in Paper E, which is discussed in Chapter 5.

Track Management

Careful track management, in terms of outlier rejection, and in terms of selecting new points to track, and restricting which tracks are used in the joint optimization is key to BA-VO.

Long tracks in particular are valuable as they reduce long term drift. There are many techniques to create longer tracks, from geometrically supported tracking, to searching for tracks which could be visible but have been lost, to loop closure. By contrast short tracks may contain insufficient information to identify and remove outliers, and adding such may be detrimental to the estimation accuracy, even if their impact is limited due to a robust loss. A good rule of thumb is to avoid adding a track to the joint optimization before the point has been observed from three poses with a minimum distance between each and the estimate passes each reprojection error test.

In general we can track far more points than we can use during bundle adjustment, and as such, selecting which are the most valuable allow us to maximize accuracy per compute time. Computing the mutual information is computationally infeasible, but there are a number of good heuristics: A track is valuable if it is long, the state well constrained, and its observations are distant from other track observations. As a result, selecting tracks which are well spread throughout the image is beneficial [23], and when two tracks end up too close, one of them can often be discarded. This is important for two reasons: first, the tracks being well spread through the image improves the conditioning of the problem. Second tracks which are too close, *i.e.* the regions their trackers use overlap, are far more likely to violate the i.i.d. assumption.

Optimization

Bundle adjustment problems have notably sparse Jacobians, and a specific structure which can be exploited to substantially reduce computational cost. However, doing so manually is neither required, nor recommended in general [24]. Instead a well tested structurally aware optimizer, such as ceres-solver [25], should be used. Such solvers can both identify and exploit such structure automatically.

Despite the highly efficient structure aware solvers, optimizing over the entire map and every observation with every new frame is prohibitively expensive. Therefore a number of approximations are used to reduce the optimization cost. Common approaches include selective track inclusion, windowed optimization, Key-framing, and the creation of virtual measurements.

Selective track optimization adds a well chosen subset of the tracks to the joint optimization and optimizes the rest separately given the fixed trajectory.

This allows us to maintain far more tracks than can be used in the joint optimization. These tracks are essentially well initialized spares, available for when new tracks are needed.

Windowed optimization assumes that only a subset of the states related to the most recent frames are likely to change, and only includes the observations which can change these states. Key-framing similarly implies selecting a subset of frames which are representative of the trajectory, and discarding the rest.

Virtual Measurements and Information Aggregation

One way to reduce optimization cost is to hold the points constant after the initial triangulation. This makes each pose independent, and reduces the problem to what is essentially sequential PNP-VO. This generally produces accurate relative poses between frames, but is more vulnerable to long term drift. The downside is that later observations of the point do not improve the 3D point estimate, and the information in them is lost.

One popular approach to capture some of the information lost this way is to model the state posterior as a simple distribution which can then be updated, based on the posterior of the latest frame pose estimate, and observation noise. This approach, often called fusion, or marginalization, is very fast [5] and allows older poses to benefit from improved 3D point estimates. The downside is that there is no way to remove a measurement which has been fused without re-estimating the state from scratch, *e.g.* if the measurement is later determined to be an outlier. In essence this approach aggregates the information in a single virtual measurement, typically of the inverse depth. However, there is little reason to restrict ourselves to a single virtual measurement to capture this information, and the use of multiple virtual measurements *e.g.* of reprojection type, can reduce the approximation error caused by the distribution model further.

The measurements themselves represent the information better however, which combined with the high accuracy of the oldest poses motivates and the use of two windows. One short for the poses, and one longer for point states. This approach is used in Paper A to capture more information and allows updating older states to a greater extent, while keeping the short pose update window to keep computational time manageable.

Monocular BA-Vo Scale

The projective measurements are invariant to scale, and as a result a monocular BA-VO loss does not constrain the scale of the map. This means the

scale of the map cannot be estimated globally, and is subject to local drift, which poses a challenge for loop closure. This problem can be alleviated to an extent by strong assumptions on the scene, such as by image-depth estimating deep networks [26]. However, additional sensors that make the scale observable provide a far better result. The cheap option is an accelerometer, but the vision centric approach is another camera.

2.7 Multi Camera Visual Odometry

A sensor platform with multiple rigidly connected synchronized cameras improve observability in many ways. For cameras c which observe $\mathbf{y}_i$ points $\mathbf{x}_i$ at time t_k the loss becomes:

$$\mathcal{L} = \sum_{i,k,c} \rho(\mathbf{y}_{i,k,c} - \mathfrak{p}_c(\mathbf{P}_\theta(t_k)\mathbf{x}_i)). \quad (2.9)$$

When a feature is in simultaneous view of multiple cameras, the known geometry between the cameras can be exploited in the tracking. Paper E shows how this can be performed for two cameras with a generic transform between them. Stereo cameras further assume that the transform is restricted to a translation along the column axis. This allows further simplifications, and as a result, synchronized stereo cameras have long been used as effective inverse depth sensors. Stereo cameras often use acute lenses as this provides better depth accuracy. The accurate depths lead to good translation estimates for VO systems, in particular during high speed, but limits how much of the scene is viewed at once. As a result, VO systems based on an acute angle stereo camera are vulnerable to rapid rotations. A camera with a wide angle lens behave in the opposite way, covering large parts of the scene, but doing so at what amounts to a lower resolution per part. VO systems using wide angle lenses generally robust rotation estimates, but the lower effective resolution limits the translation accuracy. In other words wider FOV is key to dealing with rapid rotations, while higher resolution and overlap helps with high speed. One approach would be to use many stereo camera pairs to achieve the combined benefits of both. Unfortunately this is both computationally costly and expensive.

2.8 Bootstrap Stereo Visual Odometry

The Bootstrap Stereo Visual Odometry of Paper A achieved top rank in the KITTI Odometry Benchmark [9]. The system minimizes the loss (2.9) over a window of the discrete pose trajectory $P[t_k]$ chosen to provide real time performance. To the avid reader of VO, and V-SLAM literature, this system

may sound quite similar to ORB-SLAM or SOFT [2], [3], but it precedes both. There are many parts which contribute to the systems success, but the main contribution is the bootstrap tracker, and this is the component which has been reused the most elsewhere.

The main challenge was the that the KITTI sequences had a significantly lower frame rate to dynamic than VO systems were designed for at the time, necessitating a new tracking approach.

Bootstrap Tracking

Bootstrap tracking starts with no, or a very coarse prediction of the new frames pose, and therefore similarly coarse position predictions. This is used to produce tentative correspondences, which are strictly filtered on appearance in various ways, but not on reprojection error. These tentative correspondences are then used in a framework robust to outliers, *e.g.* Ransac, to find a better pose prediction. The improved prediction is then used to perform guided tracking, the pose re-estimated, and the resulting tracks strictly filtered based on reprojection error, but less so on appearance.

The first step provides a robust way to estimate the pose of a new frame quickly. The second step substantially increases the effective inlier ratio for our tracks, which results in longer tracks, and lower drift.

Bootstrap tracking essentially combines the benefits of unguided tracking, with the high inlier rate, and long tracks of guided tracking, while avoiding the greater downsides of both. The bootstrap tracking by BRIEF [27] descriptor matching suited the frame rate to dynamic of the sequences well, and achieved better results than contemporary tracking by matching and the generative predictive based VO systems.

Optimization Strategy

The system optimizes the poses over a short window chosen to fit computational budget. However, unlike many other systems, including the at the time reigning champion Multi Frame Feature Integration (MFI) [28] system, does not fuse older measurements into a point estimate. Instead older, *i.e.* outside the window, measurements are kept, and the point state estimated over the latest pose estimates, which are held constant together with new variable poses. The reasoning is simple, the poses are highly accurate, but the point estimates are not, and the non-linear observations ensure that any simple posterior model will lose information which is available in the measurements. For low frame rate to dynamics sequences such as KITTI, this approach improves information propagation at a relatively low cost.

Weakness

The main weakness of the original system is the simplistic motion model, and how it was only used for prediction, rather than incorporated with the reprojection errors. It was sufficient at the time, but generalized poorly and was discarded in later versions. The question of how to integrate motion models motivated the investigation into pose trajectory splines, and was addressed by Paper D.

The absence of loop closure in the benchmark version system is intentional, as the trajectory improvements would not be reflective of the low latency pose accuracy. In retrospect this may not have been a strategic choice, as most later systems do use such. In particular as the benchmarks marker for loop closure is largely ignored.

Further Development

The system has since been expanded in many ways, notably to multiple cameras, with and without overlap. This including the multi-camera systems, Ladybug, Occam Omni and the Hilti VO sensor platform [29]. The system has been adapted for, and applied to, several Daimler and Scania experimental vehicles.

2.9 Sequential Hierarchical Ransac (Shire)

Visual odometry estimates the trajectory of a camera in relation to an observed rigid object. This object however, does not need to be the world. The Shire system performs identifies and estimates the trajectory of each rigidly moving object in view, including ego-motion.

Using Stereo BA-VO we can estimate the camera pose trajectory, and thus the position and world velocity for each observed track. Unfortunately, doing so for each track individually leads to a low signal to noise ratio [30], prevents the use of geometrically supported tracking, and limits our ability to identify outliers.

If we can identify which tracks lie on each object, we can estimate them jointly as before. The key idea of Paper C is to do so by first finding the pose of each previously observed object using PNP-Ransac, and assigning all tracks which can be unambiguously assigned to the known rigid objects. After which, PNP-Ransac is used to search for groups of tracks consistent with an additional rigid moving object within the tracks that are unambiguous outliers to the known objects. The system relies heavily on the tracker inlier noise level being known and applying to both the rigid world and any moving object.

Figure 2.1: Sequential Hierarchical Ransac (Shire) results. The world tracks are in red. The identified independently moving objects are shown with bounding box and their associated tracks. This is the result for the purely geometric variant, *i.e.* no deep learning used.

Sample Shire results are shown in Figure 2.1, the shire world speed estimates for the vehicles closely match what is expected, *e.g.* the blue car is matching speed with our vehicle. This holds even for more difficult cases such as the one shown in Figure 2.2. The speed of this car is not known, though it is driving on a 50km/h road. Shire estimates the speed of this car upon detection in this frame as 53km/h , 10 frames later as it leaves view shire estimates its speed as 52km/h .

PNP-Ransac

The PNP-Ransac is, in other words, key to identifying new moving objects in the scene. However, as each object is found and its inliers and ambiguous tracks are removed from consideration, the ratio of tracking failure, to potentially moving objects rises. This in turn causes an exponential rise in the minimum required number of samples drawn and solved with the minimal solver, and is part of what motivated the improved P3P solver of Paper B.

A lower bound for the minimum number of P3P calls can be found as $\frac{\ln(f)}{\ln(1-qp^3)}$ where f is the acceptable failure rate, q is the solver success rate and p is the inlier probability. This is a modification of the standard minimum sampling count for Ransac [20] which accounts for inlier noise using q .

The linear improvement to the P3P speed that the Lambda Twist solver provides, cannot overcome the exponential increase in required samples. Instead the primary advantage comes from the increased accuracy for nearly degener-

Figure 2.2: The car, green, is successfully identified in this frame, using points estimated from disparity in the previous frame. World tracks are shown in red. Small and distant objects provide a challenge to PNP-Ransac, both in terms of low signal to noise, and because the points are more likely to be in a near numerically degenerate configuration.

ate cases. P3P becomes degenerate if the points lie too close together relative to the distance to the camera. This is rarely a problem when searching for an object which covers most of the screen, but the moving objects we are looking for may be small and distant, as shown in Figure 2.2. In such cases the probability of numerically nearing degeneracy increases. The speed improvement the new solver provides would thus be primarily due to a higher q .

Further investigations revealed that the source of the issues the Shire system experienced was primarily not due to poor initialization, but rather due to a mix of poor camera calibration and faulty undistortion software. In the end, the Lambda Twist P3P made for a minor if noticeable improvement. This however highlights the importance of thorough camera calibration as a poor undistortion may not be visible, and may only lead to minor increases in drift in a VO systems operating on the entire image.

GEOMETRY

This chapter discusses the 3D map representation, and improvements made to the Lambda Twist P3P solver of Paper B since its publication.

3.1 The Map Representation

A visual odometry map can be represented in many different ways, with 3D-landmark set and inverse depth images being the most common.

The 3D-landmark approach, assumes there are *e.g.* 3D point landmarks, the position of which can be identified in an image and localized when imaged from nearby poses. The resulting maps are accurate, but sparse. This approach is flexible, fast, and well suited to minimize drift [3] and used in Papers A, C and D.

The inverse depth image approach estimates a pixel-wise inverse depth image for well chosen frames. This results in maps which are denser than those of the 3D-landmark approach. In order to limit computational cost, this approach is usually paired with prediction reliant geometrically supported tracking, Key-framing, and measurement fusion. Inverse depth methods excel in high frame rate to dynamic sequences [5], [7] and feature sparse scenes, but struggles with low frame rate to dynamic sequences. *Inverse* depth is used because it better models the relevant depth range and fits the measurement noise.

The inverse depth image approach can be viewed as the image coordinates implicitly encoding the 3D ray, *i.e.* as a coarse approximation of the point landmark approach with fixed rays. However, if the depth image approach is instead viewed as representing the depth distribution of the cone extending from the camera center through the pixel, the advantages of the model becomes clearer. Rather than using fixed rays, we are estimating 3D surfaces

represented by a distribution. This distribution needs not be uni-modal and this can be accounted for in the loss [18].

3D Point Representation

3D points can be represented as $\mathbb{R}^3$ vectors as in Paper A, or inverse depth with a fixed bearing defined by the pixel grid. The latter representation has much in common with a homogeneous point represented by a $\mathbb{R}^4$ parameter vector, which is used in Paper C and D. For numerical reasons it is wise to keep the homogeneous points at unit length. The homogeneous parametrization has several advantages, including the ability to represent points which lie at infinity using floating point arithmetic.

The $\mathbb{R}^4$ representation allows a point to be smoothly moved from in front of a camera, to behind one, by passing through infinity. This is an advantage in some cases (see Section 5.6), and is otherwise dealt with using a combination of a penalty and existing track management.

In principle, the normalised homogeneous representation is the most expensive to compute. In practice, the computational cost difference between the representations is minor. This is partially because structure aware optimizers separate the computations for the poses and points and the latter become comparably inexpensive.

In practice, the homogeneous point representation is well suited to sparse point feature odometry.

3.2 Lambda Twist P3P

Given three pinhole observations $\mathbf{y}_i$ of known 3D points $\mathbf{x}_i \in \mathbb{R}^3$, P3P finds all poses $\mathbf{P}$ that satisfy:

$$\mathbf{y}_i = \mathfrak{p}_{\text{PINHOLE}}(\mathbf{P}\mathbf{x}_i), \quad (3.1)$$

$$(\mathbf{P}\mathbf{x}_i)_2 > 0. \quad (3.2)$$

The P3P solver of Paper B, Lambda Twist remains the state-of-the-art, and is the default P3P solver for the Open Multiview Geometry Library (Open-MVG) [31]. A great thing about a widely used solver, is that any bugs in the implementation and rare numeric cases, will be found. Since publication, the author has improved the algorithm to address a missing special case. This improvement reduces the number of numeric failures by 90% and removed all incorrect solutions previously output by Lambda Twist in the benchmark, as shown in Table 3.1. The derivation of the alteration is presented here.

Figure 3.1: The pinhole image projections $\mathbf{y}$ lie along the line between the camera center and the 3D points $\mathbf{x}$.

Improved Lambda Twist

The derivation begins as before, and has a single point of departure, before converging again.

The homogeneous visual observations $\mathbf{y}_i$, $|\mathbf{y}_i| = 1$, are unknown, positive scale factors λ_i away from the 3D points in the camera coordinate system $\mathbf{x}_c = \mathbf{P}\mathbf{x}_w = \mathbf{R}\mathbf{x}_w + \mathbf{t}$, as shown in Figure 3.1:

$$\mathbf{y}_i = \rho_{\text{PINHOLE}}(\mathbf{P}\mathbf{x}_i) \implies \quad (3.3)$$

$$\lambda_i \mathbf{y}_i = \mathbf{R}\mathbf{x}_i + \mathbf{t}, \quad i \in \{1, 2, 3\}. \quad (3.4)$$

From which the pose can be eliminated using:

$$\lambda_i \mathbf{y}_i - \lambda_j \mathbf{y}_j = \mathbf{R}(\mathbf{x}_i - \mathbf{x}_j) \implies \quad (3.5)$$

$$|\lambda_i \mathbf{y}_i - \lambda_j \mathbf{y}_j|^2 = |\mathbf{x}_i - \mathbf{x}_j|^2. \quad (3.6)$$

Each combination of $i, j, i \neq j$, gives us a linearly independent quadratic polynomial in the three unknown λ_i :

$$\lambda_i^2 + \lambda_j^2 - 2b_{ij}\lambda_i\lambda_j = a_{ij}, \quad (3.7)$$

where $a_{ij} = |\mathbf{x}_i - \mathbf{x}_j|^2$ and $b_{ij} = \mathbf{y}_i^T \mathbf{y}_j$ or equivalently as:

$$\boldsymbol{\lambda}^T \mathbf{M}_{12} \boldsymbol{\lambda} = a_{12}, \quad \boldsymbol{\lambda}^T \mathbf{M}_{13} \boldsymbol{\lambda} = a_{13}, \quad \boldsymbol{\lambda}^T \mathbf{M}_{23} \boldsymbol{\lambda} = a_{23}, \quad (3.8)$$

where

$$\mathbf{M}_{12} = \begin{pmatrix} 1 & -b_{12} & 0 \\ -b_{12} & 1 & 0 \\ 0 & 0 & 0 \end{pmatrix}, \quad \mathbf{M}_{13} = \begin{pmatrix} 1 & 0 & -b_{13} \\ 0 & 0 & 0 \\ -b_{13} & 0 & 1 \end{pmatrix}, \quad \mathbf{M}_{23} = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 1 & -b_{23} \\ 0 & -b_{23} & 1 \end{pmatrix}.$$

This gives us the homogeneous quadratic polynomials $\boldsymbol{\lambda}^T \mathbf{D}_i \boldsymbol{\lambda} = 0$ for matrices:

$$\mathbf{D}_1 = \mathbf{M}_{12}a_{23} - \mathbf{M}_{23}a_{12}, \quad \mathbf{D}_2 = \mathbf{M}_{13}a_{23} - \mathbf{M}_{23}a_{13}. \quad (3.9)$$

A well chosen linear combination of $\mathbf{D}_i$ allows us to find a linear constraint on $\boldsymbol{\lambda}$ by finding γ such that:

$$\det(\mathbf{D}_0) = \det(\mathbf{D}_1 + \gamma \mathbf{D}_2) = 0, \quad (3.10)$$

which requires one real root to a cubic polynomial in γ .

Since the determinant of $\mathbf{D}_0$ is 0, it will have a zero eigenvalue and the eigenvalue decomposition:

$$\mathbf{S} = \mathbf{E}^T \mathbf{D}_0 \mathbf{E} = \begin{pmatrix} \sigma_1 & 0 & 0 \\ 0 & -\sigma_2 & 0 \\ 0 & 0 & 0 \end{pmatrix}, \quad (3.11)$$

using $\mathbf{E} = \begin{pmatrix} \mathbf{e}_1 \\ \mathbf{e}_2 \\ \mathbf{e}_3 \end{pmatrix}$ such that:

$$\sigma_1 > 0, \quad (3.12)$$

$$\sigma_2 \geq 0, \quad (3.13)$$

$$|\sigma_1| \geq |\sigma_2|. \quad (3.14)$$

Using $\mathbf{p} = \mathbf{E}\boldsymbol{\lambda}$ with $p_1 = sp_2$ in $\mathbf{p}^T \mathbf{S} \mathbf{p} = 0$ gives us $s = \pm \sqrt{\frac{-\sigma_2}{\sigma_1}}$, with each s corresponding to different possible P3P solutions.

Given either s , we have one linear equation:

$$p_1 - sp_2 = (\mathbf{e}_1 - s\mathbf{e}_2)\boldsymbol{\lambda} = \mathbf{w}(s)^T \boldsymbol{\lambda} = 0 \quad (3.15)$$

for $\boldsymbol{\lambda}$, *i.e.* $\sum_i w_i \lambda_i = 0$, and one variable can be eliminated.

In Paper B, we eliminate λ_1 with:

$$\lambda_1 = \frac{w_2}{w_1} \lambda_2 + \frac{w_3}{w_1} \lambda_3. \quad (3.16)$$

However, this did not account for the case that w_1 is 0. We note that $|w|^2 = (\mathbf{e}_1 - s\mathbf{e}_2)^2 = |\mathbf{e}_1|^2 + s^2|\mathbf{e}_2|^2 = 1 + s^2 > 1$ for non-degenerate $\mathbf{D}_0$. Therefore, if $w_1 = w_2 = 0$ then $w_3 > 1$ and $w_3 \lambda_3 = 0$, would imply $\lambda_3 = 0$. This implies that one of w_1, w_2 is not numerically close to zero. Thus, if $|w_2| < |w_1|$, the algorithm remains as before. Otherwise, we change the next step, where $\boldsymbol{\lambda}$ is identified as follows:

Let $\lambda_3 = \tau \lambda_1$ and solve:

$$\begin{pmatrix} w_2 \\ -(w_1 + w_3\tau) \\ w_2 w_3 \tau \end{pmatrix}^T \mathbf{D}_1 \begin{pmatrix} w_2 \\ -(w_1 + w_3\tau) \\ w_2 w_3 \tau \end{pmatrix} = 0 \quad (3.17)$$

for τ . Then using $\mathbf{v} = \begin{pmatrix} 1 & 0 & \tau \end{pmatrix}^T$ for each $\tau > 0$ we get:

$$\boldsymbol{\lambda}^T \mathbf{M}_{13} \boldsymbol{\lambda} = a_{13} \implies \quad (3.18)$$

$$\lambda_1 = \sqrt{\frac{a_{13}}{\mathbf{v}^T \mathbf{M}_{13} \mathbf{v}}}, \quad (3.19)$$

$$\lambda_2 = \left(\frac{w_1}{w_2} + \frac{w_3}{w_2} \tau \right) \lambda_1, \quad (3.20)$$

$$\lambda_3 = \tau \lambda_1. \quad (3.21)$$

Given $\boldsymbol{\lambda}$, the rotation and translation are computed as per Paper B.

3.3 Improved Lambda Twist Results

The improved results are shown in Table 3.1. Notably, all 16 incorrect solutions have been eliminated. The remaining four instances of missing solutions are resolved if the precision is increased from float64 to float128, indicating that they are numerically near degenerate.

Method	Improved	Lambda Twist	Ke	Kneip
GT Found	9999991	9999944	9997237	9990804
Solution found	9999996	9999950	9999663	9999228
No solution	4	50	337	772
Errors	0	16	795145	7325529

Table 3.1: Lambda Twist P3P benchmark results. "Improved" is the improved variant, "Lambda Twist" is the original, and "Ke" and "Kneip" are their respective solvers [32], [33]. The number of missing solutions has decreased from 50 to 4, and incorrect solutions have dropped from 16 to 0.

Errata

Two typos have been found since the publication of Paper B. These have been corrected in the appended version. The reference implementation was correct from the start in both cases.

- Equation (3) in the ECCV derivation lacks a 2, and has been fixed.
- The eigenvectors are ordered to ensure $|\sigma_2| \leq |\sigma_1|$, rather than the opposite.

POSE TRAJECTORIES

So far we have assumed that $\mathbf{P}_\theta(t)$ can represent the relevant trajectories using the parameters θ , which we can optimize over. Ideally, the pose trajectory should be continuous, generic, and computationally efficient. The trajectory representation should allow for both visual measurements and measurements from common auxiliary sensors such as Inertial Measurement Units (IMU) to be used. Further, we want to use motion models and predict the trajectory, and the representation should support this.

Pose trajectory B-splines are a good fit for this. In Paper D, several open questions regarding their design and application are addressed.

This chapter begins by introducing spline based trajectories, how they are regularized, and how to select their hyper-parameters. This is followed by a discussion of frame-wise discrete pose trajectories, such as used in Papers A and C. Frame-wise discrete pose trajectories can be viewed as zeroth or first degree pose trajectory splines with variable knot distances, but often are not.

4.1 Spline Based Pose Trajectories

There are numerous ways to express a continuous pose trajectory, but the combination of a $\mathbb{R}^3$ B-spline and a unit quaternion, *i.e.* versor B-spline [34], is convenient and flexible. For a comprehensive introduction to basis splines and versor splines in general, see [34]–[36].

4.2 Uniform Basis Splines (B-splines)

We will describe basis splines with knots t_i as i , for $i \in \mathbb{Z}$, as the generalizations are trivial and verbose.

Uniform $\mathbb{R}^N$ B-splines of degree n with control points $\mathbf{a}_i$ are defined:

$$\mathbf{s}_n(t) = \sum_i \mathbf{a}_i b_n(t - i), \quad (4.1)$$

where $b_n(t)$ is defined according to:

$$b_0(t) = \begin{cases} 1 & \text{if } t \in [0, 1) \\ 0 & \text{elsewhere,} \end{cases} \quad (4.2)$$

$$b_1(t) = (b_0 \otimes b_0), \quad (4.3)$$

$$b_n(t) = (b_{n-1} \otimes b_0)(t), \quad (4.4)$$

where $(f \otimes g)(t) = \int_{\mathbb{R}} f(\tau)g(t - \tau)d\tau$ is convolution. We will refer to (4.2) as the *local form*, and it is equivalent to the *cumulative form*:

$$\mathbf{s}_n(t) = \sum \mathbf{a}_i b_n(t - i) = \sum \Delta \mathbf{a}_i c_n(t - i), \quad (4.5)$$

where $\Delta \mathbf{a}_i = \mathbf{a}_i - \mathbf{a}_{i-1}$ and

$$c_n(t) = \int_{-\infty}^t b_{n-1}(t) dt. \iff \quad (4.6)$$

$$c_n(t) = \begin{cases} \sum_{i=0}^{n-1} b_n(t-i) & \text{if } t < n \\ 1 & \text{otherwise.} \end{cases} \quad (4.7)$$

Both forms can be efficiently computed for $t \in [i, i + 1)$. Using the adaptive start index $f = \lfloor t \rfloor - n - 1$, we obtain:

$$\mathbf{s}_n(t) = \mathbf{a}_f + \sum_{i=f+1}^{\lfloor t \rfloor} \Delta \mathbf{a}_i c_n(t - i). \quad (4.8)$$

That the spline is locally defined using only a few parameters is called local control. This provides significant computational advantages during trajectory optimization.

Uniform basis splines have $n - 1$ continuous derivatives. Their n -th and latter derivatives are zero everywhere except for the knots.

The Versor Spline

The Kim, Kim and Shin (KKS) unit quaternion [34], *i.e.* versor spline, is a generalization of (4.5). The control points $\mathbf{k}_i$ are versors and the operations are replaced by their rotation equivalents, *i.e.* addition with quaternion multiplication and control point weighting by exponentiation. The Δ operator for unit quaternions thus becomes $\Delta \mathbf{k}_i = \mathbf{k}_{i-1}^* \mathbf{k}_i$. Using $\mathbf{w}_i = \Delta \mathbf{k}_i$ for brevity the KKS is defined as:

$$\mathbf{q}_n(t) = \mathbf{k}_F \prod_{i=F}^{\infty} \mathbf{w}_i^{c_n(t-i)} \quad (4.9)$$

and computed efficiently as:

$$\mathbf{q}_n(t) = \mathbf{k}_f \prod_{i=f+1}^{\lfloor t \rfloor} \mathbf{w}_i^{c_n(t-i)} \quad (4.10)$$

for $f = \lfloor t \rfloor - n - 1$, as in (4.8), and similarly has local control. In practice, the expression is computed recursively, which also benefits the computation of the derivatives.

For a versor in scalar-vector form, $\mathbf{q} = (r, \mathbf{v})$, we define the scalar exponent power and logarithm as:

$$\mathbf{q}^\alpha = \left(\begin{array}{c} \cos(\theta\alpha) \\ \sin(\theta\alpha) \frac{\mathbf{v}}{|\mathbf{v}|} \end{array} \right), \quad (4.11)$$

$$\log(\mathbf{q}) = \left(\begin{array}{c} 0 \\ \theta \frac{\mathbf{v}}{|\mathbf{v}|} \end{array} \right), \quad (4.12)$$

where

$$\theta = \begin{cases} \text{atan2}(|\mathbf{v}|, r) & r \geq 0 \\ \text{atan2}(-|\mathbf{v}|, -r) & \text{otherwise,} \end{cases} \quad (4.13)$$

which selects the shortest path between control points.

Versor splines have $n - 1$ continuous derivatives. The n -th and latter derivatives are only discontinuous in the knots, but unlike real splines are non-zero between the knots.

Versor Spline Representative Power

The path ambiguity resolved by Eqn (4.13) limits the versor derivative, as the maximum distance becomes limited to a single revolution per knot. This leads to the constraint shown in Paper D: $\Delta t_i: |\boldsymbol{\omega}(t)| \leq \pi \Delta t_i^{-1}$. Thus, for a spline to be able to express $\boldsymbol{\omega}(t)$, its knot distance must satisfy:

$$\Delta t_i \leq \pi |\boldsymbol{\omega}(t)|^{-1}. \quad (4.14)$$

This is a necessary, but not sufficient, condition for the spline to be able to express a certain $\boldsymbol{\omega}(t)$. Similar constraints can be derived for the continuous higher derivatives.

B-Spline Derivatives

The non-continuous derivatives of the B-spline basis functions are often not properly defined in literature. This has led to the widespread misconception that they are not defined and, as a result, underutilized. However, as presented in Paper-D:

$$\frac{\partial}{\partial t} b_0(t) = \delta(t) - \delta(t-1), \quad (4.15)$$

where

$$\int_a^b \delta(t-i) f(t) dt = f(i) \text{ if } i \in [a, b], \quad (4.16)$$

which, combined with standard convolution theorems such as $\frac{\partial}{\partial t}(a(t) \otimes b(t)) = (a(t) \otimes \frac{\partial}{\partial t} b(t))$, gives the derivative:

$$\frac{\partial}{\partial t} \sum_i \mathbf{a}_i b_n(t-i) = \sum_i \Delta \mathbf{a}_i b_{n-1}(t-i). \quad (4.17)$$

The well defined derivative has two practical implications, which apply to two common cases.

The first is that measurements of derivatives higher than the spline degree can be included in the cost using a well chosen observer, though care needs to be taken to avoid a loss of local control.

The second is that a common regularizer class can be substantially simplified. For instance, given a second degree spline $\mathbf{s}(t)$ with white Gaussian accelerations, the regularizing cost can be derived using partial integration and (4.15)

and (4.17):

$$\int_v \ddot{\mathbf{s}}^2 dt = [\dot{\mathbf{s}}\ddot{\mathbf{s}}]_v - \int_v \dot{\mathbf{s}}\dot{\mathbf{s}}^{(3)} dt = \quad (4.18)$$

$$[\dot{\mathbf{s}}\ddot{\mathbf{s}}]_v - \int_v \dot{\mathbf{s}} \sum \Delta^2 \mathbf{a}_i \dot{b}_0(t-i) dt = \quad (4.19)$$

$$[\dot{\mathbf{s}}\ddot{\mathbf{s}}]_v - \sum_{i \in v} \dot{\mathbf{s}}(i) \Delta^3 \mathbf{a}_i = \quad (4.20)$$

$$[\dot{\mathbf{s}}\ddot{\mathbf{s}}]_v - \sum_{i \in v} \Delta \mathbf{a}_{i-1} \Delta^3 \mathbf{a}_i, \quad (4.21)$$

where dots, *e.g.* $\dot{\mathbf{s}}$, are used for time derivatives.

This approach is remarkably simple compared to alternative derivations which do not utilize the derivative (4.15). For instance, consider the one presented in, *e.g.* Furgale et al. [37] 2015, which, despite compact notation, is several pages long.

4.3 B-Spline Integrals

The supplementary material of Paper D presents a simpler way to integrate B-splines, which is repeated here. This is useful in many cases, including the approach taken in (4.18).

As the integral of a B-spline is a B-spline of one degree higher, we obtain:

$$\int \sum \mathbf{a}_i b_n(t-i) dt = \sum \boldsymbol{\mu}_i b_{n+1}(t-i) = \sum \Delta \boldsymbol{\mu}_i c_{n+1}(t-i), \quad (4.22)$$

and using (4.6)

$$\int \sum \mathbf{a}_i b_n(t-i) dt = \sum \mathbf{a}_i c_{n+1}(t-i), \quad (4.23)$$

we get:

$$\sum \mathbf{a}_i c_{n+1}(t-i) = \sum \Delta \boldsymbol{\mu}_i c_{n+1}(t-i). \quad (4.24)$$

Thus, we have:

$$\mathbf{a}_i = \Delta \boldsymbol{\mu}_i \implies \quad (4.25)$$

$$\boldsymbol{\mu}_i = \mathbf{a}_i + \boldsymbol{\mu}_{i-1}. \quad (4.26)$$

The integration constant K is baked into $\boldsymbol{\mu}_i$ and defined by the extrapolation model. For standard B-splines, $\boldsymbol{\mu}_{i < F} = 0$, which leads to:

$$\boldsymbol{\mu}_i = \sum_{k \in [F, i]} \mathbf{a}_k. \quad (4.27)$$

This approach can be applied to compute any order integral.

Figure 4.1: Extrapolating splines

4.4 B-Spline Endpoints and Extrapolation

In principle, the control points are assumed to exist, extending to infinity. In practice, a finite range is used, with missing values assumed to be, *e.g.* zero. This can result in severe boundary effects. Paper D presents a new class of extrapolating basis splines, which alleviate this problem. The spline has finite control points $\mathbf{a}_i$, $i \in [B, E]$ yet defines the spline on $\mathbb{R}$. The scalar case is shown in Figure 4.1b, but the method generalizes to $\mathbb{R}^n$ and versor splines.

The new extrapolation functions of degree n shown in Figure 4.1a are:

$$d_n(t) = \int c_{n-1}(t)dt \quad \text{and} \quad (4.28)$$

$$r_n(t) = 1 - d_n(n+1-t), \quad (4.29)$$

and the new basis spline is:

$$\begin{aligned} \mathbf{s}_n(t) = & \mathbf{a}_B + \Delta \mathbf{a}_{B+1} r_n(t-B) + \\ & + \sum_{i=B+2}^{E-1} \Delta \mathbf{a}_i c_n(t-i) + \Delta \mathbf{a}_E d_n(t-E). \end{aligned} \quad (4.30)$$

We then replace linear space operations in (4.30) with corresponding quaternion operations to obtain:

$$\mathbf{q}_n(t) = \mathbf{k}_B \mathbf{w}_{B+1}^{r_n(t-B)} \left[\prod_{i=B+2}^E \mathbf{w}_i^{c_n(t-i)} \right] \mathbf{w}_E^{d_n(t-E)}. \quad (4.31)$$

This spline is parameterized by its control points $\{\mathbf{k}_i\}_B^E$, with the end-pairs $(\mathbf{w}_{B+1}, \mathbf{w}_E)$ defining extrapolating angular velocities. Similar to the $\mathbb{R}^N$ case, this smoothly converges to a constant angular velocity and maintains the continuity properties. The solution is convenient to use in practice as only the control point lookup and basis must be modified.

4.5 Motion Models

Motion models are ubiquitous in robotics, and they serve two important purposes. The first is that they incorporate prior information regarding the expected trajectory. The second is that they improve observability, *i.e.* aiming to ensure the optimal point estimate will be unique.

This can be viewed as incorporating prior information in a maximum likelihood framework: Maximum likelihood fitting of a spline $\mathbf{s}(t, \Theta)$ implies minimizing a loss over the observations $\mathbf{y}_l$ made at times t_l :

$$\mathcal{L}_{\text{OBS}} = \sum_l \rho(\mathbf{y}_l - \mathbf{h}(\mathbf{s}(t_l, \Theta))), \quad (4.32)$$

where ρ is the negative log of the error probability density and $\mathbf{h}$ is a measurement function. For e.g. the assumption of Gaussian errors, we have $\rho(\epsilon) = |\epsilon|^2$. Given an independent prior $\mathcal{L}_{\text{REG}}$ with a prior weight λ we get:

$$\mathcal{L} = \mathcal{L}_{\text{OBS}} + \lambda \mathcal{L}_{\text{REG}}(\Theta). \quad (4.33)$$

the minimum of which is a *maximum a posteriori* point estimate. In principle the full posterior can be computed as well. However, the non-linear nature of rotations and visual observations make it multi-modal and non-trivial in general. This makes computing the full posterior intractable in practice.

Equivalently we can view $\mathcal{L}_{\text{REG}}$ as arising from an observation by a virtual sensor. In principle the two views are equivalent, but where the maximum likelihood estimation frameworks distinguish between measurements, state prior, and loss regularizers, the latter simply considers all as measurements. Further, as a state can only have one prior, it is common for state priors to be approximated using a single virtual measurement. However, if the state prior is approximated, then additional information can be available which could be described using additional virtual measurements. That is, calling one virtual measurement "the state prior" has self limiting connotations, which the virtual measurement perspective avoids. Similarly, the latter needs not describe the prior explicitly, but may simply be observations of it *e.g.* projections of a 3D point from a few poses, rather than a 3D Gaussian.

Differential Motion Models

Probabilistic differential motion models are a powerful and practical class of motion models. They are able to express constraints which arise from kinematics, as well as intuitive notions such as smoothness. Simple derivative regularizers correspond to smooth functions *e.g.*

$$\mathcal{L}(\Theta) = \int \left\| \frac{\partial^m \mathbf{s}(t, \Theta)}{\partial t^m} \right\|^2 dt. \quad (4.34)$$

This can be interpreted as an expectation that the chosen derivative is i.i.d. Gaussian with zero mean, and has an analytic primitive which can be efficiently computed and optimized over.

Similarly it is common to regularize orientation using derivatives of the angular velocity $\boldsymbol{\omega}(t)$

$$\mathcal{L}(\Theta) = \int \left| \frac{\partial^m \boldsymbol{\omega}(t)}{\partial t^m} \right|^2 dt. \quad (4.35)$$

with a similar interpretation as (4.34), but lacks an analytical primitive for degrees above 1.

More advanced motion models are derived from application specific kinematics and rarely have analytic primitives.

Generalized P-spline Penalty

P-Spline penalties are fast and practical when little is known about the signal except that it is smooth. The P-spline regularizer [38]:

$$\mathcal{L}_P^m(\Theta) = \sum_i (\Delta^m \mathbf{a}_i)^2 \quad (4.36)$$

is generalized to orientation p-splines in Paper D using the versor Δ :

$$\mathcal{L}_P^m(\Theta) = \sum_i |\Delta^m \mathbf{a}_i|_{\text{GEODESIC}}^2. \quad (4.37)$$

Integral Cost Approximation

In order to optimize over cost terms which are integrals, we must be able to either analytically evaluate them, or approximate. It is intuitive to approximate integrals of smooth integrands using Riemann sums, but the sampling rate needs to be kept low to minimize computational cost.

The key observation we make in Paper D is that the integral costs over-determine a subspace of spline parameters, and that the sample approximation should do likewise. Unless this condition is met, the optimizer may over-fit to the samples to perfectly satisfy the regularizer. The minimum which avoids this depends on the integrand, and little can be said of general non-linear costs. However, for a wide range of integrands, an upper lower bound for the minimum required can be found. In practice, if the spline is sufficient to describe the dynamic of the model within some acceptable tolerance, this bound is also sufficient within a similar tolerance.

The simple case of $K = \int_I (s(t) - o(t))^2 dt$ where s is a spline, and o is some function, is illustrative. In order for the estimate $s(t)$ to be determined by K ,

$n+1$ samples per knot are sufficient, and $n+2$ samples per knot overdetermines it similar to the integral. In particular, if $o(t)$ is some function which can be expressed by the spline $s(t)$ with reasonable accuracy the approximation will be good. If not, the spline cannot express the observations, which indicates a bigger problem, and there are no guarantees that a higher sample rate will improve the estimate. This leads to the general rule that an evenly sampled $n+2$ observations is widely sufficient, including *e.g.* linear differential models and many common non-linear ones. In practice, using $n+2$ samples per knot is quite cheap, and reducing the number further requires both careful analysis, and border management, as well as accounting for the now potentially uneven approximation error. Paper D shows that this approximation works quite well, and is feasible to use as a regularizer for real time spline trajectory based visual odometry.

In practice, it is also worth remembering that the optimization can have local minima and there is a particular case that most users will likely run into. If a trajectory which contains a full loop is being estimated from an initialization in *e.g.* identity, then most motion models combined with most losses is likely to lead to a local minima where there is a sharp twist between the two halves of the trajectory near its center. This can be addressed by incrementally growing the loss to include more observations. In practice, a good rule of thumb is to not initialize smooth trajectories with initialization that is off by more than $\frac{\pi}{2}$ to avoid this problem.

Pose Prediction

In principle the pose trajectory can be predicted by extending the motion model smoothness penalty beyond the last measurement. This approach is used in the pose trajectory spline VO system of Paper D, and the predictions were good enough to provide the initialization for the next frame assuming a robust loss was used, with an increased threshold. Overall the pose predictions were sufficient one frame ahead, but quickly diverged. This highlights the downside of the point estimate approach, as without the distributions it is difficult to determine to what extent a prediction should be trusted. Nevertheless, the success of the point estimate approach taken in Paper D indicates that this is a topic worth further study.

4.6 Representation Power

The trajectories which can be expressed by the spline form a subspace to the space of pose trajectories. This can be used as a form of spline regularization, but lacks intuitive interpretation. Therefore it is appealing to minimize

such errors, and instead use target specific and intuitive motion models. The possible trajectories expressed by the pose trajectory spline depends on the degree and knot distance. The question then becomes how to select these?

Selecting Spline Degree

Spline degree is typically selected by the properties of the lowest derivative used in the motion model or the measurements.

As an example, acceleration observations with i.i.d. Gaussian noise can be expressed in the cost directly if the spline $s(t)$ is of degree ≥ 2 :

$$\sum_m (\ddot{s}(t) - a[t_m])^2 \quad (4.38)$$

the advantage of this approach is that it is simple. Further, if a spline $p_{n-2}(t)$ can express $a(t)$ the observations can be expressed save for noise. The rule of thumb, would then be to increase the degree by one or two, as this allows for a higher knot distance while maintaining an acceptable error. This approach is ad hoc, but intuitive and common.

However, it should be noted that it is not necessary for the spline to be of degree ≥ 2 for it to use acceleration measurements, only simpler. Another approach is to reconstruct $a(t)$ from $a[t_m]$ and instead minimize:

$$\int (\ddot{s}(t) - a(t))^2 dt \quad (4.39)$$

which generally works for all degrees, optionally using an observer according to the reconstruction. This approach has significant computational advantages if the measurements are dense compared to the knots, as they generally are for *e.g.* IMU. The downside is that this requires a reconstruction of reasonable accuracy, and the approximation error may need to be accounted for [39]. This approach has significant potential upsides and is an interesting avenue of future research.

Selecting Knot Distance

For an uniform spline of degree n with knot distance $k = 1$, the pose at time t is determined by $n + 1$ knots. This implies that if we use a knot distance of

$$k = \frac{\min_m \Delta t_m}{n + 1} \quad (4.40)$$

where t_m are the measurement times, the spline can exactly fit any sequence of poses, though a motion model is required to make it observable. However,

Figure 4.2: Maximum angle error as a function of knot distance. Also shown is the upper bound for the knot distance indicated by Eqn (4.14), using a lower bound for $\omega(t)$.

the key assumption of visual odometry is that the images are sequential, and generally have a significant overlap.

The maximum angle error for fifth degree angle estimates of the KITTI sequence trajectories for different knot distances are shown in Figure 4.2. The VO experiment of paper D shows that the trajectory can be recreated with sufficient accuracy for VO using 3 frames per knot *i.e.* with 21 times the lower bound. This is useful, because bundle adjustment asymptotically scales $\mathcal{O}(N^3)$ where N is the number of poses, or control points. Implying that optimizing over the pose trajectory spline can be faster than optimizing over the corresponding frame-wise poses.

Non Uniform Knot Distances

One may ask why not use non-uniform knot distances?

There are many reasons not to. A spline expressed by non-uniform knot distances still has an upper bound for the minimum required knot distance with acceptable approximation error which works everywhere. Therefore the advantage would be computational, but optimizing over the knot distances breaks local control, and makes for a very challenging and likely np-complete problem. Greedy heuristics can be employed, such as the one used by Oth et al [40] though it is used for offline batch estimation for good reason.

Explicit Subspace Parametrization and Filter Type Optimizers

The trajectory is generally restricted to a subspace which can be exploited to reduce computational complexity, regularize estimates, and improve convergence basins. The most direct way to do so is through the use of subspace basis parametrization, and pose trajectory splines are one such, though more restrictive ones can be used.

Filter type optimizers implicitly do so within the optimizer, and as a result are robust against the otherwise severe approximation errors of commonly used trajectories. This can lead to confusion as what is written as an explicit subspace basis parametrization in filter literature, *e.g.* rotation is only around some known fixed axis, with a single parameter state v , does not correspond to an explicit subspace basis for non-filter type optimizers. Instead this translates to optimization over a general rotation, with a probabilistic penalty on rotation not around this axis.

B-spline pose trajectory representation can be chosen such that the approximation is comparably mild. The spline approximation error can also be accounted for *e.g.* IMU [41] in some cases. However, accounting for representation approximations in generic ways is difficult and its effects are often unintuitive. In practice it is often simpler to select the representation such that the effect is negligible, and add explicit state models instead.

4.7 Frame-Wise Discrete Pose Trajectories

Frame-wise discrete pose trajectories which consist of a separate pose for each frame, are perhaps the most common trajectory representation, and the one used in Papers A, C, E and F. The approach is flexible, and simple to use if poses alone are required. Such trajectories can be viewed as first or zeroth order pose trajectory splines with variable knot distances, but typically are not. Without the inherently specified trajectory derivatives, motion model smoothing is often absent or ad-hoc. Similarly IMU measurements are typically only used to predict, or fused into a virtual state measurement of a single pose. This is computationally efficient, but severely limits the ability to properly propagate new information. Nevertheless this approach remains popular with global shutter only visual odometry. The comparably poor optimization complexity for high frame-rate to dynamic sequences is often addressed through Key-framing and measurement fusion [1], [5], [7].

TRACKING

Visual trackers find where something is in an image, typically given its position in another image, and visual tracking is a broad topic in its own right. In visual odometry, we are primarily interested in tracking image features that are associated with a simple geometric generator, such as a 3D point. The tracker should be able to identify and track hundreds or thousands of features quickly, and it is important that tracking errors are independent and uncorrelated. A moderate failure rate is acceptable however, and ideally such failures should be identified by the tracker. Multiple possible correspondences can also be used by some visual odometry systems.

This chapter introduces point and line features, feature description, common matching approaches and their trade-offs. The chapter concludes with the authors alternate Good Edgels To Track (GETT) tracking iteration derivation.

5.1 Feature Types

Trackable image features can be broadly classified into two categories, those which can be uniquely localized by local appearance alone, and those for which additional information is required. The archetypal image appearances of which are points and lines respectively. In practice image features lie somewhere in between, and the distinction instead depends on how we attempt to track them.

Point features are simple to work with in many ways, as we can make fewer assumptions and do not need accurate pose predictions or joint optimization over trajectory and correspondence. This in turn allows us to track point features separately from the estimation of other states of interest, as a result they are key to otherwise ill posed tasks such as camera calibration. Line features are far more common, but require good state estimates to be tracked,

typically including the target frame pose. As a result they are more difficult to use, but make VO systems far more robust.

Point features can be identified using point detectors such as FAST [42] and line or edgel detectors such as gradient magnitude or GETT [14]. The detectors provide scores which attempt to rank how likely tracking is to succeed, and serve as a way to reduce the number of potential tracks down to something more manageable. An often crucial step, in particular for sparse tracking, is adaptive-non-maxima-suppression [23]. This ensures features are well spread in the image. The reason is twofold, adjacent tracks are likely to have correlated tracking errors, and distant tracks are more likely to result in a well conditioned optimization problem.

5.2 Feature Description and Matching

The patch around the feature is then used to create a description of their appearance which can be matched. Selecting a description and matching metric has trade-offs between computational performance, invariances, and distinctiveness *i.e.* likelihood that a match will be unique. Sub-pixel precision is also valuable, in particular point estimates, though generally not required for accurate pose reconstructions.

For descriptors which form a smooth error surface, the matching can be a non-linear minimization of appearance descriptor differences over the offset, such as in the KLT [43]. This approach is often fast, provides sub-pixel precision and the final error gradient can be used to weigh the reprojection costs. The downside is the convergence to local minima.

Exhaustive search solves the issue of local minima issue and provides valuable, if costly to use, information on the wider error surface. A good example would be stereo disparity [44]. The downside is that it is computationally expensive, though geometrically supported tracking can alleviate this.

Another approach which might be called tracking by matching works by identifying probable locations, such as the detected corners in another image, computing the descriptor for each and matching these using some metric [27].

For generic tracking, appearance descriptors should be invariant against the expected appearance changes, and distinct, in particular from nearby patches with which it may be confused. This indicates that the best generic approaches would be those that learn the expected appearance changes from large datasets, and adapts to the specific images. This turns out to be the case as they dominate generic tracking [45], though they do so at significant computational cost.

5.3 Image Pyramids

Image pyramids are often employed and serve many purposes. In cases of *e.g.* motion blur, higher levels of the pyramid may remain crisp, allowing the tracker a graceful decline in performance. Tracking on higher levels also provide correspondence predictions for the lower levels. This can be used to improve performance by narrowing the search, at the cost of fine detail with large motions. This works well in practice for visual odometry, as the relatively few features which cannot be tracked this way are simply lost.

5.4 Geometrically Supported Tracking

There are many different sources of appearance changes, but an important one is the movement of the camera. This means that if the camera pose can be predicted, we only require invariance up to the effects of the prediction error. Prediction of where to search for the feature also substantially reduces both tracking cost, and the level of distinctiveness required of the appearance descriptor.

A good example of geometrically supported predictive tracking is the guided KLT of PTAM [1] which predicts position, as well as the patch warp due to pose and the effects of the lens. A slightly less prediction reliant variant is the bootstrap tracking of Paper A, and the tracker of Paper E is a strictly geometrically supported tracker.

Some visual odometry systems take geometrically tracking further, replacing the point observations with an appearance difference in the optimization of the loss [7], [46]. This approach can be remarkably robust to homogeneous scenes, but can be quite costly. This motivates the use of computationally efficient descriptors, such as single pixel intensity, local image gradients, or small patch based binary descriptors, often used in image pyramids to reduce search space. The optimization cost is further cut down through the use of key-frames and fusion of pixel-wise inverse depths. The downside is that the limited perspective invariances such descriptors provide and reliance on prediction generally limit such systems to comparably high frame rate to dynamic scenes.

5.5 Tracking in Practice

The accuracy and robustness of the VO systems are limited by the accuracy and density of the tracking, and therefore crucial to VO design and should be selected based on the target system and expected scenes. The BRIEF-based

tracking by matching, was state-of-the-art at the time of Paper A, and remains fast, but is outperformed in terms of accuracy and robustness by more recent trackers *e.g.* ECO [45].

In practice, the BRIEF-based tracking by matching and KLT tracking, worked well enough for the targeted datasets and sensor platforms, requiring minimal tuning for videos from new scenes or new cameras. These trackers also operate at very high frame rates which simplifies experimentation. This has allowed my research to focus on other parts of the VO pipeline.

5.6 Symmetric Noise Induced Bias

A practical model for tracker noise, is that if it succeeds, the noise is symmetric and i.i.d. However, if tracking fails, the distribution is unknown, but likely to be independent of other non-adjacent tracks.

Symmetric *e.g.* i.i.d. Gaussian noise tracker observations, is an approximation which works well in many cases. However, the model has a side effect which should be accounted for. The probability that the noise makes the observation indicate that the point is behind the camera increases with distance, reaching 50% for points at infinity. The visual odometry system can account for this in a number of ways. However if such points are simply eliminated as outliers before optimization, the VO estimate would become biased.

5.7 Good Edgels To Track - Proper Derivation

Paper E presents a different derivation from the one proposed by the author of this thesis. Both derivations arrive at the same iteration, and the derivation of the author is presented here as it is clearer.

Similar to the stereo case, the Good edgels to track 1D KLT assumes that we have calibrated cameras without lens distortion, and a known pose between two images $\mathbf{P}_{I,J}$ st $\mathbf{x}_I = \mathbf{P}_{I,J}(\mathbf{x}_J) = \mathbf{R}\mathbf{x}_J + \mathbf{t}$. Any point $\mathbf{x}$ observed $\mathbf{q}$ in one image will therefore lie along a line $\mathbf{e}_h = \mathbf{F}\mathbf{q}_h$ in the other, where $\mathbf{F}$ is the fundamental matrix and $\mathbf{e}_h$ the dual homogeneous coordinates of the line. The line can equivalently be described as:

$$\mathbf{p}_0 + \mu \begin{pmatrix} e_2 \\ -e_1 \end{pmatrix} = \mathbf{p}_0 + \mu \mathbf{e}, \quad \mu \in \mathbb{R} \quad (5.1)$$

where $\mathbf{p}_{0h} \sim \mathbf{K}\mathbf{R}\mathbf{K}^{-1}\mathbf{q}_h$ is a point on the line.

Similar to the classic KLT we iteratively minimize the photometric loss

$$\min_{\alpha_k} \sum_{\mathbf{w} \in \mathbf{W}} (I(\mathbf{p}_k + \mathbf{w} + \alpha_k \mathbf{e})) - J(\mathbf{q} + \mathbf{w}))^2 \quad (5.2)$$

where $\mathbf{q}$ is the point in the original image J , and $\mathbf{p}_k$ the offset in the second image I . We do this using the approximation:

$$I(\mathbf{p}_k + \alpha \mathbf{e}) \approx I(\mathbf{p}_k) + \alpha_k \mathbf{e}^T \nabla I(\mathbf{p}_k). \quad (5.3)$$

optimizing over the scalar α_k :

$$\mathcal{L} \approx \sum_{\mathbf{w} \in \mathbf{W}} (I(\mathbf{p}_k + \mathbf{w}) - J(\mathbf{p}_0 + \mathbf{w}) + \alpha_k \mathbf{e}^T \nabla I(\mathbf{p}_k + \mathbf{w}))^2 \quad (5.4)$$

$$= \sum_{\mathbf{w} \in \mathbf{W}} (a(\mathbf{w}) + \alpha b(\mathbf{w}))^2 \quad (5.5)$$

$$\mathcal{L}' = 2 \sum_{\mathbf{w}} b(\mathbf{w})a(\mathbf{w}) + \alpha b(\mathbf{w})^2 = 0 \quad (5.6)$$

$$\alpha_k = - \frac{\sum_{\mathbf{w}} a(\mathbf{w})b(\mathbf{w})}{\sum_{\mathbf{w}} b(\mathbf{w})^2} \quad (5.7)$$

$$\mathbf{p}_{k+1} = \mathbf{p}_k + \alpha_k \mathbf{e} \quad (5.8)$$

Note that the denominator: $\sum_{\mathbf{w}} b(\mathbf{w})^2$ is the GETT cornerness score, which is likely non-zero as the tracked features are chosen by it, and the two patches must overlap significantly for KLT type optimization to be likely to converge.

CONCLUDING REMARKS

The introductory chapters present the published parts of my research on visual odometry along with key insights and practical observations. This chapter concludes the thesis with a few reflections and predictions regarding the future of visual odometry.

My PhD began with what in many ways seems like it should have been the end of the journey. The visual odometry system of Paper A achieving top rank on the key KITTI VO benchmark. The bootstrap VO system raised a number of questions and taught me much of how VO systems can be not just conceptualized, but implemented in code. Rather than chase benchmark rankings, the latter research was often driven by practical applications, and curiosity. I am grateful to have worked in this field as it transitioned from research to widespread industrial application, and it has been a remarkable journey.

Today spline based pose trajectories, in particular of degrees above one, are uncommon, and I believe underutilized. Long term I believe they will dominate, as at their core they are more expressive, simpler to work with, and are already real time. The computational cost of the relatively density of inertial measurements is often cited as a reason that they are avoided, but this assumes that the inertial measurements are not used to reconstruct the inertial signal, *e.g.* using the latest trajectory estimate before optimization, which corresponds to a very cheap cost. Notably this is the approximation used in current fusion type frameworks, except at a slight increase to the cost, the latest trajectory, rather than the trajectory at the time of the measurement, can be used. Further, hardware improvements have already made the spline based pose trajectory systems faster than the discrete pose trajectories were when PTAM used them in 2007. Therefore, I believe they are more likely held back by the needless complexity of overly generic formulations of their descriptions in literature, and unanswered design questions. These in-

cluded how motion models should be integrated, and how a trajectories can be characterized, and predicted. Paper D answered several questions and takes a concrete step with regards to general motion model costs and characterization. Extending the angular velocity knot distance constraint to the corresponding derivatives would go a long way towards further characterizing the pose trajectories the splines can express. Numerous questions remain, but I see significant potential for further use in VO beyond current rolling shutter, and visual inertial batch fusion systems. Long term, I believe that the field will move towards less approximate, more expressive representations, and KKS type pose trajectories are a significant step in this direction.

The development of deep learning changed the field of computer-vision to its core, and it has been successfully applied to tracking, optical flow, stereo, and image retrieval. Nevertheless, visual odometry remains one of the few areas where classical methods still dominate, using deep learning as components, rather than applying it end to end. I expect this will continue to be the case for a long time. I expect the current accuracy issues of deep learning based VO will be overcome fairly quickly, but the real time, low latency, low power requirements of VO will require extraordinary advances to overcome. Today, the time it takes for a simple VO system to produce a pose, including tracking, is better compared to the time it takes to upload an image to a GPU, than it is to the computational cost of any subsequent network. Thus instead of end-to-end deep learning "solving" visual odometry as it has so many other areas, I expect deep learning components will become part of visual odometry systems. Though the line will no doubt be blurred by deep networks with internal optimizers.

The field has moved fast in the past decade, and I expect it will continue to do so. Out of the systems and contributions in the thesis, I expect that Lambda Twist will last the longest. To systematically outperform Lambda Twist will be difficult, and I believe that any method which numerically outperforms it will by necessity take the same approach we did, making such systems decedents, rather than replacements. There are however, still improvements to be made, and interesting questions to answer. Notably including points at infinity, how the solutions are characterized, and numerics. The approach we took to solving the intersection is powerful, and there could be many other minimal problems to which it applies. Perhaps Lambda Twist could be the last major advance in P3P, then again it had been solved for centuries when I started, and there where plenty of interesting things left to explore. One thing I am sure of, I greatly enjoyed working on the problem and whomever advances the problem next will too.

BIBLIOGRAPHY

- [1] G. Klein and D. Murray, “Parallel tracking and mapping for small AR workspaces”, in *Proc. Sixth IEEE and ACM International Symposium on Mixed and Augmented Reality (ISMAR’07)*, Nara, Japan, Nov. 2007.
- [2] R. Mur-Artal, J. M. M. Montiel, and J. D. Tardós, “Orb-slam: A versatile and accurate monocular slam system”, *IEEE Transactions on Robotics*, vol. 31, no. 5, pp. 1147–1163, 2015.
- [3] I. Cvišić and I. Petrović, “Stereo odometry based on careful feature selection and tracking”, in *2015 European Conference on Mobile Robots (ECMR)*, 2015, pp. 1–6. DOI: 10.1109/ECMR.2015.7324219.
- [4] R. A. Newcombe, S. J. Lovegrove, and A. J. Davison, “Dtam: Dense tracking and mapping in real-time”, in *2011 International Conference on Computer Vision*, 2011, pp. 2320–2327.
- [5] J. Engel, J. Sturm, and D. Cremers, “Semi-dense visual odometry for a monocular camera”, in *2013 IEEE International Conference on Computer Vision*, 2013, pp. 1449–1456. DOI: 10.1109/ICCV.2013.183.
- [6] J. Engel, V. Koltun, and D. Cremers, “Direct sparse odometry”, *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Mar. 2018.
- [7] J. Engel, T. Schoeps, and D. Cremers, “Lsd-slam: Large-scale direct monocular slam”, vol. 8690, Sep. 2014, pp. 1–16. DOI: 10.1007/978-3-319-10605-2_54.
- [8] S. Agarwal, N. Snavely, I. Simon, S. M. Seitz, and R. Szeliski, “Building rome in a day”, in *2009 IEEE 12th International Conference on Computer Vision*, 2009, pp. 72–79. DOI: 10.1109/ICCV.2009.5459148.
- [9] A. Geiger, P. Lenz, and R. Urtasun, “Are we ready for autonomous driving? the kitti vision benchmark suite”, in *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2012.

- [10] M. Persson, T. Piccini, M. Felsberg, and R. Mester, “Robust stereo visual odometry from monocular techniques”, in *IEEE Intelligent Vehicles Symposium 2015, Soul, South Korea*, Jun. 2015, pp. 686–691.
- [11] M. Persson and K. Nordberg, “Lambda twist: An accurate fast robust perspective three point (P3P) solver”, in *The European Conference on Computer Vision (ECCV)*, Sep. 2018, pp. 334–349.
- [12] M. Persson and P.-E. Forssén, “Independently moving object trajectories from sequential hierarchical ransac”, in *SCITEPRESS VISAPP 2021: Joint conference on computer vision, imaging and computer graphics theory and applications*, vol. 5, 2021, pp. 722–731.
- [13] M. Persson, G. Häger, H. Ovren, and P.-E. Forssén, “Practical pose trajectory splines with explicit regularization”, in *International Conference on 3D Vision 2021*, Dec. 2021.
- [14] T. Piccini, M. Persson, K. Nordberg, M. Felsberg, and R. Mester, “Good edgels to track: Beating the aperture problem with epipolar geometry”, in *Computer Vision - ECCV 2014 Workshops*, 2014, pp. 652–664, ISBN: 978-3-319-16181-5.
- [15] A. Robinson, M. Persson, and M. Felsberg, “Robust accurate extrinsic calibration of static non-overlapping cameras”, in *CAIP*, 2017.
- [16] A. Eldesokey, M. Persson, M. Felsberg, and F. Shahbaz Khan, “Uncertainty-aware cnns for depth completion: Uncertainty from beginning to end”, *ICCV 2019 Workshop: Statistical Deep Learning in Computer Vision*, 2019.
- [17] A. Eldesokey, M. Felsberg, K. Holmquist, and M. Persson, “Uncertainty-aware cnns for depth completion: Uncertainty from beginning to end”, *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 12 011–12 020, 2020.
- [18] G. Häger, M. Persson, and M. Felsberg, “Predicting disparity distributions”, in *2021 IEEE International Conference on Robotics and Automation (ICRA)*, 2021, pp. 4363–4369.
- [19] J. Barron, “A general and adaptive robust loss function”, Jun. 2019, pp. 4326–4334. DOI: 10.1109/CVPR.2019.00446.
- [20] K. Lebeda, J. Matas, and O. Chum, “Fixing the locally optimized ransac”, Sep. 2012. DOI: 10.5244/C.26.95.
- [21] J. Hedborg, A. Robinson, and M. Felsberg, “Robust three-view triangulation done fast”, in *2014 IEEE Conference on Computer Vision and Pattern Recognition Workshops*, 2014, pp. 152–157. DOI: 10.1109/CVPRW.2014.28.
- [22] J. Hedborg and M. Felsberg, “Fast iterative five point relative pose estimation”, in *2013 IEEE Workshop on Robot Vision (WORV)*, 2013, pp. 60–67. DOI: 10.1109/WORV.2013.6521915.

- [23] S. Gauglitz, L. Foschini, M. Turk, and T. Hollerer, “Efficiently selecting spatially distributed keypoints for visual tracking”, in *Image Processing (ICIP), 2011 18th IEEE International Conference on*, Sep. 2011, pp. 1869–1872. DOI: 10.1109/ICIP.2011.6115832.
- [24] C. Engels, H. Stewénus, and D. Nistér, “Bundle adjustment rules”, Jan. 2006.
- [25] S. Agarwal, K. Mierle, *et al.*, *Ceres solver*, <http://ceres-solver.org>, 2012.
- [26] H. Zhan, R. Garg, C. Weerasekera, K. Li, H. Agarwal, and I. Reid, “Unsupervised learning of monocular depth estimation and visual odometry with deep feature reconstruction”, Jun. 2018, pp. 340–349. DOI: 10.1109/CVPR.2018.00043.
- [27] M. Calonder, V. Lepetit, C. Strecha, and P. Fua, “Brief: Binary robust independent elementary features”, in *Computer Vision – ECCV 2010*, K. Daniilidis, P. Maragos, and N. Paragios, Eds., Berlin, Heidelberg: Springer Berlin Heidelberg, 2010, pp. 778–792.
- [28] H. Badino, A. Yamamoto, and T. Kanade, “Visual odometry by multi-frame feature integration”, in *2013 IEEE International Conference on Computer Vision Workshops*, 2013, pp. 222–229. DOI: 10.1109/ICCVW.2013.37.
- [29] M. Helmberger, K. Morin, N. Kumar, D. Wang, Y. Yue, G. Cioffi, and D. Scaramuzza, *The hilti slam challenge dataset*, 2021. eprint: [arXiv: 2109.11316](https://arxiv.org/abs/2109.11316).
- [30] C. Rabe, *Detection of Moving Objects by Spatio-Temporal Motion Analysis: Real-time Motion Estimation for Driver Assistance Systems*. Südwestdeutscher Verlag für Hochschulschriften, 2012, ISBN 978-3-8381-3219-8, ISBN: 978-3-8381-3219-8.
- [31] P. Moulon, P. Monasse, R. Perrot, and R. Marlet, “OpenMVG: Open multiple view geometry”, in *International Workshop on Reproducible Research in Pattern Recognition*, Springer, 2016, pp. 60–74.
- [32] T. Ke and S. Roumeliotis, “An efficient algebraic solution to the perspective-three-point problem”, in *Computer Vision and Pattern Recognition (CVPR), 2017 IEEE Conference on*, IEEE, 2017.
- [33] L. Kneip, D. Scaramuzza, and R. Siegwart, “A novel parametrization of the perspective-three-point problem for a direct computation of absolute camera position and orientation”, in *CVPR*, 2011, pp. 4546–4553.
- [34] M.-J. Kim, M.-S. Kim, and S. Y. Shin, “A general construction scheme for unit quaternion curves with simple high order derivatives”, in *SIGGRAPH’95*, 1995, pp. 369–376.
- [35] M. Unser, “Splines – a perfect fit for signal and image processing”, *IEEE Signal Processing Magazine*, vol. 16, no. 6, pp. 22–38, 1999.

- [36] C. de Boor, *A Practical Guide to Splines*. Springer Verlag (New York), 1978.
- [37] P. Furgale, C. H. Tong, T. D. Barfoot, and G. Sibley, “Continuous-time batch trajectory estimation using temporal basis functions”, *International Journal of Robotics Research*, vol. 34, no. 14, pp. 1688–1710, 2015.
- [38] P. H. C. Eilers and B. D. Marx, “Flexible smoothing with B-splines and penalties”, *Statistical Science*, vol. 11, no. 2, pp. 89–121, 1996.
- [39] H. Ovrén and P.-E. Forssén, “Trajectory representation and landmark projection for continuous-time structure from motion”, *International Journal of Robotics Research*, vol. 38, no. 6, pp. 686–701, Jun. 2019.
- [40] L. Oth, P. Furgale, L. Kneip, and R. Siegwart, “Rolling shutter camera calibration”, in *IEEE Conference on Computer Vision and Pattern Recognition (CVPR13)*, Portland, Oregon, Jun. 2013, pp. 1360–1367.
- [41] H. Ovrén and P.-E. Forssén, “Spline error weighting for robust visual-inertial fusion”, in *IEEE Conference on Computer Vision and Pattern Recognition*, Salt Lake City, Utah, USA: Computer Vision Foundation, Jul. 2018.
- [42] E. Rosten and T. Drummond, “Machine learning for high-speed corner detection”, in *In European Conference on Computer Vision*, 2006, pp. 430–443.
- [43] B. Lucas and T. Kanade, “An iterative image registration technique with an application to stereo vision (ijcai)”, vol. 81, Apr. 1981.
- [44] H. Hirschmuller, “Stereo processing by semiglobal matching and mutual information”, *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 30, no. 2, pp. 328–341, 2008. DOI: 10.1109/TPAMI.2007.1166.
- [45] M. Danelljan, G. Bhat, F. S. Khan, and M. Felsberg, “ECO: efficient convolution operators for tracking”, in *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, IEEE Computer Society, 2017, pp. 6931–6939. DOI: 10.1109/CVPR.2017.733. [Online]. Available: <https://doi.org/10.1109/CVPR.2017.733>.
- [46] V. Usenko, J. Engel, J. Stückler, and D. Cremers, “Direct visual-inertial odometry with stereo cameras”, in *2016 IEEE International Conference on Robotics and Automation (ICRA)*, 2016, pp. 1885–1892. DOI: 10.1109/ICRA.2016.7487335.

PART II

PUBLICATIONS

PAPER A

ROBUST STEREO VISUAL ODOMETRY FROM MONOCULAR TECHNIQUES

A

M. Persson, T. Piccini, M. Felsberg, and R. Mester, “Robust stereo visual odometry from monocular techniques”, in *IEEE Intelligent Vehicles Symposium 2015, Seoul, South Korea*, Jun. 2015, pp. 686–691

Robust Stereo Visual Odometry from Monocular Techniques

Mikael Persson¹, Tommaso Piccini¹, Michael Felsberg¹, Rudolf Mester^{1,2}

Abstract—Visual odometry is one of the most active topics in computer vision. The automotive industry is particularly interested in this field due to the appeal of achieving a high degree of accuracy with inexpensive sensors such as cameras. The best results on this task are currently achieved by systems based on a calibrated stereo camera rig, whereas monocular systems are generally lagging behind in terms of performance. We hypothesise that this is due to stereo visual odometry being an inherently easier problem, rather than due to higher quality of the state of the art stereo based algorithms. Under this hypothesis, techniques developed for monocular visual odometry systems would be, in general, more refined and robust since they have to deal with an intrinsically more difficult problem.

In this work we present a novel stereo visual odometry system for automotive applications based on advanced monocular techniques. We show that the generalization of these techniques to the stereo case result in a significant improvement of the robustness and accuracy of stereo based visual odometry. We support our claims by the system results on the well known KITTI benchmark, achieving the top rank for visual only systems*.

I. INTRODUCTION

The main distinction we make when discussing visual odometry systems is that between stereo and monocular systems. Due to the difficulties imposed by a single camera setting, monocular visual odometry systems are still hard pressed to compete with stereo systems despite significant improvements in the last few years.

Monocular challenges such as scale estimation: Whether through ground-plane estimation or object recognition is a tough task with inherent uncertainties, requiring long tracks and long optimization windows which can propagate the scale information through the translations over longer time spans. Moving objects present a different challenge by causing outliers which cannot always be identified immediately and necessitate careful maintenance of tracks. Similarly noisy measurements and poor pose estimates further require a robustification of the triangulation and estimation processes. Finally since monocular systems must rely only on the quality of its existing tracks, the initialization of a monocular system must be performed with great care.

Stereo systems by comparison, have a fixed known baseline that can be easily exploited to recover a global metric scale. Though in rare cases using only local data may leave the system vulnerable to distant scenes. Moving objects are, in general, easier to identify for the same reason but suffer

from a similar problem. Noisy tracks cause less problems since they can be readily triangulated at every new couple of frames for verification and new tracks can be added with estimated depth from a single stereo pair. Furthermore, redundancy in the visual information due to the overlapping field of view helps stabilize tracks observed in both images. In essence the problems monocular systems face in every frame for every track are reduced to rare occurrences for the stereo system.

The hypothesis motivating the design of our system is that the methods used in monocular visual odometry are more robust by necessity and would perform well if generalized to the stereo case. In particular we use motion model predicted tracking by matching not dissimilar to the scheme proposed by Song et al [1], delayed outlier identification [2], long optimization windows and robust iterative triangulation.

This work describes the building blocks of our system as well as the general outline. We present a novel way of combining and tuning state of the art components to obtain a new stereo visual odometry system that outperforms the state of the art. Since our target is visual odometry for automotive applications, the many driving sequences in the KITTI odometry benchmark [3] serve as a strong indicator of practical performance.

II. RELATED WORK

Visual odometry is undoubtedly one of the most active topics in computer vision in the last years. Since the seminal work of Moravec [7] more and more research groups became interested in the topic of self-localization of a system relying solely or mainly on visual data. Real time monocular SLAM using commodity components was first achieved by Davison et al with MonoSLAM [8] and the filtering approach dominated the field for four years. But it was PTAM [9] by Klein et al, a bundle adjustment based system, which finally broke the barrier to direct augmented reality applications and piqued the interest of the public in 2007. These two works are still considered among the most important in the field because they showed what was possible to do by relying just on inexpensive cameras for self-localization and mapping. The obvious applications of successful systems attracted the attention of military contractors and many leading industries, especially in the automotive field. This, in turn, sparked an explosion of high quality works on the topic in the last few years. An extensive literature review on the topic is beyond the scope of this paper and we will focus exclusively on a brief overview the most relevant works for automotive applications that are of specific interest for this paper. The

¹Computer Vision Laboratory, Linköping University, Sweden, name.lastname@liu.se

²Visual Sensorics & Inf. Proc. Lab (VSI), C.S.Dept., Frankfurt University, Germany

*At the time of submission 2015-01-30

interested reader can, however, find more complete reviews of the topic in review papers such as [10].

Visual odometry is an extremely complex and difficult problem. Numerous approaches have been proposed and virtually uncountable variants and assumptions have been tried to make the problem easier to treat. We like to cluster the existing systems using four different aspects:

- Feature-based versus direct systems
- Global (loop-closing) versus local systems
- Filter based versus bundle adjustment based systems
- Monocular versus stereo systems

Feature based systems extract keypoints and track or match them in subsequent frames. These matches are then used to compute the egomotion by the means of essential matrix estimation [11], PNP [4], [1] or the trifocal tensor [12]. Direct methods on the other hand operate on the whole images thus producing a dense or semi-dense motion field [13], [14], [15], [16].

Global systems keep track of the complete map built over time so that at any time instant it is possible to identify a previously visited location, thus allowing to correct the current estimate of the trajectory [9], [14]. As argued by Song et al. this is in general not practical for automotive applications [1]. Alternative approaches keeping track solely of recent map information have become more popular in recent years [1], [4], [5], [5], [17].

Many approaches make use of some form of filter to obtain a smooth trajectory for the visual odometry and to reduce the negative effect of noisy measurements [12], [18], [19]. This approach simplifies the fusion of ancillary sensors such as IMUs, but complicates the process to revert associations retroactively [20], [21], [22], [23]. The main alternative to this approach is to instead rely on a bundle adjustment step to refine the map and camera poses by minimizing the total reprojection error [24], [4], [11], [5].

Monocular approaches make use solely of the information provided by a single moving camera, thus information on the scene and the motion can only be recovered up to a global scaling factor without assumptions on the scene [1], [25]. Stereo systems, on the other hand, can rely on the known transformation between the two cameras to extract the metric scale and on the redundancy of the visual data to improve stability and robustness [4], [25], [17], [12], [5], [13].

Comparison between different methods has been made easier recently thanks to a number of free datasets that have been made available [3], [26], [27], [28]. The KITTI dataset in particular is currently the most popular one, partly thanks to the benchmark test made available by the authors [3]. The top performing visual-only systems to date are all stereo based papers [4], [17], [13], [5]. An exception to this rule is given by the work of Song et al. which is among the best scoring systems despite relying on monocular data [1]. This system is a feature based, local method using bundle-adjustment. The system we propose has many affinities with this work, but also exploits the advantages given by a calibrated stereo setup.

III. VISUAL ODOMETRY

This section outlines our visual odometry system and its components. We denote the chain of measurements in a sequence of images and the associated 3D point as a 'track'.

The system processes the stereo sequence as follows:

Algorithm 1 Main Loop

```

1: for each stereo pair do
2:   Features = Extract Features(FAST,BRIEF)
3:   Track and estimate pose
4:   Local bundle adjustment
5:   Add new tracks

```

Initialization of the system differs only in that the motion model is not applied during the first four stereo-pairs of tracking.

A. Feature extraction

A scale pyramid is built for each image in the stereo pair. For each level of the pyramid the FAST [29] corners are extracted and subjected to a corner response, Adaptive Non-Maxima Suppression (ANMS) filter with a fixed radius of five. The pyramid consists of the full size image and a 2/3 subsampling. BRIEF descriptors are computed for each FAST corner at the corresponding level [30].

The ANMS filter both reduces the computational cost and improves estimation by improving the spatial distribution of the tracks [31]. The BRIEF descriptor was chosen due to a small advantage in training set accuracy over the FREAK [32] and ORB [33] descriptors.

B. Tracking

The latest BRIEF descriptor of every recently measured track is searched after in a large window (radius 25 pixels) around its predicted position in the new left image by BRIEF descriptor matching. The track position is predicted using the pose estimate from the motion model and the estimated 3D position of the corresponding point.

Since descriptor matching often results in several potential candidates, we use a two step approach. First, the minimum Hamming distance 2D – 3D correspondences are used to estimate the pose via RANSAC-PNP. Second, the estimated pose is used to guide the matching, selecting the best candidate taking both appearance and re-projection error, thresholded to 3 pixels, into account. Tracks found in the left image are matched into the right in the same way with the same criteria, however we do not require that a right image match is found. Finally every inlier is matched to the right image using descriptor matching, the measurement added to the track if it passes a test on the re-projection error given the known stereo configuration.

If fewer than fifty tracks are found, the result is considered untrustworthy and the system uses the motion model to predict the pose of the current frame and reinitializes.

C. Track Replenishment

We choose to keep ≈ 500 tracks at all times, adding new tracks as needed by the following method. The FAST corners of the left image are ANMS filtered with a fixed radius of 18 pixels removing every corner too close to an existing track or another corner with a higher response strength. The descriptors of the remaining features are then matched to the right image, triangulated and filtered by their re-projection error. Matches are added as candidate tracks. Candidate tracks are searched after in the next stereo pair images and added as proper tracks if they are found and pass the re-projection test and no more than 1000 tracks are already present. Excess tracks shorter than four stereo-pairs are discarded.

D. Pose prediction

We use a constant acceleration model in world coordinates to predict the pose with the added constraint that the car is driving forward i.e. along the optical axis of the camera. Let:

- The position at time t : p_t
- The velocity at time t : v_t
- The acceleration at time t : a_t
- The velocity in the camera coordinates at time t : $v_{c,t}$
- A noise component $n_{x,t} \sim N(0, \sigma^2)$

Model:

$$p_{t+1} = p_t + v_t \delta + a_t \frac{\delta^2}{2} + n_{p,t} \quad (1)$$

$$v_{t+1} = v_t + a_t \delta + n_{v,t} \quad (2)$$

$$a_{t+1} = a_t + n_{a,t} \quad (3)$$

$$(1, 1, 0)v_{c,t} = n_{vc,t} \quad (4)$$

The predictive states i.e. v_t, a_t are found by minimizing $\sum (n_{p,t}^2 + n_{v,t}^2 + n_{a,t}^2 + n_{vc,t}^2)$ over a window of twenty vehicle poses.

E. RANSAC-PNP

We use the P3P of Kneip et al [36] wrapped in the MLESAC [37] loop followed by optimization of the re-projection errors of the inlier set using the *Ceres Solver*. We perform [250 – 1000] RANSAC iterations depending on data.

F. Local Bundle adjustment

The total track re-projection errors are minimized by the *Ceres Solver* [34] over a local window over the track 3D positions and the vehicle poses. The cost contains every measurement of every recently measured track with an average re-projection error below 3 pixels.

Every track failing this test is re-triangulated independently, iteratively removing the worst measurement until the average re-projection error reaches the threshold. We found experimentally that this reduces the total computational cost compared to the use of robust cost functions.

The vehicle poses outside the optimization window which enter the cost are set constant approximating the proper transfer of the information.

- Let x_i be a 3D point feature.
- Let $\varphi : \varphi(x_i) = \frac{1}{x_{i2}} \begin{pmatrix} x_{i0} \\ x_{i1} \end{pmatrix}$
- Let P_c transform from vehicle to camera c coordinates.
- Let P_t transform from world to vehicle at time t .
- Let y_{cti} be a pinhole normalized measurement of x_i by camera c at time t .

We minimize an equivalent to:

$$\sum (y_{cti} - \varphi(P_c P_t x_i))^2 \forall c, t, i \in \text{window} \quad (5)$$

The rotations are parametrized as unit-quaternions. Normalization is maintained by backprojection to the unit sphere.

G. Robust Triangulation

New tracks or tracks which may have been corrupted by outliers need to be triangulated before becoming part of the BA optimization cost function. In the former case to ensure a good initialization and in the latter to improve convergence speed.

A track is triangulated by minimizing $\sum (y_{ct} - \varphi(x_{ct}))^2$ where $x_{ct} = P_c P_t x$. The optimization is initialized by the midway method applied to the two measurements taken the furthest apart, a track which is found behind either camera is moved in front of both. We use iterative minimization of the re-projection error due to its superior accuracy and performance over polynomial methods [35].

IV. EXPERIMENTS

For our tests, we use the publicly available KITTI dataset. This dataset provides ground truth egomotion for the 11 training sequences, furthermore a benchmark is available to test methods on a separate set of test sequences. This benchmark is used to test the methods for the KITTI odometry challenge. The average change in pose per meter is used as error metric. The distribution of the per frame error is computed using the training data ground truth. Since automotive applications require low latency the errors are computed on the estimates directly after the tracking step for each stereo-pair frame.

Our method is currently the top ranked stereo system in the KITTI odometry benchmark [†] under the name *cv4xv1-sc*.

A. Benchmark Results

In this section we present some sample results our system achieved on the KITTI benchmark test sequences.

Figures 1 and 2 show the path reconstructed from our visual odometry system compared with the ground truth data on two test sequences of the KITTI benchmark.

Further test results are available on the KITTI odometry website.

Figures: 3 and 4 Show that our method(CV4X) outperforms the state of the art visual odometry systems. Including the previously top ranked MFI [4], TLBBA [5] and 2FOCC as well as MLM-SFM [1] and even DEMO [6] a monocular system supported by a high end laser depth sensor. The

[†]http://www.cvlibs.net/datasets/kitti/eval_odometry.php (accessed on 30 Jan 2015)

Fig. 1. Reconstructed path for test sequence 11. Ground truth and our method.

Fig. 2. Reconstructed path for test sequence 13. Ground truth and our method.

results show a slight improvement on the rotation estimate and a significant improvement on the translation estimate. Figures 1 and 2 show the trajectory of the vehicle as estimated by our system.

B. Results on the training data

We also provide some results our method achieved on the training set of the KITTI benchmark. Ground truth is provided for these sequences, we therefore evaluated our method on them using the same metrics used for the test set by the KITTI benchmark.

Figures 5 and 6 respectively show the rotation and translation error plots for all the 11 sequences in the KITTI training set.

In figures 7 and 8, we show the distribution of the errors in the training sequences, for rotation and translation respectively.

Its worth noting that the systems recovery method is not tested as no tracking failure occurs in any of the KITTI sequences.

Fig. 3. Comparison of the average KITTI testing translation results

Fig. 4. Comparison of the average KITTI testing rotation results

Fig. 5. Per training sequence rotation errors

Fig. 6. Per training sequence translation errors

Fig. 7. Rotation error distribution

Fig. 8. Absolute Translation error distribution

Fig. 9. Relative Translation error distribution for speeds $> 30\text{km/h}$

C. Time Performance

Similar to the elegant two thread PTAM system, our system parallelizes tracking and mapping. We also use OpenMP and cuda for further parallelization subtasks.

The bundle adjustment iterates for up to 90 ms and the tracking takes on average 140 ms. We believe that further CUDA parallelization should allow the system to run in the full 10 fps of the KITTI dataset video source. We performed the experiments on a 4Ghz core I7x4 and a GTX 770 graphics card.

V. ANALYSIS

The analysis of the results shows that the translation errors vary significantly among the sequences in the training set. In particular for sequence 01, a highway scene with largely distant image areas driving at high speed, the translation estimates are poor. This is most likely caused by the very long distances of the majority of feature points from the cameras. This sequence also has severe perceptual aliasing during a few frames, which cause failures if the motion model tracking constraint is disabled, indicating that the motion prediction improves robustness.

The translation error distribution graphs show a significantly higher noise than the long term drift, this indicates that an error in one frame will be compensated for by opposed error in the next. Further the error is also reduced by the BA optimization. Figure 9 also shows that the error is proportional to speed as expected.

It is also interesting that the error distributions show how the system is able to recover from large PNP errors, up to 2 degrees or nearly 30% presumably surrounded by frames with opposed errors. This may also explain the rather counterintuitive observation that the system is less accurate and robust with a small re-projection threshold such as 1 pixel rather than 3 when evaluated on the training sequences. Though the errors do not cause a tracking failure, they are the main cause of the odd behaviour of the KITTI rotation

error for training sequence 00. The error occurs during rapid rotations which cause the loss of all longer older tracks.

Additionally, our results also show that, though there is a great deal of work aimed at achieving sub-pixel tracking accuracy, this is not necessary for visual odometry when the poses are constrained by hundreds of tracks.

The motion model provides predictions of sufficient quality for its purpose, given the smoothness of the trajectory of a car. Direct inclusion of the motion model in the main cost function, as is common in filtering approaches, holds the promise of further accuracy improvements.

VI. ACKNOWLEDGEMENTS

Research funded in part by: Daimler, Vinnova through grant iQmatic, and ELLIIT & EMC², funded by the Swedish Research Council.

VII. CONCLUSIONS

We have developed a stereo visual odometry system which incorporates several techniques developed for monocular systems and show that it achieves state of the art performance on the KITTI odometry benchmark, outperforming all other published, KITTI ranked, stereo odometry methods.

REFERENCES

- [1] S. Song, M. Chandraker, and C. C. Guest, "Parallel, real-time monocular visual odometry," in *ICRA*, Karlsruhe, Germany, May 6-10, 2013.
- [2] M. Persson, "Online Monocular SLAM: Rittums," Lith-ISY-EX-13/4741-SE, Linköping University, Sweden, 2014.
- [3] A. Geiger, P. Lenz, and R. Urtasun, "Are we ready for autonomous driving? the kitti vision benchmark suite," in *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2012.
- [4] H. Badino, A. Yamamoto, and T. Kanade, "Visual odometry by multi-frame feature integration," in *First International Workshop on Computer Vision for Autonomous Driving at ICCV*, December 2013.
- [5] W. Lu, Z. Xiang, and J. Liu, "High-performance visual odometry with two-stage local binocular ba and gpu," in *Intelligent Vehicles Symposium (IV)*, 2013 IEEE. IEEE, 2013, pp. 1107–1112.
- [6] J. Zhang, M. Kaess, and S. Singh, "Real-time depth enhanced monocular odometry," in *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, Chicago, IL, Sept. 2014.
- [7] H. P. Moravec, "Obstacle avoidance and navigation in the real world by a seeing robot rover," DTIC Document, Tech. Rep., 1980.
- [8] A. Davison, "Real-time simultaneous localisation and mapping with a single camera," in *Computer Vision, 2003. Proceedings. Ninth IEEE International Conference on*, Oct 2003, pp. 1403–1410 vol.2.
- [9] G. Klein and D. Murray, "Parallel tracking and mapping for small ar workspaces," in *Mixed and Augmented Reality, 2007. ISMAR 2007. 6th IEEE and ACM International Symposium on*. IEEE, 2007, pp. 225–234.
- [10] D. Scaramuzza and F. Fraundorfer, "Visual odometry [tutorial]," *Robotics & Automation Magazine, IEEE*, vol. 18, no. 4, pp. 80–92, 2011.
- [11] J. Hedborg, P.-E. Forssén, and M. Felsberg, "Fast and accurate structure and motion estimation," in *Advances in Visual Computing*. Springer, 2009, pp. 211–222.
- [12] B. Kitt, A. Geiger, and H. Lategahn, "Visual odometry based on stereo image sequences with ransac-based outlier rejection scheme," in *Intelligent Vehicles Symposium (IV)*, 2010 IEEE. IEEE, 2010, pp. 486–492.
- [13] C. Forster, M. Pizzoli, and D. Scaramuzza, "Svo: Fast semi-direct monocular visual odometry," in *Proc. IEEE Intl. Conf. on Robotics and Automation*, 2014.
- [14] R. A. Newcombe, S. J. Lovegrove, and A. J. Davison, "Dtam: Dense tracking and mapping in real-time," in *Computer Vision (ICCV), 2011 IEEE International Conference on*. IEEE, 2011, pp. 2320–2327.
- [15] S. Lovegrove, A. J. Davison, and J. Ibanez-Guzmán, "Accurate visual odometry from a rear parking camera," in *Intelligent Vehicles Symposium (IV)*, 2011 IEEE. IEEE, 2011, pp. 788–793.
- [16] J. Engel, T. Schöps, and D. Cremers, "Lsd-slam: Large-scale direct monocular slam," in *Computer Vision-ECCV 2014*. Springer, 2014, pp. 834–849.
- [17] F. Bellavia, M. Fanfani, F. Pazzaglia, and C. Colombo, "Robust selective stereo slam without loop closure and bundle adjustment," in *ICIAP (I)*, ser. Lecture Notes in Computer Science, vol. 8156. Springer, 2013, pp. 462–471.
- [18] J. Montiel, J. Civera, and A. J. Davison, "Unified inverse depth parametrization for monocular slam," *analysis*, vol. 9, p. 1, 2006.
- [19] M. Kaess, A. Ranganathan, and F. Dellaert, "isam: Incremental smoothing and mapping," *Robotics, IEEE Transactions on*, vol. 24, no. 6, pp. 1365–1378, 2008.
- [20] K. Konolige, M. Agrawal, and J. Sola, "Large-scale visual odometry for rough terrain," in *Robotics Research*. Springer, 2011, pp. 201–212.
- [21] C. F. Olson, L. H. Matthies, M. Schoppers, and M. W. Maimone, "Rover navigation using stereo ego-motion," *Robotics and Autonomous Systems*, vol. 43, no. 4, pp. 215–229, 2003.
- [22] E. S. Jones and S. Soatto, "Visual-inertial navigation, mapping and localization: A scalable real-time causal approach," *The International Journal of Robotics Research*, vol. 30, no. 4, pp. 407–430, 2011.
- [23] M. Pollefeys, D. Nistér, J.-M. Frahm, A. Akbarzadeh, P. Mordohai, B. Clipp, C. Engels, D. Gallup, S.-J. Kim, P. Merrell, et al., "Detailed real-time urban 3d reconstruction from video," *International Journal of Computer Vision*, vol. 78, no. 2-3, pp. 143–167, 2008.
- [24] H. Strasdat, J. Montiel, and A. J. Davison, "Real-time monocular slam: Why filter?" in *Robotics and Automation (ICRA), 2010 IEEE International Conference on*. IEEE, 2010, pp. 2657–2664.
- [25] A. Geiger, J. Ziegler, and C. Stiller, "Stereoscan: Dense 3d reconstruction in real-time," in *IV, Baden-Baden, Germany*, June 2011.
- [26] G. Pandey, J. R. McBride, and R. M. Eustice, "Ford campus vision and lidar data set," *International Journal of Robotics Research*, vol. 30, no. 13, pp. 1543–1552, November 2011.
- [27] M. Smith, I. Baldwin, W. Churchill, R. Paul, and P. Newman, "The new college vision and laser data set," *The International Journal of Robotics Research*, vol. 28, no. 5, pp. 595–599, May 2009. [Online]. Available: <http://www.robots.ox.ac.uk/NewCollegeData/>
- [28] P. Koschorek, T. Piccini, P. Oberg, M. Felsberg, L. Nielsen, and R. Mester, "A multi-sensor traffic scene dataset with omnidirectional video," in *Computer Vision and Pattern Recognition Workshops (CVPRW), 2013 IEEE Conference on*. IEEE, 2013, pp. 727–734.
- [29] E. Koster and T. Drummond, "machine learning for high-speed corner detection," in *European Conference on Computer Vision*, vol. "1", "May" "2006", pp. "430–443". [Online]. Available: http://edwardrosten.com/work/rosten_2006_machine.pdf
- [30] M. Calonder, V. Lepetit, M. Ozyual, T. Trzcinski, C. Strecha, and P. Fua, "BRIEF: Computing a Local Binary Descriptor Very Fast," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 34, no. 7, pp. 1281–1298, 2012.
- [31] S. Gauglitz, L. Foschini, M. Turk, and T. Hollerer, "Efficiently selecting spatially distributed keypoints for visual tracking," in *Image Processing (ICIP), 2011 18th IEEE International Conference on*, Sept 2011, pp. 1869–1872.
- [32] A. Alahi, R. Ortiz, and P. Vanderghenst, "Freak: Fast retina keypoint," in *Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on*, June 2012, pp. 510–517.
- [33] E. Rublee, V. Rabaud, K. Konolige, and G. Bradski, "Orb: An efficient alternative to sift or surf," in *Computer Vision (ICCV), 2011 IEEE International Conference on*, Nov 2011, pp. 2564–2571.
- [34] S. Agarwal, K. Mierle, and Others, "Ceres solver," <http://ceres-solver.org>.
- [35] J. Hedborg, A. Robinson, and M. Felsberg, "Robust Three-View Triangulation Done Fast," in *Proceedings: 2014 IEEE Conference on Computer Vision and Pattern Recognition Workshops, CVPRW 2014*, 2014, pp. 152–157.
- [36] L. Kneip, D. Scaramuzza, and R. Siegwart, "A novel parametrization of the perspective-three-point problem for a direct computation of absolute camera position and orientation," in *Proc. of The IEEE International Conference on Computer Vision and Pattern Recognition (CVPR)*, Colorado Springs, USA, June 2011.
- [37] P. H. S. Torr and A. Zisserman, "MLESAC: A New Robust Estimator with Application to Estimating Image Geometry," *Computer Vision and Image Understanding*, vol. 78, pp. 138–156, 2000.

PAPER B

LAMBDA TWIST: AN ACCURATE FAST ROBUST PERSPECTIVE THREE POINT (P3P) SOLVER

B

M. Persson and K. Nordberg, “Lambda twist: An accurate fast robust perspective three point (P3P) solver”, in *The European Conference on Computer Vision (ECCV)*, Sep. 2018, pp. 334–349

Lambda Twist: An Accurate Fast Robust Perspective Three Point (P3P) Solver

Mikael Persson, Klas Nordberg *

Computer Vision Laboratory, Linköping University, Sweden,

Abstract. We present Lambda Twist; a novel P3P solver which is accurate, fast and robust. Current state-of-the-art P3P solvers find all roots to a quartic and discard geometrically invalid and duplicate solutions in a post-processing step. Instead of solving a quartic, the proposed P3P solver exploits the underlying elliptic equations which can be solved by a fast and numerically accurate diagonalization. This diagonalization requires a single real root of a cubic which is then used to find the, up to four, P3P solutions. Unlike the direct quartic solvers our method never computes geometrically invalid or duplicate solutions. Extensive evaluation on synthetic data shows that the new solver has better numerical accuracy and is faster compared to the state-of-the-art P3P implementations. Implementation and benchmark are available on github.

Keywords: P3P, PnP, Visual Odometry, Camera Geometry

1 Introduction

Pose estimation from projective observations of known model points, also known as the Perspective n -point Problem (PnP), is extensively used in geometric computer vision systems. In particular, finding the camera pose (orientation and position) from observations of n 3D points in relation to a world coordinate system is often the first step in visual odometry and augmented reality systems[1,2]. It is also an important part in structure from motion and reconstruction of unordered images [3]. The minimal PnP case with a finite number of solutions requires three ($n = 3$) observations in a nondegenerate configuration and is known as the P3P problem (Figure 1).

We are concerned with the latency and accuracy critical scenarios of odometry on low power hardware and AR/VR. Since both latency and localization errors independently not only break immersion, but also cause nausea, accurate solutions and minimal latency are crucial. As an example application, vision based localization for AR/VR places a few markers/beacons on a target, which are then found using a high speed camera. Ideally we would then solve the pose directly on chip without sending the full image stream elsewhere, mandating minimal cost. Further, because the markers are placed on a small area and the camera is of relatively low resolution, the markers are close to each other, meaning numerical issues due to near degenerate cases are common and the algorithm must be robust. The experiments will show that we have made substantial progress on both speed and accuracy compared to state-of-the-art.

* name.surname@liu.se

Surveying the literature we find that P3P solvers are either direct or triangulating. Triangulating methods first triangulate the points in the camera coordinate system using a pose invariant, leaving only distances as unknowns and then solve for the pose. In this case the rotation is solved for as either a quaternion or $\mathbf{R} \in SO(3)$ depending on end user preference. This allows the geometric feasibility constraints, i.e. each point must lie in front of the camera, to limit the solutions prior to computing the pose. In contrast, direct methods parametrize the pose in the input coefficients using a projective invariant. Therefore, they have to apply the feasibility constraint after the solutions are found, as a post processing step.

To our knowledge, all direct methods, including state-of-the-art [4,5], are based on finding the four roots of a quartic. This requires complex arithmetics and root polishing to achieve high numerical accuracy. In contrast, triangulating methods can find all P3P solutions by diagonalizing a three by three matrix. Further, the methods by Kneip and Ke output $\mathbf{R} \in SO(3)$, which if unit quaternion representation is desired requires careful conversion. Thus, triangulating methods have a potential advantage in terms of numerical complexity and accuracy. This motivates us to revisit the P3P problem. To this end we derive a novel triangulating P3P solution designed to provide high numerical accuracy and computational performance. Unlike earlier approaches based on similar pose invariants, we use a novel solution path. This allows us to discard infeasible and duplicate solutions at an earlier stage, thereby saving computation. We explicitly exploit that only a single real root of the diagonalizing cubic is required. We find this root using Newton’s method with an initializing heuristic. This improves the numerical accuracy and again saves computation.

We believe that the main strength of our algorithm is the relative numerical stability of solving for one root of a cubic compared to the multiple iterative solvers used in the solution of a quartic. Note that while discarding invalid and duplicate solutions in advance saves us time, there is another more subtle problem which this our solution avoids. Note that the numeric accuracy of quartic solver roots decrease severely with increasing root multiplicity. Because such roots correspond to duplicate or near duplicate solutions and because such duplicates are common see Section 4.4, this reduces the numerical accuracy of the quartic based solvers beyond what might otherwise be expected. Further this predicts the behavior seen in the experiments where a incorrect solution found by Ke’s solver will be refined to a duplicate root with further iterations. Since we compute the single root we need iteratively, the multiplicity of the cubic does not significantly affect the numerical accuracy of our solver. Further, since the different roots of the cubic do not correspond to different or duplicate solutions, higher multiplicities are rare. Finally, the initialization used makes it very likely that the root we converge to is the one with the best numerical properties.

Although grounded in geometry, the proposed method is derived using methods from linear algebra. The method is parameterized simply in the signed distance to the three 3D points. Although difficult to compare, we believe that the proposed approach is comparatively simple to understand.

Through extensive experiments we show that our solver achieves superior computational and significantly better numerical performance over prior state of the art.

Fig. 1. The P3P setup, where each pair $\{\vec{x}_1, \vec{y}_1\}$, $\{\vec{x}_2, \vec{y}_2\}$ and $\{\vec{x}_3, \vec{y}_3\}$ are used in the calculation of the camera pose $\mathbf{P} = [\mathbf{R}, \vec{t}]$.

1.1 Related Work

Several methods for solving P3P can be found in the literature. The first solution for P3P was published 1841 by Grunert [6], which demonstrated that P3P has up to 4 feasible solutions. Since then, a large number of solvers have been published, which improve the original formulation in various ways. An overview of several of the relevant P3P algorithms until 1991 is presented in the paper by Haralick et al. [7]. More recent methods can be found in the work by Gao et al. [8], Kneip et al. [5], and by Ke et al. [4].

A common theme in a majority of P3P solvers is that each valid solution is associated with a root of a quartic. What differs between the solvers is how this quartic is formulated from the known data, and how the solution are associated with the roots. To find all valid solutions to P3P these methods thus need to find all real roots to a quartic.

A few of the proposed methods, e.g. the one by Finsterwalder, accounted for by Haralick et al. [7], and the one by Grafarend et al. [9], have observed that pairs of P3P solutions can be associated with the roots of a cubic. This observation has not been given much attention in the literature on P3P. In particular, it has not been discussed in the more recent P3P methods.

In this paper we present a novel P3P solver that, while it shares the projective invariant beginnings with Grafarend et al. [9], follows a different solution path which enables an efficient implementation

2 Problem Formulation

Given a calibrated pinhole camera, three 3D points $\vec{x}_i = (x_i, y_i, z_i)$, and corresponding homogeneous image coordinates $\vec{y}_i \sim (u_i, v_i, 1)$ such that $|\vec{y}_i| = 1$, then:

$$\lambda_i \vec{y}_i = \mathbf{R} \vec{x}_i + \vec{t}, \quad i \in \{1, 2, 3\}, \quad (1)$$

where the rotation $\mathbf{R} \in SO(3)$ together with the translation $\vec{t} \in \mathbb{R}^3$ define the pose of the camera. In short a P3P solver is a function $[\mathbf{R}_k, \vec{t}_k] = \text{P3P}(\vec{x}_{1:3}, \vec{y}_{1:3})$. Depending on the configuration of the points, P3P has up to four solutions.

2.1 Requirements

It is well known that a necessary condition to assure a finite set of solutions, is that neither the 3D points nor the 2D points are collinear[7]. In addition there are two specific requirements any solution should meet. First, they should be real. Second, since the parameters λ_k is the signed distance from the camera center for each 3D point, λ_1, λ_2 , and λ_3 are required to be positive and real. This is a geometric feasibility condition on the solutions, which implies that all three 3D points are “in front of” the camera.

3 Lambda Twist Derivation

In this section we derive the the proposed algorithm for solving P3P. The starting point is (1), and the first step is to eliminate $\vec{t}$ and $\mathbf{R}$, leaving only the signed distance parameters λ_i as unknowns. More precisely, they have to solve a system of three inhomogeneous quadratic equations. As we will see, the solutions to the three inhomogeneous equations can be determined by first reducing the problem to a pair of homogeneous quadratic equations. Solving these homogeneous quadratic equations is isomorphic to finding the intersection of two ellipses in the plane. We diagonalize the elliptic equations by finding a rank 2 linear combination of the constraints. Finding this rank 2 combination requires a single root of a cubic polynomial. In general, this root gives us up to four sets of positive $(\lambda_1, \lambda_2, \lambda_3)$, corresponding to a vector $\vec{\Lambda} \in \mathbb{R}^3$, an element of the “lambda-space”. Finally, for each geometrically feasible set of $\vec{\Lambda}_k$ parameters, we determine a corresponding camera pose $(\mathbf{R}_k, \vec{t}_k)$.

3.1 Pose Invariant Constraints

In principle, the homogeneous image coordinates $\vec{y}_i$ in (1) can be multiplied by an arbitrary non-zero scalar. By doing so, the parameters λ_i have to scale inversely. If the scaling is positive, each λ_i then represents a scaled depth, but the sign rules described in Section 2.1 still apply. In the following, we scale each $\vec{y}_i$ such that $\|\vec{y}_i\| = 1$.

We begin the elimination with the translation $\vec{t}$, by taking the pairwise differences of the three equations in (1), then taking into account that $\mathbf{R} \in SO(3)$ and $\|\vec{y}_i\| = 1$:

$$\lambda_i \vec{y}_i - \lambda_j \vec{y}_j = \mathbf{R}(\vec{x}_i - \vec{x}_j), \implies \quad (2)$$

$$|\lambda_i \vec{y}_i - \lambda_j \vec{y}_j|^2 = |\vec{x}_i - \vec{x}_j|^2 \stackrel{def}{=} a_{ij}, \implies \quad (3)$$

$$\lambda_i^2 + \lambda_j^2 - 2b_{ij}\lambda_i\lambda_j = a_{ij},$$

$$b_{ij} \stackrel{def}{=} \vec{y}_i^T \vec{y}_j.$$

This leaves us with only λ_i as free variables to be determined from the three non-trivial ij i.e. $\{12, 13, 23\}$. This is what we will do next.

3.2 Three Inhomogeneous Quadratic Polynomials

The constraints on the scaled depth parameters λ_i in (3) can be formulated in a more compact way as

$$\vec{\Lambda}^T \mathbf{M}_{12} \vec{\Lambda} = a_{12}, \quad \vec{\Lambda}^T \mathbf{M}_{13} \vec{\Lambda} = a_{13}, \quad \vec{\Lambda}^T \mathbf{M}_{23} \vec{\Lambda} = a_{23}, \quad (4)$$

where

$$\mathbf{M}_{12} = \begin{pmatrix} 1 & -b_{12} & 0 \\ -b_{12} & 1 & 0 \\ 0 & 0 & 0 \end{pmatrix}, \quad \mathbf{M}_{13} = \begin{pmatrix} 1 & 0 & -b_{13} \\ 0 & 0 & 0 \\ -b_{13} & 0 & 1 \end{pmatrix}, \quad \mathbf{M}_{23} = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 1 & -b_{23} \\ 0 & -b_{23} & 1 \end{pmatrix}.$$

There is a geometric interpretation of the variables: $b_{ij} = \vec{y}_i^T \vec{y}_j$ is the cosine of the angle between the projection rays of image point i and j , and a_{ij} is the squared distance between 3D points $\vec{x}_i$ and $\vec{x}_j$. Since we require that the 3D points are not collinear, it follows that $a_{ij} > 0, \forall i, j$.

Some observations can be made from (4). First, we see that if $\vec{\lambda}$ solves these three equations, then so does $-\vec{\lambda}$. However as mentioned in Section 2.1 only solutions where all $\lambda_i > 0$ are of interest. A second observation is that the set of $\vec{\lambda}$ which solves an equation in (4) forms an elliptic cylinder centered on each of the three axes in the lambda-space. Each solution $\vec{\lambda}$ is a point where all three cylinders intersect each other. In general there are 8 such points, taking the sign flip of $\vec{\lambda}$ into account, though some of these intersection points may be complex. As mentioned in Section 2.1, we want to remove complex $\vec{\lambda}$ and also any $\vec{\lambda}$ which does not lie in the “positive octant” of the lambda-space, where $\lambda_1, \lambda_2, \lambda_3 > 0$.

3.3 Two Homogeneous Quadratic Polynomials

A linear combination of Eqn (4) provide a set of homogeneous polynomials which are compactly formulated as

$$\mathbf{D}_1 = \mathbf{M}_{12}a_{23} - \mathbf{M}_{23}a_{12} = \begin{pmatrix} \vec{d}_{11}\vec{d}_{12}\vec{d}_{13} \end{pmatrix}, \quad (5)$$

$$\mathbf{D}_2 = \mathbf{M}_{13}a_{23} - \mathbf{M}_{23}a_{13} = \begin{pmatrix} \vec{d}_{21}\vec{d}_{22}\vec{d}_{23} \end{pmatrix}, \quad (6)$$

$$\vec{\lambda}^T \mathbf{D}_i \vec{\lambda} = 0, \forall i \in \{1, 2\}, \quad (7)$$

where $\vec{d}_{ij}$ is column j of the matrix $\mathbf{D}_i$.

Since (7) are homogeneous polynomials, any requirement on the norm of $\vec{\lambda}$ is lost. By substituting the solution into one of the equations in (4) the proper scale is found. The equations in (7) specify two ellipses in (λ_1, λ_2) if $\lambda_3 = 1$. Thus the solution represents the intersections of the ellipses.

3.4 The Cubic Polynomial

We now turn to the problem of finding $\vec{\lambda}$ that solves (7). For now we assume that $\mathbf{D}_1$ and $\mathbf{D}_2$ are indefinite as the rare cases when this is not true is either trivial or degenerate. In Eq (7), each quadratic form has a solutions set in the form of an elliptic double cone in the lambda-space. These two cones intersect along, at most, four lines. This is true for any quadratic form specified as a linear combination of $\mathbf{D}_1$ and $\mathbf{D}_2$ as well. A special case of such a double cone is a pair of planes, where each plane intersects with two of the lines. Such a degenerate case occurs precisely when the linear combination has rank

2. A plane which includes $\vec{A}$ is then an extra linear constraint in addition to the previous quadratic relations. This observation is key for the proposed solver, and we will next consider how to determine these planes, and how they can be used to find all valid $\vec{A}$.

We form $\mathbf{D}_0 = \mathbf{D}_1 + \gamma \mathbf{D}_2$ that has a corresponding solution space which is simple to determine. We find this $\mathbf{D}_0$ by solving

$$0 = \det(\mathbf{D}_0) = \det(\mathbf{D}_1 + \gamma \mathbf{D}_2). \quad (8)$$

This corresponds to a cubic polynomial in γ :

$$c_3 \gamma^3 + c_2 \gamma^2 + c_1 \gamma + c_0. \quad (9)$$

The four coefficients are given by

$$\vec{c} = \begin{pmatrix} c_3 \\ c_2 \\ c_1 \\ c_0 \end{pmatrix} = \begin{pmatrix} \det(\mathbf{D}_2) \\ \vec{d}_{21}^T (\vec{d}_{12} \times \vec{d}_{13}) + \vec{d}_{22}^T (\vec{d}_{13} \times \vec{d}_{11}) + \vec{d}_{23}^T (\vec{d}_{11} \times \vec{d}_{12}) \\ \vec{d}_{11}^T (\vec{d}_{22} \times \vec{d}_{23}) + \vec{d}_{12}^T (\vec{d}_{23} \times \vec{d}_{21}) + \vec{d}_{13}^T (\vec{d}_{21} \times \vec{d}_{22}) \\ \det(\mathbf{D}_1) \end{pmatrix}. \quad (10)$$

In the special case that either of $\mathbf{D}_1$ or $\mathbf{D}_2$ are semi-definite, or indefinite with one eigenvalue equal to zero, we get $c_0 = 0$ or $c_3 = 0$. In this case, is not necessary to form and solve this cubic, we simply set $\mathbf{D}_0 = \mathbf{D}_1$ or $\mathbf{D}_0 = \mathbf{D}_2$. In the general case, we may still want to avoid being close to a case where $c_3 \approx 0$, as the cubic then becomes numerically unstable. In this case the real root of the inverse polynomial, i.e. $\mu = \gamma^{-1}$, is found instead. In practice these are near non-existent cases and the polynomial is well conditioned.

In general, we can assume that neither c_3 nor c_0 vanish, and the cubic polynomial is well-defined and has one, two, or three distinct roots. Diagonalizing $\mathbf{D}_0$ requires only one real root γ_0 which can be found with any of several standard methods. With γ_0 at hand, we set $\mathbf{D}_0 = \mathbf{D}_1 + \gamma_0 \mathbf{D}_2$.

We recall that $\mathbf{D}_0$ specifies two planes, each intersecting with two distinct lines that includes $\vec{A}$ solving (7). In the case of four such lines, there are *three* ways to specify the two planes. Therefore we should expect the problem of finding the degenerate cone, specified by $\mathbf{D}_0$, to have three solutions. As we have seen, finding this $\mathbf{D}_0$ can be formulated as finding a root of a cubic. Although additional roots provide more constraints on $\vec{A}$, we will in the next step see that one case of $\mathbf{D}_0$ is sufficient for finding all solutions to P3P.

3.5 Diagonalization of $\mathbf{D}_0$

An eigenvalue decomposition of $\mathbf{D}_0$ results in

$$\mathbf{D}_0 = \mathbf{E} \mathbf{S} \mathbf{E}^T, \text{ where } \mathbf{E} = \begin{pmatrix} e_0 & e_1 & e_2 \\ e_3 & e_4 & e_5 \\ e_6 & e_7 & e_8 \end{pmatrix} = (\vec{e}_1, \vec{e}_2, \vec{e}_3). \quad (11)$$

The matrix $\mathbf{E}$ holds an orthogonal basis of $\mathbb{R}^3$ in its columns $\vec{e}_i$, and $\mathbf{S}$ holds the corresponding eigenvalues in its diagonal. Since $\det(\mathbf{D}_0) = 0$, at least one of the eigenvalues are zero, and we can assume $\mathbf{S}$ to have the following form:

$$\mathbf{S} = \mathbf{E}^T \mathbf{D}_0 \mathbf{E} = \begin{pmatrix} \sigma_1 & 0 & 0 \\ 0 & -\sigma_2 & 0 \\ 0 & 0 & 0 \end{pmatrix}, \quad (12)$$

and $\sigma_1 > 0, \sigma_2 \geq 0$. The fact that there is at least one non-zero eigenvalue, and that if there is more than one they have opposite sign, is a general observation. This property holds when a rigid transform relates the observations.

We exploit that we know one eigenvalue of $\mathbf{D}_0$ is zero for a efficient eigenvalue decomposition in Algorithm 2. This algorithm also reorders the eigenvectors to ensure that $|\sigma_2| \leq |\sigma_1|$. This improves numerical performance in later steps.

3.6 Solving for $\vec{A}$

We use the eigenvalue decomposition of $\mathbf{D}_0$ to solve $\vec{A}^T \mathbf{D}_0 \vec{A} = 0$ by first solving the simpler equation $\vec{p}^T \mathbf{S} \vec{p} = 0$ using the substitution $\vec{p} = \mathbf{E}^T \vec{A}$ where $\vec{p} = (p_1, p_2, p_3)^T$. With $p_1 = sp_2$ we find that $s = \pm \sqrt{\frac{-\sigma_2}{\sigma_1}}$ for any p_3 .

Each solution of s gives us a linear relation between $\lambda_1, \lambda_2, \lambda_3$ using $\vec{p} = \mathbf{E}^T \vec{A}$:

$$\begin{aligned} \vec{e}_1 \vec{A} &= p_1 = sp_2, \\ \vec{e}_2 \vec{A} &= p_2, \implies \\ s \vec{e}_2 \vec{A} &= sp_2, \implies \\ \vec{e}_1 \vec{A} - s \vec{e}_2 \vec{A} &= 0, \implies \\ \lambda_1 &= \underbrace{\frac{e_3 - se_4}{se_1 - e_0}}_{w_0} \lambda_2 + \underbrace{\frac{e_6 - se_7}{se_1 - e_0}}_{w_1} \lambda_3 = w_0 \lambda_2 + w_1 \lambda_3. \end{aligned} \quad (13)$$

The two solutions for s gives two possible expressions for λ_1 in Eqn (13).

Next let: $\lambda_3 = \tau \lambda_2$. This implies $\tau > 0$ since we only seek the solutions where $\lambda_i > 0$ which satisfy the geometric feasibility constraint. Inserting $\lambda_3 = \tau \lambda_2$ and Eqn (13) in e.g. $\vec{A}^T \mathbf{D}_1 \vec{A} = 0$ gives

$$\lambda_2^2 \begin{pmatrix} w_0 + \tau w_1 \\ 1 \\ \tau \end{pmatrix}^T \mathbf{D}_1 \begin{pmatrix} w_0 + \tau w_1 \\ 1 \\ \tau \end{pmatrix} = 0. \quad (14)$$

This leads to a quadratic equation in τ : $a\tau^2 + b\tau + c = 0$ with coefficients:

$$\begin{aligned} a &= ((a_{13} - a_{12})w_1^2 + 2a_{12}b_{13}w_1 - a_{12}), \\ b &= (2a_{12}b_{13}w_0 - 2a_{13}b_{12}w_1 - 2w_0w_1(a_{12} - a_{13})), \\ c &= ((a_{13} + a_{12} - a_{12})w_0^2 - 2a_{13}b_{12}w_0). \end{aligned} \quad (15)$$

In summary, for each of the two possible values of s , we get two solutions for τ . This gives up to four solutions. Complex and negative τ are discarded at this point since they will never lead to real and geometrically feasible poses. We denote the surviving solutions as τ_k .

Next we determine λ_{2k} for each τ_k using $\lambda_{3k} = \tau_k \lambda_{2k}$ and Eqn (4). Specifically we use $\vec{A}^T \mathbf{M}_{23} \vec{A}^T = a_{12}$ because it does not depend on λ_1 . The result is

$$\lambda_{2k}^2 \begin{pmatrix} 1 \\ \tau_k \end{pmatrix}^T \begin{pmatrix} 1 & -b_{23} \\ -b_{23} & 1 \end{pmatrix} \begin{pmatrix} 1 \\ \tau_k \end{pmatrix} = a_{23}, \quad \lambda_{2k} > 0, \quad (16)$$

which is solved by $\lambda_{2k} = \sqrt{\frac{a_{23}}{\tau_k(b_{23} + \tau_k) + 1}}$. This gives us a λ_{2k} for each τ_k . Note that $a_{23} > 0$ and $(\tau_k(b_{23} + \tau_k) + 1) > 0$ since $|b_{23}| \leq 1$.

Finally we compute $\lambda_{3k} = \tau_k \lambda_{2k}$ and λ_{1k} from Eqn (13). To summarize, for each τ_k we get a $\vec{A}_k$. So far we have only guaranteed that λ_2 and λ_3 are positive. If $\lambda_{1k} < 0$ then $\vec{A}_k$ is discarded. This ensures that the remaining $\vec{A}_k$ are geometrically feasible.

3.7 Recovering $\mathbf{R}$ and $\vec{t}$

At this point we have a set of up to four geometrically feasible solutions $\vec{A}_k$. For each $\vec{A}_k$, it remains to determine the corresponding camera pose $(\mathbf{R}_k, \vec{t}_k)$. The rotation $\mathbf{R}_k$ can be recovered from $ij \in \{12, 13, 23\}$ in (2), but since the differences of the 3D points that appear in the right hand sides of these equations are linearly dependent, these three equations are of rank two. To increase the rank, we can take the cross product of the entries in the left hand side of the first two equations. This must equal the cross product of the corresponding entries in the right hand side:

$$\vec{z}_1 \times \vec{z}_2 = \mathbf{R} \left((\vec{x}_1 - \vec{x}_2) \times (\vec{x}_2 - \vec{x}_3) \right), \quad (17)$$

where $\vec{z}_1 = \lambda_1 \vec{y}_1 - \lambda_2 \vec{y}_2$ and $\vec{z}_2 = \lambda_2 \vec{y}_2 - \lambda_3 \vec{y}_3$.

The first two equations in (2) together with (17) gives:

$$\mathbf{Y} = \mathbf{R}\mathbf{X}, \quad (18)$$

$$\mathbf{Y} = \begin{pmatrix} \vec{z}_1 & \vec{z}_2 & \vec{z}_1 \times \vec{z}_2 \end{pmatrix}, \quad (19)$$

$$\mathbf{X} = \begin{pmatrix} \vec{x}_1 - \vec{x}_2 & \vec{x}_2 - \vec{x}_3 & (\vec{x}_1 - \vec{x}_2) \times (\vec{x}_2 - \vec{x}_3) \end{pmatrix}, \quad (20)$$

$$\mathbf{R} = \mathbf{Y}\mathbf{X}^{-1}. \quad (21)$$

This solution only provides $\mathbf{R} \in SO(3)$ if the correspondences are exact. This is guaranteed by Eqn (1).

Finally, the translation part of the pose can be solved from any of the three equations in (1):

$$\vec{t} = \lambda_i \vec{y}_i - \mathbf{R} \vec{x}_i. \quad (22)$$

In the end, this produces one pose $(\mathbf{R}_k, \vec{t}_k)$ that solves (1) for each feasible vector $\vec{A}_k$ that is generated by the previous step.

If desired, the corresponding unit quaternions $\vec{q}_k$ can be extracted given the two 3D correspondences in (17), see Appendix A.2. We use the rotation matrix representation to make the algorithm more closely comparable to the alternatives.

Algorithm 1 Lambda Twist P3P

```

1: function MIX( $\vec{n}, \vec{m}$ ) =  $(\vec{n}, \vec{m}, \vec{n} \times \vec{m})$ 
2: function P3P( $\vec{y}_{1:3}, \vec{x}_{1:3}$ )
3:   Normalize  $\vec{y}_i = \vec{y}_i / |\vec{y}_i|$ 
4:   Compute  $a_{ij}$  and  $b_{ij}$  according to (3)
5:   Construct  $\mathbf{D}_1$  and  $\mathbf{D}_2$  from (5) and (6)
6:   Compute a real root  $\gamma$  to (8)-(10) of the cubic equation
7:    $\mathbf{D}_0 = \mathbf{D}_1 + \gamma \mathbf{D}_2$ 
8:    $[\mathbf{E}, \sigma_1, \sigma_2] = \text{EIG3X3KNOWN0}(\mathbf{D}_0)$ . See Algorithm 2
9:    $s = \pm \sqrt{\frac{-\sigma_2}{\sigma_1}}$ 
10:  Compute the  $\tau_k > 0, \tau_k \in \mathbb{R}$  for each  $s$  using Eqn (14) with coefficients in Eqn (15)
11:  Compute  $\vec{\Lambda}_k$  according to Eqn (16),  $\lambda_{3k} = \tau_k \lambda_{2k}$  and Eqn (13),  $\lambda_{1k} > 0$ 
12:   $\mathbf{X}_{\text{inv}} = (\text{mix}(\vec{x}_1 - \vec{x}_2, \vec{x}_1 - \vec{x}_3))^{-1}$ 
13:  for each valid  $\vec{\Lambda}_k$  do
14:    Gauss-Newton-Refine( $\vec{\Lambda}_k$ ), see Section 3.8
15:     $\mathbf{Y}_k = \text{MIX}(\lambda_{1k}\vec{y}_1 - \lambda_{2k}\vec{y}_2, \lambda_{1k}\vec{y}_1 - \lambda_{3k}\vec{y}_3)$ 
16:     $\mathbf{R}_k = \mathbf{Y}_k \mathbf{X}_{\text{inv}}$ 
17:     $\vec{t}_k = \lambda_{1k}\vec{y}_1 - \mathbf{R}_k \vec{x}_1$ 
18:  Return all  $\mathbf{R}_k, \vec{t}_k$ 
    
```

3.8 Implementation Details

We find the diagonalizing γ as a root of the cubic in Eqn (9) by using Newton-Raphson’s method initialized using a simple heuristic.

Once the $\vec{\Lambda}_k$ have been computed they are also refined in accordance with standard praxis[10]. Specifically, we refine the solution using a few verified steps of Gauss-Newton optimization on the sum of squares of Eqn (4). A similar refinement is used in the P3P solver by Ke et al. Note that for both algorithms the accuracy rarely improves after 2 iterations.

This concludes the Lambda Twist P3P algorithm, summarized in Algorithms 1 and 2.

4 Experiments

We have performed three experiments: one to evaluate the numerical accuracy of the proposed method, and two to evaluate the execution time. In order to demonstrate the performance of the proposed method, the experiments were performed on random synthetic data. The proposed method is implemented in C++ and is compared to the state-of-the-art P3P solver by Ke et al. [4], and the P3P solver Kneip et al. [5]. The publicly available C++ implementations of the two state-of-the-art methods have been used. The method by Ke et al. [4] is available as part of OpenCV[11] and the method by Kneip et al. [5] is available at [12]. These solvers both show that they provide superior computational and numerical performance compared to earlier work. The algorithms are compiled with gcc using the same optimization settings as part of the same program. The numerical and time benchmarks are available along with the code on the main authors

Algorithm 2 eig3x3known0

```

1: function GETEIGVECTOR( $\vec{m}, r$ )
2:    $c = (r^2 + \vec{m}_1\vec{m}_5 - r(\vec{m}_1 + \vec{m}_5) - \vec{m}_2^2)$ 
3:    $a_1 = (r\vec{m}_3 + \vec{m}_2\vec{m}_6 - \vec{m}_3\vec{m}_5)/c$ 
4:    $a_2 = (r\vec{m}_6 + \vec{m}_2\vec{m}_3 - \vec{m}_1\vec{m}_6)/c$ 
5:    $\vec{v} = (a_1 \ a_2 \ 1)$ 
6:   Return  $\vec{v}/|\vec{v}|$ 
7: function EIG3X3KNOWN0( $\mathbf{M}$ )
8:    $\vec{b}_3 = \mathbf{M}(:, 2) \times \mathbf{M}(:, 3);$ 
9:    $\vec{b}_3 = \vec{b}_3/|\vec{b}_3|$ 
10:   $\vec{m} = \mathbf{M}(:, 1)$ 
11:   $p_1 = \vec{m}_1 - \vec{m}_5 - \vec{m}_9$ 
12:   $p_0 = -\vec{m}_2^2 - \vec{m}_3^2 - \vec{m}_6^2 + \vec{m}_1\vec{m}_5 + \vec{m}_9 + \vec{m}_5\vec{m}_9$ 
13:   $[\sigma_1, \sigma_2]$  as the roots of  $\sigma^2 + p_1\sigma + p_0 = 0$ 
14:   $\vec{b}_1 = \text{GETEIGVECTOR}(\vec{m}, \sigma_1)$ 
15:   $\vec{b}_2 = \text{GETEIGVECTOR}(\vec{m}, \sigma_2)$ 
16:  if  $|\sigma_1| > |\sigma_2|$  then
17:    Return  $([\vec{b}_1, \vec{b}_2, \vec{b}_3], \sigma_1, \sigma_2)$ 
18:  else
19:    Return  $([\vec{b}_2, \vec{b}_1, \vec{b}_3], \sigma_2, \sigma_1)$ 

```

github page. The comparison is performed using a Intel Core i7-6700 3.40 GHz CPU and the code compiled using gcc 4.4 on ubuntu 14.04 with the compile options: -O3 and -march=native.

The implementations by Ke and by Kneip always output four solutions, not all of which are correct. The user must determine which of these are valid. Thus we extend these implementations with a minimal post-processing step. This removes solutions which do not satisfy the geometric feasibility constraint, i.e. $\lambda_i > 0$. We also remove solutions which contains NaN or do not approximately contain rotation matrices, i.e. $|\det(\mathbf{R}) - 1| < 10^{-6}$ and $\|\mathbf{R}^T \mathbf{R} - \mathbf{I}\|_{L1} < 10^{-6}$. This step takes a total of 40ns per sample. This cost is included in the timings since this step must always be performed before the result can be used. Table 1 shows that there is approximately 1.7 unique valid solutions on average per sample. Note that the solutions output by our algorithm intrinsically fulfill these criterion by construction.

We time the system in two ways. First we time the computation of each sample resulting in a time distribution graph. Second we take the total runtime over the same samples providing an average time without the overhead of per sample timing. The timing is performed using high resolution stable timers.

4.1 Synthetic Data

We generate random rigid transforms and random reasonably distributed observations. There are two goals with the sampling. First, the samples should uniformly cover both the image, and the set of rotations. Second, we want substantial depth and translation direction variation within reasonable limits. This resembles data found in the recon-

struction of unordered images, a challenging application. Specifically we generate a P3P observation as follows: The rotation $\mathbf{R}$ is represented by a unit quaternion $\vec{q} \in \mathbb{R}^4$. Each sample of $\vec{q}$ is drawn from a isotropic Gaussian distribution in $\mathbb{R}^4$, before being normalized to unit norm and then converted to a matrix. This assures that the rotations have a uniform distribution in $SO(3)$ [13]. The translation components $\vec{t}$ are sampled from a normal distribution with $\sigma = 1$. Combined, $[\mathbf{R}_{gen}, \vec{t}_{gen}]$ is the generating pose of the sample. Observations are generated by a uniform sampling of the normalized image coordinates (u_i, v_i) in the range $[-1, 1]$, and the corresponding 3D point is computed as $\vec{x}_i = \mathbf{R}^T(\vec{y}_i z - \vec{t})$ for a uniform random positive depth $z \in [0.1, 10]$.

Note that P3P is algebraically complete in the sense that it has the same number of constraints as there are free parameters, i.e. it is a minimal solver. Therefore there is no coherent interpretation of adding noise to the observations. We do not remove near degenerate data but instead rely on their presence to strain the algorithms. Strictly degenerate cases, i.e. exactly collinear samples, are removed. It is worth pointing out that this dataset strains the algorithms far more than the "near degenerate" samples experiment of Ke et al., which fails to find the problem cases we find.

The resulting data set consists of 10^7 samples, and the same set is used in all experiments. The experiments are performed sequentially but caching cannot occur due to the size of the dataset. Note, one sample is 104Byte and the full dataset is therefore 1GB.

4.2 Experiment 1: Numerical Accuracy

The numerical accuracy is evaluated by letting the three methods determine their solutions for each sample. Each valid solution $[\mathbf{R}_k, \vec{t}_k]$ is then compared to the generating pose $[\mathbf{R}_{gen}, \vec{t}_{gen}]$ of the sample. For each algorithm, the total pose error $\|\vec{t}_{gen} - \vec{t}_k\|_{L1} + \|\mathbf{R}_{gen} - \mathbf{R}_k\|_{L1}$ of the solution with the error are compared. We are primarily interested in the error in $\mathbf{R}$ but add the translation error to avoid hiding errors in the computation of $\vec{t}$. The matrix differences are used to avoid the angle conversion from contaminating the comparison. Similarly the L1 norm is used to reduce numerical error in the norm computation and provide a fair comparison for the smaller errors. Larger errors above 10^{-6} simply indicate failure. The numerical ranking of the algorithms does not change if the L2 norm, or the delta angle, is used. The latter case favors our solution since the $\mathbf{R}$ to quaternion conversion can be avoided in using the method in Appendix A.2.

Figure 2(a) shows the numerical errors of the three methods. The graph shows that lower errors are more likely with our method than either of the other methods. The number of successes, shown in Table 1, is the number of samples with an error $\leq 10^{-6}$. The table support that failures are significantly less likely with our method. It also shows that the rate of outright failure is far less likely with our algorithm than either of the other two. In particular its interesting to note that Kneip's algorithm has fewer extreme failures than the method by Ke et al. It also turns out the algorithm by Kneip et al. occasionally returns NaN rather than any correct solution. NaNs are replaced by a error of 1 and partially explain the increase at the end of Figure 2(a) for Kneip's algorithm. Finally we note that for every single sample our error is lower than the errors of both Ke and Kneip. In short, the numerical performance of our solver is substantially better than the other two methods.

4.3 Experiment 2: Execution Time Comparison

We provide each algorithm with identical sequences of synthetic data. Since timing a function interferes with performance, we have sampled both a total time and each sample separately. Figures 2(a)-2(b) and Table 1 show that the new method is faster than the method by Ke et al., and that both methods are substantially faster than the method by Kneip et al. Note that excluding the post processing step does not change the ranking. In order to show that the timings are stable the primary comparison has been repeated 1000 times on the same data while keeping the computer otherwise idle. The result is shown in Table 2.

Table 1. Output statistics over 10^7 samples.

Method	Mean[ns]	Successes	Failures	Unique
Lambda Twist	278	9999968	32	16934510
Ke et al. 2 iters	342	9995790	4210	16924141
Ke et al. 10 iters	435	9996105	3895	16925025
Kneip et al.	1042	9994973	5027	16909306

Table 2. Timing statistics over 10^7 samples iterated 1000 times.

Method	Median[ns]	Min[ns]	Max[ns]
Lambda Twist	277	271	289
Ke et al. 2 iters	341	335	353

4.4 Solutions and Successes

First and foremost, Table 1 shows that we have less than one hundredth the number of failures for this data. Further Table 1 shows that we find more unique solutions, i.e. where $|\mathbf{R}_i - \mathbf{R}_j|_{L1} > 10^{-6}$ and $\mathbf{R}_i, \mathbf{R}_j \in SO(3)$, than either of the other methods. This is largely, but not entirely, due to the samples for which the other algorithms do not find any accurate solution. It is worth mentioning that we do not find duplicate solutions, unlike Ke et al. Their algorithm finds about 0.3% duplicates and 36% incorrect solutions in the standard configuration with two root refinement iterations. Interestingly, if the number of root refinement iterations are increased, Ke’s methods only finds slightly more solutions. Instead it refines solutions, which otherwise would not satisfy the solution criteria, into duplicates which do. This results in a duplicate ratio of 36%. Arguably, duplicates should be removed in most applications, but this step was not added to the post-processing as they are technically correct.

Fig. 2. (a) Solver numerical precision likelihoods. (b) Time comparison over 10^7 samples.

We make two additional observations: First, any sample which results in a failure for our method, results in a failure for both other methods, i.e. we are never worse. Second: Every failure for our algorithm and the algorithm of Ke et al. are near known degenerate cases. This is not the case for the algorithm by Kneip et al where a rare cancellation of terms causing a division by zero can occur in a nondegenerate case.

When Ke’s algorithm fails, the most common reason is that the method does not ensure that the output matrix is in $SO(3)$ due to numerical noise after the quartic root. The benchmark by Ke et al unfortunately hides this error as it normalizes/converts the resulting rotation matrix to a unit quaternion as part of the evaluation. This step is costly and not included in their timing measurements. The degradation of performance seen here compared to their work is because our metric does not hide this issue. While we understand the appeal of a geometrically interpretable error, we conclude that for the estimation of numerical accuracy, the measure which minimizes error estimation error is preferable.

5 Conclusions

We have presented a novel P3P method with substantially better numerical performance that is faster than previous state-of-the-art. We believe that both the speed and the accuracy are a result of avoiding the quartic and instead going for a cubic. We have shown the performance of the method using extensive synthetic tests. The test stresses the algorithms sufficiently to find failures. Further, the method lets the user select if a unit quaternion or $\mathbf{R} \in SO(3)$ rotation is desired as output without conversion. The method and the benchmark will be available at:

<https://github.com/midjji/lambda-twist-p3p>.

6 Acknowledgments

This work was funded in part by Daimler Ag, Singulareye AB and Linköping University.

A Appendix

A.1 Degeneracy of (7)

The two equations in (7) become degenerate when $\mathbf{D}_1$ is a scalar multiplied with $\mathbf{D}_2$, in which case the set of solutions is infinite. Taking into account that $a_{ij} > 0$, a straightforward inspection of the two matrices in (5)-(6) shows that the degenerate case implies $\mathbf{D}_1 = \mathbf{D}_2$. This happens if and only if

$$b_{12} = b_{13} = b_{23} = 0, \quad \text{and} \quad a_{23} = 0. \quad (23)$$

This means that degeneracy requires $a_{23} = 0$, which in turn implies that the 3D points are collinear.

A.2 Quaternion from two 3D Correspondences

The rotation can be found as a unit quaternion q given the two 3D correspondences $\vec{a}_i, \vec{b}_i$:

$$\begin{aligned} \vec{a}_i = \mathbf{R}\vec{b}_i &\iff \begin{pmatrix} 0 \\ \vec{a}_i \end{pmatrix} = \vec{q} * \begin{pmatrix} 0 \\ \vec{b}_i \end{pmatrix} * \vec{q}^c = \mathbf{Q}\mathbf{B}_i\vec{q}^c \iff \\ \mathbf{Q}^T\vec{a}_i &= \mathbf{B}_i\vec{q}^c \iff \mathbf{A}_i\vec{q}^c = \mathbf{B}_i\vec{q}^c \implies \\ (\mathbf{A}_i - \mathbf{B}_i)\vec{q}^c &\stackrel{def}{=} \mathbf{Z}_i\vec{q} = 0 \implies \\ (\mathbf{Z}_1 \ \mathbf{Z}_2) \begin{pmatrix} \mathbf{Z}_1 \\ \mathbf{Z}_2 \end{pmatrix} \vec{q} &\stackrel{def}{=} \mathbf{K}\vec{q} = 0 \end{aligned}$$

$\vec{q}$ is then extracted from $\mathbf{K}$ using a specialized solver which exploits that $\mathbf{K}$ has exactly one zero singular value.

References

1. Persson, M., Piccini, T., Mester, R., Felsberg, M.: Robust stereo visual odometry from monocular techniques. In: IEEE Intelligent Vehicles Symposium. (2015) 1
2. Klein, G., Murray, D.: Parallel tracking and mapping for small AR workspaces. In: Proc. Sixth IEEE and ACM International Symposium on Mixed and Augmented Reality (ISMAR'07), Nara, Japan (November 2007) 1
3. Agarwal, S., Snavely, N., Simon, I., Sietz, S.M., Szeliski, R.: Building rome in a day. In: Twelfth IEEE International Conference on Computer Vision (ICCV 2009), Kyoto, Japan, IEEE (September 2009) 1
4. Ke, T., Roumeliotis, S.: An efficient algebraic solution to the perspective-three-point problem. In: Computer Vision and Pattern Recognition (CVPR), 2017 IEEE Conference on, IEEE (2017) 2, 3, 9
5. Kneip, L., Scaramuzza, D., Siegwart, R.: A Novel Parametrization of the Perspective-Three-Point Problem for a Direct Computation of Absolute Camera Position and Orientation. In: IEEE Computer Society Conference on Computer Vision and Pattern Recognition. (2011) 4546–4553 2, 3, 9
6. Grunert, J.A.: Das Pothenotische Problem in erweiterter Gestalt nebst über seine Anwendungen in der Geodäsie. In: Grunerts Archiv für Mathematik und Physik. (1841) 3
7. Haralick, R.M., Lee, C., Ottenberg, K.: Analysis and Solutions of The Three Point Perspective Pose Estimation Problem. In: IEEE Computer Society Conference on Computer Vision and Pattern Recognition. (1999) 592–598 3, 4
8. Gao, X.S., Hou, X.R., Tang, J., Cheng, H.F.: Complete Solution Classification for the Perspective-Three-Point Problem. IEEE Transactions on Pattern Analysis and Machine Intelligence **25**(8) (2003) 930–943 3
9. Grafarend, E.W., Lohse, P., Schaffarin, B.: Dreidimensionaler Rückwärtsschnitt, Teil I: Die Projectiven Gleichungen. Technical report, Geodätisches Institut, Universität Stuttgart (1989) 3
10. Press, W.H., Teukolsky, S.A., Vetterling, W.T., Flannery, B.P.: Numerical Recipes in C++: The Art of Scientific Computing. Cambridge University Press (2002) 9
11. Web page: <https://opencv.org/>. 9
12. Web page: <http://www.laurentkneip.com/software/>. 9
13. Muller, M.E.: A Note on a Method for Generating Points Uniformly on N-Dimensional Spheres. Comm of ACM **2**(4) (1959) 19–20 11

PAPER C

INDEPENDENTLY MOVING OBJECT TRAJECTORIES FROM SEQUENTIAL HIERARCHICAL RANSAC

C

M. Persson and P.-E. Forssén, “Independently moving object trajectories from sequential hierarchical ransac”, in *SCITEPRESS VISAPP 2021: Joint conference on computer vision, imaging and computer graphics theory and applications*, vol. 5, 2021, pp. 722–731

Independently Moving Object Trajectories from Sequential Hierarchical Ransac

Mikael Persson^a and Per-Erik Forssén^b

*The Authors are with the department of Electrical Engineering at Linköping University, Sweden.
first.last@liu.se*

Keywords: Robot Navigation, Moving Object Trajectory Estimation, Visual Odometry, SLAM

Abstract: Safe robot navigation in a dynamic environment, requires the trajectories of each independently moving object (IMO). We present the novel and effective system Sequential Hierarchical Ransac Estimation (Shire) designed for this purpose. The system uses a stereo camera stream to find the objects and trajectories in real time. Shire detects moving objects using geometric consistency and finds their trajectories using bundle adjustment. Relying on geometric consistency allows the system to handle objects regardless of semantic class, unlike approaches based on semantic segmentation. Most Visual Odometry (VO) systems are inherently limited to single motion by the choice of tracker. This limitation allows for efficient and robust ego-motion estimation in real time, but preclude tracking the multiple motions sought. Shire instead uses a generic tracker and achieves accurate VO and IMO estimates using track analysis. This removes the restriction to a single motion while retaining the real-time performance required for live navigation. We evaluate the system by bounding box intersection over union and ID persistence on a public dataset, collected from an autonomous test vehicle driving in real traffic. We also show the velocities of estimated IMOs. We investigate variations of the system that provide trade offs between accuracy, performance and limitations.

1 INTRODUCTION

Navigation in an environment with uncoordinated, Independently Moving Objects (IMOs) is a challenging problem. A key component to the biological solution of this problem is *stereo vision*. Humans robustly identify moving objects. We do this for objects in categories never before seen, and use what is seen over time to predict where objects are moving. It should therefore be possible to find, estimate and predict moving objects in a manner useful for navigation using a stereo camera.

In this work we focus on the real-time detection and trajectory estimation of moving objects in stereo video. In the image space this gives us instance segmentation for rigid independently moving objects as shown in Figure 1. We seek the trajectories in 6D pose-space over time in order to be able to plan around them. While a robot would benefit from a multitude of sensors such as lidar and IMU, we limit ourselves to a stereo sensor. This reduces the complexity of the system and the number of dependencies.

Figure 1: Shire result. World tracks in red, IMOs marked by bounding boxes along with the tracks that are considered as belonging to the objects. Their full 6D trajectories in pose space are estimated in each frame. Shire does not use deep networks or semantic segmentation.

We further limit ourselves to rigid objects, such as vehicles, as they are of key importance to autonomous driving. The principle however generalizes to piecewise rigid objects and temporarily rigid objects. This covers many real obstacles, as can be seen in Figure 4.

We present a novel, fast, accurate, and robust solution for real stereo sequences. The solution is based on a causal greedy probabilistic approach to the assignment and cluster count problems. The solution exploits the sequential nature of the track data and the

^a <https://orcid.org/0000-0002-5931-9396>

^b <https://orcid.org/0000-0002-5698-5983>

typical distribution of moving objects in real scenes. The proposed system extends the feature tracking type of visual odometry system (Klein and Murray, 2007; Badino et al., 2013; Mur-Artal and Tardós, 2017; Persson et al., 2015; Cvišić et al., 2017) to detect and estimate multiple trajectories. The implementation is based on CV4X (Persson et al., 2015) which achieved state of the art results on the KITTI egomotion benchmark and can thus provide reliable egomotion. We now extend this system to also estimate trajectories of independently moving objects. The proposed system uses geometric consistency over time to detect objects. This takes the form of reprojection error minimization to assign tracks and estimate object states over time. As the world is also detected as a rigidly moving object, a useful by-product of the system is the ego-motion trajectory. We call the system described in Section 3 Sequential Hierarchical Ransac Estimation (Shire). Shire performs well in practice, in particular for nearby and fast moving objects. These objects are exactly those that are important for dynamic obstacle avoidance. Shire is real-time (30 Hz) on a standard desktop CPU.

The system is evaluated using a novel dataset, which we make available (Persson, 2020). Ideally we would have liked to evaluate our method by comparing the trajectories of the estimated IMO to their ground truth. To the best of our knowledge no suitable dataset is available for this, nor can we generate such ground truth for our dataset. The dataset is collected from our experimental vehicle, when driving in real traffic. It covers inner city, country road, and highway. We evaluate using bounding box instance segmentation of moving objects. This acts as a proxy for detection, ID persistence, and estimation. This dataset has been preprocessed and we provide rectified images, estimated disparity and semantic segmentation as well as manually annotated IMOs. At the dataset link, you can also find evaluation software, the Shire code, and an example video.

2 Related Work

IMO detection and trajectory estimation could be approached by *scene-flow* methods. Scene-flow is the observed 3D motion per pixel. These methods implicitly segment the flow into rigid objects. Scene-flow approaches can be categorized as classic or deep learning based methods.

Classic methods are well represented by Piecewise Rigid Scene Flow (Vogel and Roth, 2015). The method uses classic flow, classic stereo and (classic) superpixel-segmentation. These are used to form

a regularized scene-flow cost function. This cost is then optimized over a single stereo image pair using Gauss-Newton (GN). The recent Deep Rigid Scene-flow (Ma et al., 2019) method is similar in many ways. The method uses a flow network, a stereo network, and a semantic-segmentation network. The networks are used to form a similar cost function. The cost is then optimized over a single stereo image pair using GN, unrolled for differentiability. Replacing each component with its deep learning based variants requires supervised training. This implies the need for large datasets with both semantic and 3D correspondences ground truth. The cost of such is the main disadvantage of the modern method. However, comparison on the KITTI scene-flow benchmark shows that the latter method significantly outperforms the former. However, while the deep learning approach is faster at 746ms compared to 3 minutes on 0.5Mpixel images, both methods are far from real time. Both methods could hypothetically be extended to use multiple images. However, it is unclear how to do so without further increasing the computational cost. The methods are potentially useful as input to the proposed system. We conclude that they are currently too slow for our target application.

Another deep learning approach which targets a similar problem is MOTSFusion (Luiten et al., 2019). This method aims to identify and separate cars, both still and moving. The method uses deep optical flow, bounding box detections, semantic segmentation, deep stereo. The method also performs egomotion compensation using ORBSLAM. Next they use they use a per track geometrically aware bootstrap tracking method in order to associate tracks over time. This results in strong id propagation performance for the object detections. The method also achieves good results on the MOTS benchmark. The purpose here is tracking rather than 6D trajectory estimation however, though the method could be extended or used as input. Similar to the deep rigid scene-flow the issues are with general moving objects and computational cost. MOTSFusion operating at 0.5MPixel takes 440ms per frame, and while this may be applicable in some cases, it is a long time in collision avoidance.

The good performance of the deep learning approaches comes at a price. Relying on bounding box and/or segmentation limits the systems to the classes for which data is available. For new cameras or scene content, the deep learning methods require finetuning, which requires ground truth. Even if only to adapt to the minor differences in resolution, scene and image characteristics, this requires ground truth data we do not have. By contrast, the classic methods typically

only require manual tuning of a few parameters.

A different approach to the problem of IMO state estimation is found in the 6DVision system (Rabe, 2012). The system fuses stereo and KLT tracks over time using a set of Extended Kalman filters over 3D position (with a constant velocity state). The each filter set is initialized using nearby features states. The filters of each filterset have varying state priors, measurement noise and process noise. The main advantages of this method are low computational cost. The main downside is that individual tracks are noisy and that the filter sets take a long time to converge. In practice, the state estimates are strongly smoothed. This leads to decent results for long tracks, but the system often fails to account for rapid changes.

In this work we introduce a new driving dataset for the purposes of evaluating the system. Compared to KITTI our dataset has higher resolution (2Mpixel vs 0.5Mpixel) and higher framerate (30fps vs 10fps). Using our own dataset allows us to ensure highly accurate calibration which is required for our method. We cannot evaluate on the scene flow benchmarks such as KITTI as it requires dense scene flow, which our method does not provide. Nor can we meaningfully submit to the KITTI (Geiger et al., 2012) MOTS benchmark. This is because the MOTS benchmark does not distinguish moving objects from stationary ones. In practice the latter overwhelmingly outnumber the former. We have however run our system on the these datasets. See section 4.3 for results and further discussion.

Real time stereo VO systems lie on a scale from direct to feature based. Direct systems estimate geometry directly from pixel intensities and pixelwise depths. Feature based systems use higher level image features such as patches and descriptors. The association process of direct systems relies heavily on assumed geometry. This is because pixel intensities are ambiguous, and the geometry constrains the problem. Relying on predicted geometry in this way is a form of geometrically supported tracking. The simplest case of which would be to search for correspondences along a predicted epipolar line. The DSO systems of (Engel et al., 2018) and the stereo variant by (Wang et al., 2017) are typical direct VO systems. A major advantage of single geometry supported tracking is that it allows the use of line features. This improves the VO systems robustness to inarticulate environments and simplifies the tracking. The downside is that it fundamentally limits this type of system. While DSO could hypothetically be recursively applied in a similar manner to our system, in practice we have found that initializing the DSO requires a single dominant motion in view which pre-

cludes this.

Shire is an extension and generalization of the well studied point feature type visual odometry system class. The basis for our method is found in systems such as PTAM (Klein and Murray, 2007), MFI (Badino et al., 2013), ORBSLAM (Mur-Artal and Tardós, 2017), Cv4x (Persson et al., 2015) and SOFT (Cvišić et al., 2017). These methods emphasize the use of inlier/outlier identification and windowed bundle adjustment. They also use measurement virtualization, keyframing, and as well as non-causal processing. Finally most point feature based systems use geometrically supported tracking. Rather than as a core of the tracker, the focus is often on improved robustness against structural aliasing. But it is also used to extend tracks which in turn reduces trajectory drift. A core assumption of these methods is that they are limited to a single rigid object in view. In turn this means that the tracking can and should detectably fail for everything else. Due to the features used, feature based systems are inherently robust against the basic aperture problem. This means that the integration with the tracker is less restrictive. For all VO systems, geometrically supported tracking is key to good performance. How limiting this is varies however. Out of the systems considered, the bootstrap tracking by matching of Cv4x, is perhaps the least restrictive. Cv4x essentially iterates selecting the best correspondence and finding the pose. This places places no restrictions on the initial search. Without the hard reliance on the single motion assumption, it is suited for our purpose. We strip down these systems into a simple core suited for fast causal local mapping and generalize this core system to support IMOs. We also investigate how to apply geometrically supported tracking to Shire with Shire-retrack.

3 Method

3.1 Visual Odometry Overview

Our system is an extension of the feature tracking type of visual odometry system (Klein and Murray, 2007; Badino et al., 2013; Mur-Artal and Tardós, 2017; Persson et al., 2015; Cvišić et al., 2017). Tracks are key to such systems and can be defined as the sequence of image coordinates of a repeatably localizable feature (landmark). An example would be the projections of a 3D point with distinct appearance. Landmark tracking visual odometry systems exploit that the tracks lie on a single static rigid object (world). This facilitates identifying outliers and reducing tracking errors.

First landmarks are detected and then tracked in latter frames. A cost corresponding to Eqn 1 is then minimized. This computes the egomotion trajectory $P_t \forall t$ and local 3d point cloud $x_i \forall i$.

$$\min_{P_t, x_i} \sum_{t,i} \rho(y_{t,i} - \mathcal{P}_\theta(P_t, x_i)) \quad (1)$$

where ρ is a robust error function, $y_{t,i}$ is the observation of landmarks x_i , at time t and P_t is the camera pose, i.e. the rigid transform, at time t for $t \in \{t_0, t_1, \dots, t_N\}$ and $\mathcal{P}_\theta$ is the projection operator suited for x_i where θ is the intrinsic parameters of the camera.

In the simplest case, $x \in \mathbb{R}^3$, is a 3D point in world coordinates. The observation noise is Gaussian plus outliers, the cameras are calibrated, and the correspondences are given.

Typically, ρ , is the L_2 loss combined with an outlier rejection scheme based on reprojection error. The orientation part of the pose is represented as a unit quaternion. Primarily to avoid the gimbal lock problem of Euler angles.

The cost Eqn 1 is non-convex, but optimization will generally converge if the data is balanced and well initialized. A good way to initialize is by sequentially growing the cost i.e. adding one image at a time. This is further improved by computing PnP to find the initial pose of each new frame before bundle adjustment.

3.2 Stereo Point Feature Visual Odometry

Shire is best understood as an extension to point feature visual odometry, and for that reason we will first introduce a base method.

Given a sequence of rectified, calibrated stereo images, iterating Algorithm 1 provides a basic, but good, ego-motion trajectory estimate as indicated by (Persson et al., 2015; Cvišić et al., 2017; Mur-Artal and Tardós, 2017).

Specifically we use: the SGM from (Hirschmüller, 2008) to compute disparity. The KLT implementation from (Rabe, 2012). The P3P and PnP methods from (Persson and Nordberg, 2018), and ANMS from (Gauglitz et al., 2011).

The stereo reprojection error, ϵ , Eqn 2 for each track includes disparity $d(y) \geq 0$. It also requires the points to be in front of each observing camera.

$$\epsilon(y, d, P, x) = (y - \mathcal{P}_{\Theta_l}(P, x))^2 + \lambda(d - [\mathcal{P}_{\Theta_l}(P, x) - \mathcal{P}_{\Theta_r}(P, x)]_0)^2 \quad (2)$$

where Θ_l, Θ_r are the camera intrinsics, and P_t is the relative pose of the stereo rig. Subscript 0 denotes using the horizontal coordinate only.

Algorithm 1 Stereo Point Feature Visual Odometry

```

1: Let: Left, right images at time t:  $LR_t$ 
2: Let: Tracks of object  $o$  at time t:  $tracks_{o,t}$ 
3: Let: Pose at time t:  $Pose_t$ 
4: # Compute disparity
5:  $depth_t = \text{SGM}(LR_t)$ 
6: # Track features using KLT
7:  $tracks_t \leftarrow \text{tracker}(LR_t, tracks_{t-1}, depth_t(LR_t))$ 
8: # Compute pose: Ransac P3P and refinement
9:  $P_t \leftarrow \text{robust\_PnP}(tracks_t)$ 
10:  $\text{windowed\_bundle\_adjustment}(P_t, x_i)$ 
11:  $tracks_t \leftarrow \text{inliers}(tracks_t : \epsilon(track_t) < \tau_{inlier})$ 
12: # Detect new features
13:  $tracks_t \cup \leftarrow \text{detector}(LR_t, depth_t)$ 
14:  $tracks_t \leftarrow \text{ANMS}(tracks_t)$ 

```

The parameter $\lambda = 0.5$ is a balancing weight correcting for the relative variance of the tracker and disparity methods. We found this value by comparing the relative errors when viewing a static scene. The method is fairly robust to different values however. $\lambda \in [0.1, 2]$ provides similar results if the other thresholds are adjusted accordingly.

We minimize the squared L2 norm of the stereo reprojection error, as it achieved good results and performance:

$$\min_{P_t, x_i} \sum \epsilon(y_{t,i}, d_{t,i}, P_t, x_i) \forall t, i \quad (3)$$

We have found that the quality and robustness of Algorithm 1 method is bounded by the tracker and disparity estimates (assuming pixel accurate calibration and typical scenes).

Algorithm 1 is not limited by geometrically supported tracking. Therefore we can extend it to support multiple independently moving objects.

Many different tracking, disparity or optical flow methods could be used, but this is not the focus of this work. Instead we use real time implementations of standard methods. It is common to use keyframing to facilitate loop closure or reduce computational cost, but for clarity this is omitted here.

Adaptive Non-Maxima Suppression (ANMS) is often overlooked in VO descriptions (Gauglitz et al., 2011). We explicitly include ANMS as it is key to good performance both computationally and in terms of accuracy. ANMS conditions the optimization problem, as nearby observations will have correlated errors. The importance of ANMS also indicates that there is a limit to the accuracy gain possible by increasing the track density. In other words, observations must cover a minimum amount of image for accurate pose estimation, regardless of track density. This applies to both Shire and Algorithm 1. Typical

ANMS parameters are radius = 1% image width, 100 minimum tracks, and a strength score which is (track age, cornerness score).

We use the high performance sparsity aware Ceres Solver (Agarwal et al., 2020) to optimize the cost.

3.3 Extension to IMOs

We view reprojection error based inlier/outlier classification as a world/not world assignment operator. Thus we extend this notion to the simultaneous assignment and optimization of multiple rigid objects. A simple idea, which never the less results in a challenging optimization problem:

$$\min_{P_{c,t}, c_{is}} \sum_{t, i \in c_{is}} \rho(y_{t,i}, d, P_{c,t}, x_{c,i}) + C(c_{is}) \quad (4)$$

Here ρ is a robust and weighted stereo reprojection error, similar to Eqn 2. The pose $P_{c,t}$ is that of the camera in IMO c 's coordinate system at time t and $x_{c,i}$ is the 3D point coordinates in IMO c 's coordinates. The set of features belonging to object c is c_{is} . Finally the clustering penalty $C(c_{is})$ accounts knowledge of the distribution of objects. Without which a global minimum is trivially found by putting every point in its own object.

From an abstract perspective the problem is one of association, clustering and minimization. The clustering space is non-metric due to the use of reprojection errors as distance to cluster. This violates the assumptions of many greedy solver such as KMeans. Further complicating things, the number of clusters and their distribution is unknown. In short the problem is challenging.

Restricting ourselves to rigid objects, there is no fundamental difference between the estimation of the IMO trajectory with respect to the static world, and the estimation of the IMO trajectory with respect to the moving rigid object. Thus if the cluster association of each track is known, the stereo VO method of subsection 3.2 can be applied to each IMO independently.

Similar to the static world inlier/outlier case we can assign tracks to IMOs using a noise model, and when there is sufficient evidence, initialize new IMOs. The key observation on which the system is built, is that while tracker errors leave many track assignments ambiguous, an often sufficient subset can be unambiguously assigned in each frame. Thus by accumulating information over time we causally detect, assign and estimate in real time. In essence we have three possible states for a track, inlier, ambiguous, and outlier.

3.4 Shire

Given a sequence of rectified, calibrated stereo images, Shire iterates the steps in Algorithm 2. This algorithm segments the scene into rigid IMOs and estimates their full 6D pose trajectories. The variable *objects* consists of both the object pose trajectory and the 3D coordinates of landmarks associated with the object.

Algorithm 2 Shire

```

1: Let: Objects at time  $t$ :  $objects_t$ 
2: Let: Tracks of object  $o$  at time  $t$ :  $tracks_{o,t}$ 
3: Let: Reprojection error of track  $tr$  for object given
   optimized track state:  $\epsilon_{o,tr}$ 
4:  $score(o, tr) = \max_t(\epsilon_{o,t}(tr))$ 
5:  $inlier(o, tr) = score(o, tr) < \tau_{inlier}$ 
6:  $found(o) = \#tracks_{o,t} > IMO_{minimum\ tracks}$ 
7: Track, depth, detect (as per 3.2)
8: Unassigned:  $us_t \leftarrow us_{t-1} \cup \text{new tracks}$ 
9: for each  $o \in objects_{t-1}$  do
10:    $poses_{o,t} \leftarrow \text{PnP}(objects_{0:t-1}, tracks_{o,t})$ 
11:    $tracks_{o,t} \leftarrow tracks_{o,t-1} \cup inlier(o, tracks_{o,t-1})$ 
12:    $us_t \leftarrow tracks_{o,t-1} \text{ not in } inlier(o, tracks_{o,t-1})$ 
13:    $objects_t \cup \leftarrow found(o)$ 
14:    $windowed\_bundle\_adjustment(o)$ 
15:    $os = \text{not inlier}(o, tracks_{o,t})$ 
16:   if  $o \neq \text{world}$  then
17:     Split Tracks:  $us_t \cup \leftarrow lasttwo(os)$ 
18:   end if
19: end for
20: Let:  $cs \leftarrow$  Potential IMO candidates
21: for each  $tr \in us_t$  do
22:    $rs \leftarrow sort(score(o, tr) \forall o \in objects_t)$ 
23:   if  $rs[0] \geq \tau_{inlier}$  then  $cs_t \cup \leftarrow tr$ 
24:   else if  $rs[1] > \tau_{outlier}$  then  $tracks_{o,t} \cup \leftarrow tr$ 
25:   end if
26: end for
27:
28: Initialize New Object( $cs_t$ )
29:  $cs_t.x \leftarrow disparity_{t-1}(cs_t)$ 
30: candidate:  $c \leftarrow \text{PNP}(cs_t)$ 
31: inliers:  $ins \leftarrow cs_t.s.t. rpe_{c,cs_t}$ 
32: if  $\#inliers > \tau_{creation\ count}$  then
33:   Optimize candidate trajectory and points
34:    $objects_{o,t} \cup \leftarrow candidate$ 
35: end if

```

Additional details in the source code.

3.4.1 Assignment

The track score for a trajectory is the maximum of the reprojection errors among the observations given

the optimal state. The optimal state is the state which minimizes the squared sum of reprojection errors for that trajectory over the optimization window. Computing track scores for all trajectories is comparatively costly. Thus this is only performed for tracks which are unassigned. The inlier test requires that the reprojection error satisfies the inlier threshold, and is not ambiguous with respect to the second best possible assignment. Additionally for IMOs, it is required that the point is within three meters of the object center. For an IMO we require a minimum track count of $\tau_{creation\ count} = 20$. For the inlier, and outlier thresholds we set $\tau_{inlier} = 2.5$ pixels, and $\tau_{outlier} = 4$ pixels. The thresholds were found by looking at error rates of tracks with known assignment. They coarsely correspond to a probability of $P(\text{observation}|\text{from object}) = 0.8$ and $P(\text{observation}|\text{from object}) = 0.05$.

3.4.2 Detection

The Ransac PNP solver is likely to find IMOs in size order, beginning with the first object which is considered the world. Visualization aside it is generally treated the same as the IMOs with two exceptions: Outliers which successfully pass the inlier check for the world, are assigned to it regardless of ambiguity and regardless of distance to its mass center. This prevents the formation of competing static objects should an IMO come to a full stop.

Assignment to IMOs is only considered if the IMO median world coordinate mass center is within five meters of the points world coordinates in the latest frame.

Initialization of a new object is performed as for the first two frames in stereo VO, its origin set to identity at the timestamp of the previous frame. After initialization, any object for which the tracks do not satisfy the assignment test to itself are unassigned. Objects with less than ten remaining tracks are discarded, and its tracks are split and unassigned.

IMOs typically cover a small part of the image limiting the number of tracks available. This in turn necessitates denser tracking to meet minimum robust track count for detection and estimation. To account for this we use a small ANMS radius 12 pixels. Experimentally we have found that this is a good trade-off between speed and robustness. Increasing the radius increases computational speed, but impacts the detection of smaller objects if increased above 20 pixels. Lowering the radius increases computational cost without an observed associated gain in performance.

The system initializes at most one new object each frame in order to limit max per frame processing time.

Should performance permit, it is straightforward to initialize multiple objects by iterating this step.

Ransac PNP with nl-refinement is used because it is robust against the high outlier ratios that occurs when searching among candidates formed from a several not yet identified IMOs.

3.5 Computational Speed

The tracking and disparity can be performed in advance in parallel on CUDA, taking taking 30ms for 2Mpixel images.

In order to speed up optimization, bundle adjustment of trajectories is performed over a maximum of 500 tracks. These tracks are found by increasing radius ANMS. The remainder of the tracks are subsequently optimized using fixed poses. To further improve performance, all optimizations and error computations use a window size of five.

The baseline version of Shire operates at 30fps with two frames of latency between input and trajectory estimates. Shire retrack requires an additional 12ms.

3.6 Semantic Segmentation

While we generally argue in favor of the generic geometric approach, in the specific case of vehicles, fast semantic segmentation networks are available. Therefore we investigate how the method can be improved by semantic labels. In the variant of our method called Shire-labels we use the FCN (Cordts, 2017; Long et al., 2015). The segmentation network was trained on Cityscapes (Cordts et al., 2016).

In Shire-labels, only tracks that lie on vehicles can be assigned to IMOs. The semantic segmentation was performed offline in batches, but may be feasible to run in real time online. The evaluation shows a minor improvement to intersection over union (IoU) scores. Qualitatively we see a significant reduction in false positives.

4 Experiments

We investigate four variations of the Shire system. Shire is the baseline and the fastest variant. Shire+labels uses semantic segmentation to limit the search for candidate tracks. Shire+labels only considers tracks where the starting pixel is labeled as a car or truck as IMO candidates. Shire+retrack uses a second tracking pass to refine the track associations for lost tracks. The second tracking pass uses predictions based on the estimated world and object motions. The

new track result is kept if consistent with its prediction. This retrack tracking step comes at the cost of an additional tracking pass. However, unlike the base tracking pass, this only uses the bottom pyramid level and is slightly faster. Shire+retrack+labels uses both labels and the retrack step.

4.1 Dataset and Evaluation

The lack of benchmarks for the identification of moving objects makes evaluation of IMO estimation a challenge. Object motion 6D trajectories are generally difficult to acquire for real sequences. The available benchmarks are focused on bounding box segmentation of semantic classes. This makes them ill suited for evaluating the quality of a system which needs motion, but not semantic class. We propose to evaluate the system by bounding box IoU and number of ID switches. Specifically we are interested in the results on the 2Mpixel stereo dataset we collected from a Daimler test vehicle. We annotate 7k images for quantitative evaluation.

We performed manual bounding box instance segmentation for IMOs. The criteria for an object to be annotated as an IMO were as follows: The object is a car or truck. The object boundary must move more than two pixels from frame to frame. This is after manual egomotion compensation i.e. compared to known static background. The object must be bigger than 5% of the image and closer than 70 meters. The distance was determined using manually verified disparity. Further, the object must be in unoccluded view for at least five sequential frames. Objects that come to a complete stop for more than five frames are no longer considered IMOs. Unoccluded view requires that 70% or more of the object must be visible. Any IMO which fully leaves view is considered as having a new IMO ID. Not all IMOs are annotated.

This IMO selection is conservative in the sense that the system can detect smaller, shorter lived and occluded IMOs. The IMO requirements are made in part because the annotation of such IMOs is often ambiguous. Their prevalence in the dataset would also make annotation too costly. This means that false positives cannot be automatically evaluated. As a result the primary scores of interest are intersection over union and false negatives.

Bounding boxes for each proposed object are computed in each frame as the range of the associated tracks positions. The proposals are then associated to the ground truth boxes by IoU order in a one to one greedy fashion. The greedy assignment is in descending GT bounding box area order with the added constraint of a minimum IoU score of > 0.2 . The result

Method	median time	mean time
shire	27 ms	30 ms
+labels	26 ms	29 ms
+retrack	43 ms	45 ms
+retrack+labels	40 ms	42 ms

Table 1: Per frame computational cost. Note that this is only the cost of the Shire algorithm. The first tracking, disparity and semantic segmentation are excluded as these can be performed in parallel one frame in advance. However, the second tracking pass required by the retrack method is included in the timing as this cannot be performed in parallel.

Method	switches	missed
shire	4	1430
+labels	4	1730
+retrack	3	1505
+retrack+labels	11	902

Table 2: Number of ID switches, and number of false negatives. Total nr of annotation bounding boxes is 9380. Total images 7000.

of which is summarized in Figure 2.

We compute ID switches as the number of times the IMO ID of the IoU order top choice for a GT IMO changes. An object must be found at least once to be included in the computation. If an object is found lost and found repeatedly again any number of frames later, each repetition counts as one ID change. The evaluation software implementation is available.

4.2 Results

Table 1 shows that our method performs in real time on the i7 3GHz CPU. Table 2 shows that the number of ID switches is infrequent, but also indicates that more id switches happen for harder to detect IMOs.

Figure 2 shows excellent performance for the combined variant. It also shows that the labeled variant is better at finding object boundaries. Without label information slightly more IMOs are found at low IoU scores. Most of these are false positives that happen to overlap with a gt object. Overall performance is fairly good for detected IMOs. Unfortunately a significant fraction are not detected. IMO shadows play a role in reducing IoU accuracy as shown in Figure 5.

The experiments show that the purely geometric Shire achieves moderate success in the generic setting. This result is significantly improved when combined with the segmentation labels, though this is hidden by partial overlaps with false positives at lower IoU scores. This result is further improved by retracking, though less so in the purely geometric case.

The main differences between the using segmentation and not lies in the effect of shadows and outliers

Figure 2: Intersection over Union (IoU) for the best one to one match for each GT IMO. We see that the using the label information (Red) provides good results when a high overlap is required but misses slightly more objects 30%. Bootstrap (Blue) provides a direct improvement over Shire (Yellow). Combined they achieve a significant improvement (Purple). Note that not all IMO are detected in every frame. Roughly 16-30% are not found, most of which lie at far distances at the beginning or end of a GT IMO.

Figure 3: Shire results. On the left top to bottom. First frame where cyan car is found. Last frame before it is lost. First frame where the blue car is found. Last frame before it is lost. On the right. The two cars mass centers in world coordinates over time shown as dots and the Vehicle egomotion poses shown as blue/red coordinate systems. Egomotion is from the bottom left to the upper right, IMOs are driving in the opposite direction. Best viewed electronically.

on bounding boxes. There is also a small impact on speed and an increase in the number of false positives.

A simple heuristic was used to reduce the impact of outliers that fit the geometry. Tracks used for finding the bounding box must be tracked for at least three frames. This heuristic applies only if the at least half

Figure 4: Shire result. A pedestrian IMO detected by the system. While violating the rigid object assumption, people, and most other non rigid IMOs, are often locally rigid. At 100x200 pixels the pedestrian is too small to be fractured into several IMOs. Instead it is intermittently lost and re-detected. The ability to detect generic IMOs is an advantage of the purely geometric method.

Figure 5: Shire results. Red tracks are world, cyan, yellow and pink are IMOs. The track on the cyan car's shadow causes the IMO bounding box to be significantly extended for the car. This happens because the sun is distant, and the car moves in the plane the shadow is projected on top. A downside of the purely geometric method, as we do not collide with shadows.

the tracks on the object have been tracked for three frames. We note that better heuristics could be devised. In particular an analysis of the plane of the motion could be used to identify tracks on shadows. However this is left as future work.

We observe that the system excels at detecting and segmenting fast or nearby objects, but struggles with distant ones. This expected result is never the less beneficial in terms of which objects are important for safe navigation.

Like most feature tracking VO systems, the method is bounded in performance by the tracker. The tracker struggles if the object tracks lengths near or exceed the maximum supported distance. This is in part due to direct search distance limitation and due to large appearance changes due to perspective. The feature detector also struggles with low contrast or blurry images, such as caused by dark regions in otherwise sunny scenes and rain.

The system provides decent ID propagation for IMOs. The primary error source being when two

Figure 6: Starting bottom left, the RGB coordinate axis shows the car trajectory. The colored dots show the various IMOs encountered and their estimated trajectories. Some are driving in the lane to the left, others along the same lane. Best viewed electronically.

IMOs cover separate parts of and therefore compete for a single GT object. More concerning the system fails to detect a fair number of the annotated objects. There are two main causes for false negatives. The first case is an insufficient deviation from the world geometry tracking. This happens for objects that are too far away, especially if they are driving away from the observer. A single car driving away in the same lane at a distance above $35m$ results in nearly a third of all missing detections. The second case is that the tracker or stereo has failed, which happens for objects that are moving or warping too fast in the image. This is a fundamental failure of the tracker and could be addressed by better tracking.

4.3 MOTS and KITTI Results

Shire sample results on the MOTS and KITTI sequences are shown in Figure 7. The Shire parameters are based on tracker and disparity system properties. Therefore we expect they should work for the MOTS and KITTI dataset as well as our. Thus the same parameters are used throughout.

Qualitatively the performance is slightly worse compared to results on our own dataset. Primarily in terms of the number of false positives. This may be partially explained by the frame-rate difference, as the

Figure 7: Top image shows performance on the KITTI benchmark, bottom image shows performance on the MOTS benchmark. Note that the color image from MOTS was converted to grey scale for illustration purposes.

expected parallax increases. Though the difference in sensor characteristics, baseline and resolution may be contributing. We also note that performance is sub-par to the MOTSFusion system, though we do note that our system is more than ten times faster. The performance on the MOTS varies significantly between sequences, but not by scene complexity as may be expected. A possible explanation is that the calibration is slightly worse for some sequences. A calibration error of 1-3 pixels instead of 0-1 pixel error would be sufficient, as Shire is sensitive to calibration errors due to the assignment mechanism. This problem does not appear to apply to the KITTI sequences which use the grey scale cameras instead of the RGB cameras. Since the grey cameras were calibrated for the VO challenge, but the RGB cameras have primarily been used for deep learning, we would not be surprised if they are better calibrated.

4.4 Conclusion

We have presented stereo based Sequential Hierarchical Ransac Estimation (Shire). Shire detects and estimates, in realtime, the 6D pose trajectories of multiple moving objects, and the egomotion using geometric consistency alone. The system can benefit from semantic segmentation, but, unlike for similar methods, it is not required. Shire can be used to predict object trajectories for path planning with dynamic obstacles. It can also detect spatiotemporally separable objects, which form an interesting semantic class, or be used to generate ground truth for optical flow including that on moving objects. Though we leave the training of self supervised systems using Shire as future work. We provide the core Shire code, and the dataset used for evaluation, as well as annotation and evaluation tools (Persson, 2020).

REFERENCES

- Agarwal, S., Mierle, K., and Others (2020). Ceres solver. <http://ceres-solver.org>.
- Badino, H., Yamamoto, A., and Kanade, T. (2013). Visual odometry by multi-frame feature integration. In *First International Workshop on Computer Vision for Autonomous Driving at ICCV*.
- Cordts, M. (2017). *Understanding Cityscapes: Efficient Urban Semantic Scene Understanding*. PhD thesis, Technische Universität, Darmstadt.
- Cordts, M., Omran, M., Ramos, S., Rehfeld, T., Enzweiler, M., Benenson, R., Franke, U., Roth, S., and Schiele, B. (2016). The cityscapes dataset for semantic urban scene understanding. In *Proc. of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.
- Cvišić, I., Česić, J., Marković, I., and Petrović, I. (2017). Soft-slam: Computationally efficient stereo visual slam for autonomous uavs.
- Engel, J., Koltun, V., and Cremers, D. (2018). Direct sparse odometry. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(3):611–625.
- Gauglitz, S., Foschini, L., Turk, M., and Hollerer, T. (2011). Efficiently selecting spatially distributed keypoints for visual tracking. In *Image Processing (ICIP), 2011 18th IEEE International Conference on*, pages 1869–1872.
- Geiger, A., Lenz, P., and Urtasun, R. (2012). Are we ready for autonomous driving? the kitti vision benchmark suite. In *Conference on Computer Vision and Pattern Recognition (CVPR)*.
- Hirschmüller, H. (2008). Stereo processing by semi-global matching and mutual information. in *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 30:328–341.
- Klein, G. and Murray, D. (2007). Parallel tracking and mapping for small AR workspaces. In *Proc. Sixth IEEE and ACM International Symposium on Mixed and Augmented Reality (ISMAR'07)*, Nara, Japan.
- Long, J., Shelhamer, E., and Darrell, T. (2015). Fully convolutional networks for semantic segmentation. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.
- Luiten, J., Fischer, T., and Leibe, B. (2019). Track to reconstruct and reconstruct to track.
- Ma, W.-C., Wang, S., Hu, R., Xiong, Y., and Urtasun, R. (2019). Deep rigid instance scene flow.
- Mur-Artal, R. and Tardós, J. D. (2017). ORB-SLAM2: an open-source SLAM system for monocular, stereo and RGB-D cameras. *IEEE Transactions on Robotics*, 33(5):1255–1262.
- Persson, M. (2020). IMO dataset. <https://www.cvl.isy.liu.se/research/datasets/imo-dataset/>.
- Persson, M. and Nordberg, K. (2018). Lambda twist: An accurate fast robust perspective three point (p3p) solver. In *The European Conference on Computer Vision (ECCV)*.
- Persson, M., Piccini, T., Mester, R., and Felsberg, M. (2015). Robust stereo visual odometry from monocular techniques. In *IEEE Intelligent Vehicles Symposium*.
- Rabe, C. (2012). *Detection of Moving Objects by Spatio-Temporal Motion Analysis: Real-time Motion Estimation for Driver Assistance Systems*. Südwestdeutscher Verlag für Hochschulschriften. ISBN 978-3-8381-3219-8.
- Vogel, C. and Roth, S. (2015). 3d scene flow estimation with a piecewise rigid scene model. *International Journal of Computer Vision*, 115.
- Wang, R., Schwörer, M., and Cremers, D. (2017). Stereo DSO: Large-scale direct sparse visual odometry with stereo cameras. In *International Conference on Computer Vision (ICCV17)*.

PAPER D

PRACTICAL POSE TRAJECTORY SPLINES WITH EXPLICIT REGULARIZATION

D

M. Persson, G. Häger, H. Ovren, and P.-E. Forssén, “Practical pose trajectory splines with explicit regularization”, in *International Conference on 3D Vision 2021*, Dec. 2021

Practical Pose Trajectory Splines With Explicit Regularization

Mikael Persson¹

Gustav Häger¹

Hannes Ovrén²

Per-Erik Forssén¹

Abstract

We investigate spline-based continuous-time pose trajectory estimation using non-linear explicit motion priors. Current regularization priors either linearize the orientation, rely on the implicit regularization obtained from the used spline basis function, or use sampling based regularization schemes. The latter is a special case of a Riemann sum approximation, and we demonstrate when and why this can fail, and propose a way to avoid these issues. In addition we provide a number of novel practically useful theoretical contributions, including requirements on knot spacing for orientation splines, new basis functions for constant velocity extrapolation, and a generalization of the popular P-Spline penalty to orientation. We analyze the properties of the proposed approach using synthetic data. We validate our system using the standard task of visual-inertial calibration, and apply it to stereo visual odometry where we demonstrate real-time performance on KITTI.

1. Introduction

State estimation problems in computer vision are usually modeled by estimating the sensor pose only at a discrete set of times (for example, one per camera frame). This works well for data which is itself discretely sampled e.g. global shutter camera images in reconstruction from collections of images [1, 34] and low framerate video [31]. Many sensors provide data more akin to a continuous stream than discrete samples, e.g. high framerate video, rolling shutter images, spinning lidars, event cameras, and inertial sensors. These are better represented by continuous-time pose trajectories [12]. Such *pose splines* allow the convenient incorporation of derivative measurements, such as from an inertial measurement unit (IMU), as predictions of the analytic trajectory derivatives. High frame-rate video Visual Odometry (VO) illustrates another advantage. Standard discrete bundle adjustment approaches scale cubically with the number of frames, and as a result, often necessitate key framing i.e. tossing information. Continuous pose trajectories with local control instead scale cubically with the number of knots,

which can be much lower than the frame rate [21].

Basis splines are a natural fit for continuous-time poses, and were introduced for this purpose by Furgale et al. [12]. They have since been refined by many follow-up papers e.g. [24, 14, 4, 28, 23, 25, 26, 37]. While the continuous-time approach provides clear benefits over the discrete-time approach, it has not yet been widely adopted by the computer vision community, outside niche topics such as rolling shutter structure from motion, and lidar fusion.

In the pose spline formulation, motion models are incorporated as a prior term in the cost, and need thus not be linearized. We argue that they should instead be approximated using a Riemann sum, and propose a lower bound for the sampling rate (i.e. the inverse sub-interval width) based on observability, and frequency analysis.

We provide several practical improvements to the theoretical framework of pose trajectory estimation:

- 1) We generalize the unit quaternion spline (KKS) by Kim, Kim and Shin [20], by extending it to infinity using constant angular velocity. We do this by modifying the basis functions at the beginning and end in such a way that the spline locality and continuity is maintained.
- 2) We provide a simpler way to derive and compute integrals of spline derivative product functions.
- 3) We provide an upper bound on the angular velocity $\omega(t)$, for the KKS spline, which in turn has important implications for the sampling and knot distance selection.

These contributions, together with the provided optimization framework code [29] should make it easier to use pose splines for various applications in geometric vision and robotics.

2. Related Work

Here we describe related work on continuous-time trajectories, and on regularization strategies for pose splines.

An excellent overview of continuous-time pose trajectories is given in Furgale et al. [14]. The methods discussed by Furgale mostly fall into two categories: They are either KKS splines [20], or equivalent to a straightforward approximation, such as a linearization of a KKS spline. For instance, the popular SLERP construction [36] on pairs of consecutive control points corresponds to a first order KKS spline, and splines over non-quaternion rotation representa-

¹first.last@liu.se, Linköping University, Computer Vision Laboratory

²first.last@foi.se, Swedish Defence Research Agency

tions are either equivalent to, or linearizations of the KKS spline. Many of the more recent papers also use the KKS construct [28, 23, 25, 26, 37].

The extension of classic Bayesian discrete filtering approaches to continuous states i.e. Gaussian Processes (GP) by Barfoot et al. [5] and especially pose trajectory GP frameworks [2, 9] are relevant if the full posterior and not just a point estimate is needed. These frameworks are similar to a zeroth or first degree version of [14] using Gaussian observer functions. In principle GPs are a powerful approach, but in practice, the price is high. In order to achieve feasible computation, the GP pose frameworks linearize the rotation, and since they lose local control, short optimization windows are generally used. This work instead focuses on point estimates using KKS pose splines with local control, and on-manifold rotation representation.

The range of motions a spline can express is constrained by the choice of basis functions, their degree and the knot spacing. This has previously been used as a regularizer although it might not be explicitly stated as such [20, 19, 23, 6]. Bibby et al. [6] discuss the connection between spline parameters and the constraints on dynamics. Anderson et al. [3], and Ovrén et al. [25], investigated how to select a knot spacing so as to ensure the spline could represent the necessary motions. Oth et al. [24] instead use a variable knot spacing. They find the spacings by successively inserting control points during optimization at any interval where residuals are not normally distributed, or moving knots further apart until the predicted observation error variances match the measurement model. Such non-causal methods work well in batch, e.g. for offline calibration [13, 24], but are ill-suited to causal prediction or real time applications.

Incorporation of inertial measurements reduces the need for explicit regularization, and they are thus sometimes also referred to as regularizing measurements [27, 25]. Depending on what other type of measurements are available, there is however a risk of overfitting to one modality. In [25] this problem is addressed by adaptively weighting the inertial measurements based on the motion energy present in the inertial data, and the chosen spline knot spacing.

A common form of trajectory regularization is a cost term derived from a motion model. Motion models usually result in cost terms of integral type, e.g. a constant angular velocity $\omega(t)$ model with Gaussian process noise results in the cost term $\int_{\mathbb{R}} \frac{\partial \omega(t)}{\partial t}^2 dt$. However, the non-linear nature of rotation means that in all but the simplest cases these cannot be used to formulate analytic maximum a posteriori (MAP) estimation problems without approximation.

One approach is to approximate the model formulation. Furgale et al. [14] use an $\mathbb{R}^6$ spline state to represent the pose trajectory. The state is regularized by the integral of the second derivative of the spline. With regards to the trans-

lation, this has an intuitive interpretation; it penalizes the linear acceleration. However, with regards to the rotation it does not, as the angular acceleration is a non-linear function of the parameters. This approach also linearizes expressions involving the rotation. This requires that both true orientation, and estimate at every iteration, must lie within a small region. In the discrete case, the linearization is typically re-centered as needed, but doing so in the continuous case is not possible without losing either continuity or linearity.

Cost terms of integral form can also be approximated by sampling the integrand [28, 21, 18, 4]. In [28, 21] a single sample per knot is used, whereas [39] uses one sample per observation. The former are Riemann approximations, and the latter could be made into such by weighting according to sampling frequency. The Riemann approximation is well known, but there are critical differences between approximating an integral to estimate the value, and approximating a cost term, as will be discussed in Section 5.5. Furgale and Anderson [14, 4] observe issues caused by the state becoming unobservable as knot distance decreases, and note the need to lower knot distances to account for high frequency dynamics. This class of methods along with several other approaches [28, 21, 39, 18] would have these issues as well. However, their experiments do not show this due to the use of relatively dense measurements, though e.g. Huang et al. [18] do note that they were unable to represent a high frequency signal in one experiment. In this work we establish a lower bound for the sampling rate, which is notably above the one/knot used by [28, 21], and show how it is related to the minimum degree and maximum knot distances given signal properties.

Huang et al. [18] consider different ways to regularize trajectories using a forward-only vehicle model and investigate the alternatives with regards to noise sensitivity. Their variant SSBARv is an orientation spline estimated from visual measurements where the regularization is applied as an L^2 penalty on the deviation from forward velocity at the frames. The open issues with the SSBARv method, i.e. the uneven weighting over time, what the weight should be, and the knot distance required for an orientation spline to express a given frequency, are answered by this work.

3. Basis Splines

Here we briefly introduce basis splines and give a few novel and/or practical extensions. For a comprehensive introduction to basis splines and quaternion splines in general, see [38, 8, 20]. We use the Δ operator, which is defined by $\Delta \mathbf{a}_i = \mathbf{a}_i - \mathbf{a}_{i-1}$ and $\Delta^n \mathbf{a}_i = \Delta^{n-1}(\Delta \mathbf{a}_i)$ for $\mathbf{a}_i \in \mathbb{R}^N$. We use dots to denote time derivatives, e.g. $\dot{\mathbf{a}}(t)$ is $\frac{\partial \mathbf{a}(t)}{\partial t}$. We will describe uniform splines with knot distance $\Delta t_i = 1$, as the generalizations are trivial, but verbose. Further we choose the knots t_i as i , for $i \in \mathbb{Z}$. Now

Figure 1. Backwards extrapolation from (6) (orange) and (7) (blue) for $n = 2$. Black dots are control points, $(i + (n + 1)/2, a_i)$.

our uniform $\mathbb{R}^N$ B-splines of degree n , with control points $\mathbf{a}_i$ are defined as in e.g. [38]:

$$\mathbf{s}_n(t) = \sum_i \mathbf{a}_i b_n(t - i) \quad (1)$$

where $b_n(t)$ is defined according to:

$$b_0(t) = \begin{cases} 1 & \text{if } t \in [0, 1) \\ 0 & \text{elsewhere.} \end{cases} \quad (2)$$

$$b_n(t) = (b_0 \otimes b_{n-1})(t) = (b_0 \otimes b_0 \dots \otimes b_0)(t) \quad (3)$$

where $(f \otimes g)(t) = \int f(\tau)g(t - \tau)d\tau$ denotes a convolution. We will refer to this as the *local form*, and it is equivalent to the *cumulative form*, as defined by e.g. Kim et al. [20]:

$$c_n(t) = \sum_{i=0}^{\infty} b_n(t - i) = \begin{cases} \sum_{i=0}^{n-1} b_n(t - i) & \text{if } t < n \\ 1 & \text{otherwise.} \end{cases} \quad (4)$$

Now (1), for a control point interval $[B, E]$, becomes:

$$\mathbf{s}_n(t) = \sum_{i=B}^E \mathbf{a}_i b_n(t - i) = \quad (5)$$

$$\mathbf{a}_B c_n(t - B) + \sum_{i=B+1}^E \Delta \mathbf{a}_i c_n(t - i) \quad (6)$$

where $\Delta \mathbf{a}_i = \mathbf{a}_i - \mathbf{a}_{i-1}$. By omitting the basis function on the first control point, we obtain:

$$\mathbf{s}_n(t) = \mathbf{a}_B + \sum_{i=B+1}^E \Delta \mathbf{a}_i c_n(t - i) \quad (7)$$

This expression extrapolates backwards using the first knot instead of zero, see figure 1.

By using an adaptive start index, $f = \lfloor t \rfloor - n - 1$, we finally obtain the expression used in practice:

$$\mathbf{s}_n(t) = \mathbf{a}_f + \sum_{i=f+1}^{\lfloor t \rfloor} \Delta \mathbf{a}_i c_n(t - i). \quad (8)$$

3.1. Differential Relations

B-splines are straightforward to differentiate and integrate, and the following relations are useful [38, 20]:

$$\frac{\partial}{\partial t} \sum_i \mathbf{a}_i b_n(t - i) = \sum_i \Delta \mathbf{a}_i b_{n-1}(t - i) \quad (9)$$

$$\frac{\partial c_n(t)}{\partial t} = b_{n-1}(t) \quad (10)$$

We also note that:

$$\frac{\partial}{\partial t} b_0(t) = \delta(t) - \delta(t - 1) \text{ where} \quad (11)$$

$$\int_a^b \delta(t - i) f(t) dt = f(i) \text{ if } i \in [a, b]. \quad (12)$$

We propose to use the often overlooked property (11) to significantly simplify integrals of simple functions of splines. For instance, given a second degree spline $s_2(t)$ with white Gaussian accelerations, the regularizing cost can be derived using partial integration and (9)-(11):

$$\int_a^b \ddot{s}_2^2 dt = [\dot{s}_2 \ddot{s}_2]_a^b - \int_a^b \dot{s}_2 \ddot{s}_2 dt = \quad (13)$$

$$[\dot{s}_2 \ddot{s}_2]_a^b - \sum_i \Delta^2 \mathbf{a}_i \int_a^b \dot{s}_2 (\delta(t - i) - \delta(t - i - 1)) dt = \quad (14)$$

$$[\dot{s}_2 \ddot{s}_2]_a^b - \sum_{i \in [a, b]} \dot{s}_2(i) \Delta^3 \mathbf{a}_i \quad (15)$$

This approach is significantly simpler than the common matrix formulation approach taken by e.g. Furgale et al. [14], in Eqn 37 to 59 for the same problem. Our approach generalizes to a broad category of spline differential functions, and has to the best of our knowledge been overlooked until now. Additional examples are found in the supplementary material.

3.2. KKS Quaternion Spline

The KKS(Kim, Kim and Shin) quaternion spline [20] is a generalization of (6). The control points $\mathbf{k}_i$ are unit quaternions and the operations are replaced by their rotation equivalents i.e. addition with quaternion multiplication, and control point weighting by exponentiation. The Δ operator for unit quaternions thus becomes $\Delta \mathbf{k}_i = \mathbf{k}_{i-1}^* \mathbf{k}_i$. Using $\mathbf{w}_i = \Delta \mathbf{k}_i$ for brevity the KKS is defined as:

$$\mathbf{q}_n(t) = \mathbf{k}_F^{c_n(t-F)} \prod_{i=F}^{\infty} \exp(\log(\mathbf{w}_i) c_n(t - i)). \quad (16)$$

Where $\exp()$ and $\log()$ map between unit quaternions and their tangent space. By instead using (7) and $\mathbf{q}^a =$

$\exp(\log(\mathbf{q})a)$ we obtain a simpler definition of the orientation spline as:

$$\mathbf{q}_n(t) = \mathbf{k}_F \prod_{i=F}^{\infty} \mathbf{w}_i^{c_n(t-i)} = \mathbf{k}_f \prod_{i=f+1}^{\lfloor t \rfloor} \mathbf{w}_i^{c_n(t-i)} \quad (17)$$

for $f = \lfloor t \rfloor - n - 1$ as in (8). This formulation also extrapolates backwards towards $\mathbf{k}_F$ rather than identity. Using helper variables τ, W, T we find the recursive form of (17):

$$\tau_{n,i}(t) = \tau_{n,i-1}(t) \mathbf{w}_i^{c_n(t-i)}, \quad \tau_{n,f} = \mathbf{k}_f \quad (18)$$

$$\mathbf{q}_n(t) = \tau_{n,\lfloor t \rfloor}(t) \quad (19)$$

This simplifies computing derivatives [20]:

$$\dot{\mathbf{W}}_i(t) = \dot{\mathbf{w}}_i^{c_n(t-i)}, \quad \dot{\mathbf{W}}_0(t) = 0 \quad (20)$$

$$\dot{\mathbf{W}}_i(t) = b_{n-1}(t-i) \log(\mathbf{w}_i) \mathbf{W}_i(t) \quad (21)$$

$$\dot{\tau}_{n,0}(t) = 0 \quad (22)$$

$$\dot{\tau}_{n,i}(t) = \dot{\tau}_{n,i-1}(t) \mathbf{W}_i(t) + \mathbf{q}_n(t) \dot{\mathbf{W}}_i(t) \quad (23)$$

which gives the angular velocity $\omega(t)$ in rad/s as

$$\mathbf{T}_{n,i}(t) = \tau_{n,i}^*(t) \dot{\tau}_{n,i}(t), \quad \mathbf{T}_{n,0}(t) = \mathbf{W}_0 \quad (24)$$

$$\begin{aligned} \omega(t) &= 2\mathbf{q}_n^*(t) \dot{\mathbf{q}}_n(t) = 2\mathbf{T}_{n,n} \\ &= 2(\mathbf{W}_n^* \mathbf{T}_{n,n-1} \mathbf{W}_n + \dot{\mathbf{W}}_n) \end{aligned} \quad (25)$$

In practice, the recursive approach is not only simpler to implement, but was shown by Sommer et al. [37] to be significantly faster to compute. Comparing our implementation using their benchmark also shows indistinguishable performance for automatic differentiation.

For a unit quaternion in scalar-vector form, $\mathbf{q} = (r, \mathbf{v})$, we define the scalar exponent and quaternion logarithm as:

$$\mathbf{q}^\alpha = \left(\begin{array}{c} \cos(\theta\alpha) \\ \sin(\theta\alpha) \frac{\mathbf{v}}{|\mathbf{v}|} \end{array} \right), \quad \log(\mathbf{q}) = \left(\begin{array}{c} 0 \\ \theta \frac{\mathbf{v}}{|\mathbf{v}|} \end{array} \right) \quad (26)$$

$$\theta = \begin{cases} \text{atan2}(|\mathbf{v}|, r) & r \geq 0 \\ \text{atan2}(-|\mathbf{v}|, -r) & \text{otherwise.} \end{cases} \quad (27)$$

These ensure $\theta \in [-\pi/2, \pi/2]$ i.e. that the shortest geodesic path is selected, regardless of the signs of $\mathbf{k}_i$. From this and (25) we see that regularizers for orientation splines like $\int |\omega(t)|^2 dt$ will lack analytical primitives in general.

3.3. The KKS Domain

The ambiguity resolved by (27) leads to an important but previously overlooked restriction on the domain of the KKS, in addition to those shared with the $\mathbb{R}$ spline. Using (25), $|\log(\mathbf{w}_i)| \leq \frac{\pi}{2}$, $|\mathbf{W}_i| = 1$ and the triangle inequality:

$$\begin{aligned} |\omega(t)| &\leq 2 \sum_{i=1}^n |\dot{\mathbf{W}}_i(t)| = 2 \sum_{i=1}^n |b_{n-1}(t-i) \log(\mathbf{w}_i) \mathbf{W}_i| \leq \\ &2 \sum_{i=1}^n b_{n-1}(t-i) \frac{\pi}{2} |\mathbf{W}_i| = \pi \sum_{i=1}^n b_{n-1}(t-i) \leq \pi \end{aligned} \quad (28)$$

That is: $|\omega(t)| \leq \pi$. More generally a spline with knot distance $\Delta t_i = 1$ has $|\omega(t)| \leq \pi \Delta t_i^{-1}$. Thus for a spline to be able to express $\omega(t)$, its knot distance must satisfy:

$$\Delta t_i \leq \pi |\omega(t)|^{-1}, t \in \mathbb{R} \quad (29)$$

This novel constraint is necessary, but not sufficient, for the spline to be able to express a given dynamic. This can be used to regularize *e.g.* by assuming all $\omega(t)$ above some value are noise. Another use case would be restricting the knot distance search given gyro measurements. In practice this means a sufficiently expressive knot distance can be found quickly. Note also that (29) implies a bound on the Riemann approximation error for many orientation regularizers.

4. Spline Endpoints and Extrapolation

In theory, the control points are often assumed to exist extending to infinity. In practice a finite range is used, and boundary effects must be considered for any regularizer of form $\int_{\mathbb{R}} f(s(t)) dt$. In particular for (6) and (16), as they will extremely quickly move towards identity. The modified splines (7) and (17) alleviate, but do not resolve this issue, as their derivatives will still go to zero in just a few knots, which can also cause severe boundary effects. To address this, we propose a new class of pose trajectory spline which uses constant linear and angular velocity for extrapolation. Our new spline class has the finite control points $\mathbf{a}_i$, $i \in [B, E]$ and the full domain $\mathbb{R}$ while maintaining the continuity properties.

Using (9) we can expand $\ddot{\mathbf{s}}_n(t) = 0$ to:

$$\ddot{\mathbf{s}}_n(t) = \sum_i (\mathbf{a}_i - 2\mathbf{a}_{i-1} + \mathbf{a}_{i-2}) b_{n-2}(t-i) = 0 \quad (30)$$

This constrains the control points as:

$$\mathbf{a}_i = 2\mathbf{a}_{i-1} - \mathbf{a}_{i-2} = \mathbf{a}_{i-1} + \Delta \mathbf{a}_{i-1} \quad (31)$$

which is a common recursive extrapolation strategy. Note however that (31) implies $\Delta \mathbf{a}_{i-1} = \mathbf{a}_i - \mathbf{a}_{i-1} = \Delta \mathbf{a}_i$, and thus $\Delta \mathbf{a}_i = \Delta \mathbf{a}_E$ for $i > E$. We can thus replace the recursion with:

$$\mathbf{a}_i = \mathbf{a}_E + (i - E) \Delta \mathbf{a}_E \text{ for } i > E. \quad (32)$$

Rather than using this expression, we replace the first and last basis functions with r_n , and d_n , and define the extrapolating cumulative spline as follows:

$$\begin{aligned} \mathbf{s}_n(t) &= \mathbf{a}_B + \Delta \mathbf{a}_{B+1} r_n(t-B) + \\ &+ \sum_{i=B+2}^{E-1} \Delta \mathbf{a}_i c_n(t-i) + \Delta \mathbf{a}_E d_n(t-E). \end{aligned} \quad (33)$$

Figure 2. Left: Extrapolation functions (34) (blue) and (35) (orange) for $n = 2$ and $[B, E] = [0, 7]$. Right: Example extrapolation.

The extrapolation functions of degree n are:

$$d_n(t) = \sum_{i=0}^{\infty} c_n(t-i) \quad \text{and} \quad (34)$$

$$r_n(t) = 1 - d_n(n+1-t) = \sum_{i=-\infty}^1 c_n(t-i). \quad (35)$$

These two functions are plotted in figure 2. The forward expression can be rewritten for implementation as:

$$d_n(t) = \sum_{i=0}^{\infty} c_n(t-i) = \begin{cases} \sum_{i=0}^{n-1} c_n(t-i) & \text{if } t < C \\ t - C + 1 & \text{otherwise.} \end{cases} \quad (36)$$

Where $C = (n+1)/2$ is the center of gravity of the basis functions. Similarly, the backward function becomes:

$$r_n(t) = \sum_{i=-\infty}^1 c_n(t-i) - n = \begin{cases} \sum_{i=1-n}^1 c_n(t-i) - n & \text{if } t > C \\ t - C & \text{otherwise.} \end{cases} \quad (37)$$

We then replace linear space operations in (33) with corresponding quaternion operations as in Kim et al. [20] to obtain:

$$\mathbf{q}_n(t) = \mathbf{k}_B \mathbf{w}_{B+1}^{r_n(t-B)} \left[\prod_{i=B+2}^E \mathbf{w}_i^{c_n(t-i)} \right] \mathbf{w}_E^{d_n(t-E)} \quad (38)$$

This spline is parametrized by its control points $\{\mathbf{k}_i\}_B^E$, with the end-pairs $(\mathbf{w}_{B+1}, \mathbf{w}_E)$ defining extrapolating angular velocities. Similar to the $\mathbb{R}^N$ case, this smoothly converges to a constant angular velocity and maintains the continuity properties. The solution is convenient to use in practice as only the control point lookup and basis must be modified.

5. System Models and Regularizers

System models and regularizers are different sides of the same coin. Maximum likelihood fitting of a spline $\mathbf{s}(t, \Theta)$

implies minimizing a loss on the prediction errors of the observations $\mathbf{y}_l$ made at times t_l :

$$\mathcal{L}_{\text{obs}}(\Theta) = \sum_l \rho(\mathbf{y}_l - \mathbf{h}(\mathbf{s}(t_l, \Theta))), \quad (39)$$

where ρ is the negative log of the error probability density and $\mathbf{h}$ is a measurement function. For e.g. the assumption of Gaussian errors, we have $\rho(\epsilon) = |\epsilon|^2$. We can regularize this cost by introducing an independent prior $\mathcal{L}_{\text{reg}}$, and a prior weight λ to get

$$\mathcal{L}(\Theta) = \mathcal{L}_{\text{obs}}(\Theta) + \lambda \mathcal{L}_{\text{reg}}(\Theta). \quad (40)$$

Minimizing (40) results in a *maximum a posteriori* point estimate spline fit.

5.1. Derivative Based Regularizers

Derivative regularizers correspond to smooth functions e.g.

$$\mathcal{L}_{\text{der}}^m(\Theta) = \int_{-\infty}^{\infty} \left\| \frac{\partial^m \mathbf{s}(t, \Theta)}{\partial t^m} \right\|^2 dt. \quad (41)$$

This can be interpreted as an expectation that the chosen derivative is i.i.d. Gaussian with zero mean. E.g. $m = 2$ corresponds to a constant velocity model, but higher order derivative regularizers are in use as well, e.g. the $m = 4$ Snap [22]. For $\mathbb{R}^N$ splines such costs can be efficiently computed using their analytical primitives, as derived using our approach in (13).

5.2. Orientation Regularization

Similar to the $\mathbb{R}^N$ case, it is common to regularize orientation using derivatives of the angular velocity $\boldsymbol{\omega}(t)$ weighted by the inertial tensor $\mathbf{I}$ [14]:

$$\int_{\mathbb{R}} \frac{\partial^m \boldsymbol{\omega}(t)}{\partial t^m}^T \mathbf{I} \frac{\partial^m \boldsymbol{\omega}(t)}{\partial t^m} dt. \quad (42)$$

This regularizer lacks an analytical primitive in general.

5.3. Orientation P-spline

The P-spline regularizer $\mathcal{L}_{\text{P}}^m(\Theta) = \sum_i (\Delta^m \mathbf{a}_i)^2$ of Eilers and Marx [10] was originally derived as an approximation to (41), in part to simplify making a spline observable, and in part to avoid the "difficult" integral (13). This approach is popular due to its simplicity and is practical when little is known about the signal except that it is smooth.

The P-spline regularizer is limited to $\mathbb{R}^N$ splines. In order to address this, we here introduce the Orientation P-Spline regularizer $\mathcal{L}_{\text{PO}}(\Theta)$ which uses the unit quaternion Δ operator: $\Delta \mathbf{k}_i = \mathbf{k}_{i-1}^* \mathbf{k}_i$, $\Delta^m \mathbf{k}_i = \Delta^{m-1}(\Delta \mathbf{k}_i)$. This allows us to define the regularizer:

$$\mathcal{L}_{\text{PO}}^m(\Theta) = \sum_i |\Delta^m \mathbf{k}_i|_{\text{geo}}^2, \quad (43)$$

where we note that $|\mathbf{p}^*\mathbf{q}|_{\text{geo}} = 2\cos^{-1}(\mathbf{p}^T\mathbf{q})$. Thus $\mathcal{L}_{\text{PO}}^1(\Theta)$, $\mathcal{L}_{\text{PO}}^2(\Theta)$ roughly correspond to a constant orientation and constant $\omega(t)$ respectively. The first order in particular is useful for higher degree KKS splines, as it penalizes discontinuities, much like the corresponding $\mathbb{R}^N$ variant does.

5.4. Car Motion Models

There are two motion models commonly used for e.g. cars which we consider for the stereo visual odometry experiment section 7. In the vehicle coordinate system with z forwards, y down, x to the right and position p . A car moving forwards only leads to $\dot{p}_x = n(t)$, $\dot{p}_y = n(t)$ for iid Gaussian $n(t)$. Moving on a surface leads to the coordinated turn model $\ddot{p}_x = v_z(t)w_y(t) + n_0(t)$.

$$\mathcal{L}_{\text{twd}}(\Theta) = \int_{\mathbb{R}} (\ddot{p}_x)^2 + (\ddot{p}_y)^2 dt \quad (44)$$

$$\mathcal{L}_{\text{ct}}(\Theta) = \int_{\mathbb{R}} (\ddot{p}_x - v_z(t)w_y(t))^2 \quad (45)$$

The latter cost (45) lacks analytic primitives in general, and many different approximations have been investigated, e.g. Roth [33] and Yuan [40]. The forward motion model has an analytic solution for specific pose definitions, but is nevertheless often approximated e.g. in SSBARv [39].

5.5. Integral Cost Approximation

In order to optimize over cost terms which are integrals, we must be able to either analytically evaluate them, or approximate them. A common approach is to approximate the function [14, 39], but we have noticed that for smooth functions such as splines, Riemann sums are an appealing alternative. In practice we should use few samples to minimize the computational cost. So how sparsely can we sample?

The key observation we make is that optimizing over samples rather than the integral can turn an overdetermined problem into a determined, or underdetermined one. This in turn allows the optimizer to overfit to the samples and thus perfectly satisfy the regularizer. This is the cause of the ringing artifacts shown in Figure 4. Avoiding this gives us a lower bound for the required minimum number of samples. For N knots we will need a minimum of $N + 1$ samples. This also implies that using one sample at each knot as in e.g. [28, 4], is insufficient. For a longer spline, 2 samples/knot is mostly sufficient, but for a short interval, and in the beginning, we should have at least $n + 2$ samples/knot to know that the state is overdetermined.

Next we consider the local frequency properties. When a function is sampled at a rate f_s , frequencies above $0.5f_s$ are aliased, and cause errors. The Fourier transform of the basis function is $\text{sinc}^n(f)$ which means that the amplitude of the aliased frequencies decay faster than $(0.5f_s)^{-n}$ where n is the degree (less the derivative) for e.g. (41). This also

suggests a minimum sample rate above 2 per knot, and that the minimum approximation error drops faster for higher degree splines. Because the rotation spline is smooth and therefore can be locally described by a spline of the same degree with good precision, this is likely a good approximation for them as well.

We conclude that unless a careful constraint analysis has been performed, $n + 2$ evenly spaced samples per knot should be used.

6. Regularization Experiments

We evaluate how the sample rate affects estimate accuracy and compare the Orientation P-Spline and variable knot spacing. This experiment corresponds to a model of e.g. detected correspondences in RGB-D video. The ground truth trajectory uses a knot spacing of $\Delta t_i = 1$ and degree 4 and is generated by simulation. The trajectory smoothly rotates through, and between each of the planes while moving on a sphere, and is designed to expose every special case. See the supplementary material for additional details. The regularizers are evaluated on the problem of fitting the pose spline trajectory $\hat{P}_{\Theta}(t)$ consisting of KKS $q(t)$ and a $\mathbb{R}^3$ splines given 3D point correspondences which satisfy:

$$\hat{\mathbf{x}}_i = P(t)\mathbf{x} + \mathbf{n}_{i,t} \quad (46)$$

for ground truth trajectory $P(t)$ and the IID Gaussian noise $\mathbf{n}_{i,t} \sim \mathcal{N}(0, 1.0\mathbf{E})$. The 3D landmarks $\mathbf{x}$ are randomly drawn from the unit sphere at $5Hz$. We estimate a trajectory of the same degree and knot distance by minimizing:

$$\min_{\Theta} \sum_{i,t} \alpha^{-1} \left\| \hat{\mathbf{x}}_i - \hat{P}_{\Theta}(t)\mathbf{x} \right\|_2^2 + \beta^{-1} \mathcal{L}_{\text{reg}}(\Theta) \quad (47)$$

where α, β are the variances of the measurements and of the regularizer on the ground truth. The estimated trajectory has the same degree and knot distance as the ground truth. The trajectory estimate is initialized using the ground truth, i.e. we are studying how far the noise causes the trajectory to diverge. This is to avoid any issue caused by local minima. As metric we use $\int \theta^2(t)dt$ where θ is the angle between ground truth and estimated orientations. The integral is evaluated using dense sampling (10^5 per knot).

Figure 3 shows the relative accuracy of the constant angular velocity model, often called *energy* (i.e. (41) with $n = 2$) when varying the number of regularizer samples that are used per control point.

The figure shows that the energy regularizer provides excellent performance even at low sampling rates. Qualitatively the reconstruction is nearly indistinguishable from the ground truth for $f_s \geq 2$ whereas the signal is extremely noisy without regularization. Using one sample per knot, the system performs reasonably well, but visibly oscillates/overfits at the beginning as shown in Figure 4 and predicted by the constraint analysis.

Figure 3. Performance of the regularizers depending on the number of samples per spline knot that are used for the approximating integral. The error is reported relative to using no regularization. Knot spacing $\Delta t_i = 1$.

Figure 4. Sampling the regularizer using single sample per knot allows the optimizer to overfit, exactly satisfying the samples and causing oscillation if the regularizer weight is high enough.

Figure 5. Regularization using knot spacing as an implicit regularizer. The error is reported relative to using no regularization and knot spacing $\Delta t_i = 1$. The difference to the energy regularization is approximately 30%. The problem becomes unobservable for knot spacing below 0.2 and errors above 1 are excluded.

We also compare to implicit regularization by using varied knot spacing in figure 5. We conclude that if the optimal knot spacing can be found, this approach works reasonably well, but it is difficult to predict what that spacing is in advance based on e.g. dynamic models.

For P-spline regularization (43) we try using both first and second order, and vary the regularizer weight. In both cases the optimal weight is predicted by the ground truth

Figure 6. Performance of P-spline regularizers for different weights. Left: $m = 1$, right: $m = 2$. The error is reported relative to using no regularization and knot spacing $\Delta t_i = 1$.

variance weighting. Figure 6 shows that second order generalized P-splines are better than first order, but both are inferior to using the sampled energy model.

We conclude that the energy penalty with a moderate number of samples per knot performs well. The improvement plateaus after 2 samples per knot. Adding this regularizer significantly improves convergence speed, reducing total computational time by 33%. Overall, the generalized P-splines are faster but also perform worse.

7. Visual Odometry

This experiment demonstrates that continuous pose trajectories are applicable to real-time odometry using the KITTI odometry dataset [16]. Specifically we examine how varying knot distance and spline degree affects the computation time and reconstruction accuracy.

The visual odometry system we use is intentionally simple. We use a KLT [32] tracker and a SGM [17] stereo, which at each step tracks 3d features into the next image. After minimization we discard outliers based on a reprojection error with threshold 3 pixels by eliminating the track's last measurement. We initialize new features using ANMS [15] and prune old features using the approach of [31] keeping the number of tracks $\in [100, 300]$. The system is initialized using PnP for the first five frames, after which the regularizers allow the spline to predict the next frame pose. In each frame the system optimizes the reprojection errors, the sampled regularization using $n+2$ samples, and the 3d point positions, giving the cost:

$$\mathcal{L}(\Theta) = \sum_{k,f} \|y_{t_i,f} - \wp(P_{cv}P_{wv}^{-1}(t_i)x_f)\|^2 \quad (48)$$

$$+ \alpha^{-1}\mathcal{L}_{\text{twd}}(\Theta) + \beta^{-1}\mathcal{L}_{\text{ct}}(\Theta) \quad (49)$$

where $y_{t_i,f}$ are observations of feature f at time t_i and $\wp$ is the stereo projection. P_{cv} is the transform between the camera and the rear axle, and $P_{wv}(t)$ is the pose trajectory. The weights α, β are found as the inverse variances of the regularizers applied to the ground truth trajectory of KITTI

Figure 7. The processing time per frame related to the knot distance, for $n = 3, 4, 5$ on knot distances from 0.05 to 1. Evaluated on the first training sequence.

Figure 8. The KITTI rotation error metric evaluated on the first training sequence, for $n = 3, 4, 5$ on knot distances from 0.05 to 1. The current top performer SOFT2[7] achieves an error of 0.0009 overall on test data.

sequence two. The entire history of each track present in any of the five most recent frames are included in the cost. All knots preceding those affected by the five most recent frames are set constant, as are all 3d points which are not present in the current image. We use up to five iterations per frame. To our knowledge, we are the first to use a windowed optimization strategy for real-time VO on real data.

We evaluate the system on the first training sequence as it lets us perform the evaluation repeatedly and because it is simple enough to use a simple tracker. Results are shown in figures 7 and 8. This demonstrates that real-time on-line stereo odometry using pose trajectory splines is feasible, with the degree three alternative running at 30fps while achieving reasonable results. The experiment also shows that knot distances shorter than one are possible given that a regularizer is used. A video showing sample results is available in the supplementary material.

8. Visual-Inertial Calibration

Visual-inertial calibration is commonly used as a validation experiment for pose trajectory spline implementations, e.g. Furgale et al. [14], Patron-Perez et al. [28] and Sommer et al. [37]. We similarly validate our system by calibrating the *calib-cam1* sequence from the dataset by Shubert

et al. [35]. The sequence has 10 336 IMU measurements and 1038 stereo pairs spanning 52.8 seconds, but it lacks ground truth. Therefore we compare to the result of Sommer et al. [37] and use the same $P_{\text{cam,imu}}$ initialization and weights $\gamma_{\text{acc}}, \gamma_{\text{gyro}}$ as them. We initialize the spline using per frame PnP-Ransac [30, 11] followed by bundle adjustment.

Since poses from calibration patterns are highly accurate, we wish to be able to go through each, which implies a minimum knot distance of 0.05s. We verify that this is likely sufficient to represent the observed $\omega(t)$ as using (29) implies a minimum knot distance of 0.7s. The lowest derivative of interest i.e. acceleration should have one or preferably two continuous derivatives. Therefore degree 3 or 4 is suitable and we use four. We find the transform P_{ci} between camera and IMU by minimizing the cost:

$$\mathcal{L}(\Theta) = \sum_{t_f, i} \|y_{t_f, i} - \wp(P_{cw}(t_f)x_i)\|^2 + \quad (50)$$

$$\gamma_{\text{acc}} \sum_{t_a} \|\ddot{p}_{\text{body}}(t_a) - \ddot{p}[t_a] + g_{\text{body}} + b_{\text{acc}}\|^2 + \quad (51)$$

$$\gamma_{\text{gyro}} \sum_{t_g} \|\omega_{\text{body}}(t_g) - \omega_{\text{body}}[t_g] + b_{\text{gyro}}\|^2 \quad (52)$$

Where $\wp$ is the projection operator, $y_{t_f, i}$ visual measurements, and $P_{cw}(t) = P_{ci}P_{wi}^{-1}(t)$ the offset pose trajectory spline. The $\omega_{\text{body}}(t_i)$, and $\ddot{p}(t_i)$ are gyro and accelerometer measurements with constant IMU bias. We optimize over P_{ci} and the pose trajectory. We do not add regularization, as this would conflict with the sought estimate.

Using this procedure we recover the IMU-camera transformation with a geodesic difference of 10^{-5} and 10^{-4} meters, relative to the calibration of Sommer (which is not a ground truth).

9. Concluding Remarks

This paper has investigated pose trajectory regularization by sampling explicit non-linear priors. This is aided by a novel spline construct with constant linear and angular velocity extrapolation. We have found a lower bound for the sampling rate, which is notably above the common choice of a single sample per knot. We have compared several different types of pose trajectory regularization, including derivative penalties, implicit (using knot spacing), and a novel orientation P-spline penalty. We have also derived an upper bound on the knot distance required to represent a given $\omega(t)$. The code for our system is available on GitHub [29]. The system has been validated on the standard task of visual-inertial calibration, and applied to stereo visual odometry where we demonstrate real-time performance.

Acknowledgements: This work was supported by Vinnova through the Visual Sweden network, Dnr 2019-02261, and by Singulareye.

References

- [1] Sameer Agarwal, Noah Snavely, Ian Simon, Steven M. Seitz, and Richard Szeliski. Building rome in a day. In *2009 IEEE 12th International Conference on Computer Vision*, pages 72–79, 2009. 1
- [2] Sean Anderson and Timothy D. Barfoot. Full steam ahead: Exactly sparse gaussian process regression for batch continuous-time trajectory estimation on $se(3)$. In *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 157–164, 2015. 2
- [3] Sean Anderson, Frank Dellaert, and Timothy D. Barfoot. A hierarchical wavelet decomposition for continuous-time SLAM. In *IEEE International Conference on Robotics and Automation (ICRA14)*, pages 373–380, Hong Kong, China, May 2014. 2
- [4] Sean Anderson, Kirk MacTavish, and Timothy D. Barfoot. Relative continuous-time SLAM. *International Journal of Robotics Research*, 34(12):1453–1479, 2015. 1, 2, 6
- [5] T. Barfoot, C. Tong, and S. Särkkä. Batch continuous-time trajectory estimation as exactly sparse gaussian process regression. In *Robotics: Science and Systems*, 2014. 2
- [6] Charles Bibby and Ian D. Reid. A hybrid SLAM representation for dynamic marine environments. In *IEEE International Conference on Robotics and Automation (ICRA)*, pages 257–264. IEEE, 2010. 2
- [7] Igor Cvii and Ivan Petrovi. Stereo odometry based on careful feature selection and tracking. In *2015 European Conference on Mobile Robots (ECMR)*, pages 1–6, 2015. 8
- [8] Carl de Boor. *A Practical Guide to Splines*. Springer Verlag (New York), 1978. 2
- [9] Jing Dong, Mustafa Mukadam, Byron Boots, and Frank Dellaert. Sparse gaussian processes on matrix lie groups: A unified framework for optimizing continuous-time trajectories. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6497–6504, 2018. 2
- [10] Paul H. C. Eilers and Brian D. Marx. Flexible smoothing with B-splines and penalties. *Statistical Science*, 11(2):89–121, 1996. 5
- [11] M. A. Fischler and R. C. Bolles. Random Sample Consensus: A Paradigm for Model Fitting with Applications to Image Analysis and Automated Cartography. *Communications of the Association for Computing Machinery*, 24(6):381–395, 1981. 8
- [12] Paul Furgale, Timothy D. Barfoot, and Gabe Sibley. Continuous-time batch estimation using temporal basis functions. In *IEEE International Conference on Robotics and Automation (ICRA12)*, 2012. 1
- [13] Paul Furgale, Joern Rehder, and Roland Siegwart. Unified temporal and spatial calibration for multi-sensor systems. In *IEEE International Conference on Intelligent Robots and Systems (IROS13)*, Tokyo, Japan, November 2013. 2
- [14] Paul Furgale, Chi Hay Tong, Timothy D. Barfoot, and Gabe Sibley. Continuous-time batch trajectory estimation using temporal basis functions. *International Journal of Robotics Research*, 34(14):1688–1710, 2015. 1, 2, 3, 5, 6, 8
- [15] S. Gauglitz, L. Foschini, M. Turk, and T. Hollerer. Efficiently selecting spatially distributed keypoints for visual tracking. In *Image Processing (ICIP)*, 2011 18th IEEE International Conference on, pages 1869–1872, Sept 2011. 7
- [16] Andreas Geiger, Philip Lenz, and Raquel Urtasun. Are we ready for autonomous driving? the kitti vision benchmark suite. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2012. 7
- [17] Heiko Hirschmüller. Stereo processing by semiglobal matching and mutual information. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 30(2):328–341, 2008. 7
- [18] Kun Huang, Yifu Wang, and Laurent Kneip. B-splines for purely vision-based localization and mapping on non-holonomic ground vehicles. In *IEEE International Conference on Robotics and Automation (ICRA21)*, 2021. 2
- [19] Christian Kerl, Jörg Stückler, and Daniel Cremers. Dense continuous-time tracking and mapping with rolling shutter cameras. In *IEEE International Conference on Computer Vision (ICCV15)*, 2015. 2
- [20] Myoung-Jun Kim, Myung-Soo Kim, and Sung Yong Shin. A general construction scheme for unit quaternion curves with simple high order derivatives. In *SIGGRAPH'95*, pages 369–376, 1995. 1, 2, 3, 4, 5
- [21] Steven Lovegrove, Alonso Patron-Perez, and Gabe Sibley. Spline fusion: A continuous-time representation for visual-inertial fusion with application to rolling shutter cameras. In *British Machine Vision Conference (BMVC)*. BMVA, September 2013. 1, 2
- [22] Daniel Mellinger and Vijay Kumar. Minimum snap trajectory generation and control for quadrotors. In *2011 IEEE International Conference on Robotics and Automation*, pages 2520–2525, 2011. 5
- [23] E. Mueggler, G. Gallego, H. Rebecq, and D. Scaramuzza. Continuous-time visual-inertial odometry for event cameras. *IEEE Transactions on Robotics*, 34(6):1425–1440, 2018. 1, 2
- [24] Luc Oth, Paul Furgale, Laurent Kneip, and Roland Siegwart. Rolling shutter camera calibration. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR13)*, pages 1360–1367, Portland, Oregon, June 2013. 1, 2
- [25] Hannes Ovrén and Per-Erik Forssén. Spline error weighting for robust visual-inertial fusion. In *IEEE Conference on Computer Vision and Pattern Recognition*, Salt Lake City, Utah, USA, June 2018. Computer Vision Foundation. 1, 2
- [26] Hannes Ovrén and Per-Erik Forssén. Trajectory representation and landmark projection for continuous-time structure from motion. *International Journal of Robotics Research*, 38(6):686–701, May 2019. 1, 2
- [27] Chanoh Park, Peyman Moghadam, Soohwan Kim, Alberto Elfes, Clinton Fookes, and Sridha Sridharan. Elastic LiDAR fusion: Dense map-centric continuous-time SLAM. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2018. 2
- [28] Alonso Patron-Perez, Steven Lovegrove, and Gabe Sibley. A spline-based trajectory representation for sensor fusion and rolling shutter cameras. *International Journal on Computer Vision*, 113(3):208–219, 2015. 1, 2, 6, 8
- [29] Mikael Persson. Explicitly regularized pose splines. <https://github.com/midjji/pose-splines>, 2021. 1, 8

- [30] Mikael Persson and Klas Nordberg. Lambda twist: An accurate fast robust perspective three point (P3P) solver. In *The European Conference on Computer Vision (ECCV)*, September 2018. 8
- [31] M Persson, T Piccini, R Mester, and M Felsberg. Robust stereo visual odometry from monocular techniques. In *IEEE Intelligent Vehicles Symposium*, 2015. 1, 7
- [32] Clemens Rabe. *Detection of Moving Objects by Spatio-Temporal Motion Analysis: Real-time Motion Estimation for Driver Assistance Systems*. Südwestdeutscher Verlag für Hochschulschriften, 2012. ISBN 978-3-8381-3219-8. 7
- [33] Michael Roth, Gustaf Hendeby, and Fredrik Gustafsson. EKF/ukf maneuvering target tracking using coordinated turn models with polar/cartesian velocity. In *17th International Conference on Information Fusion (FUSION)*, pages 1–8, 2014. 6
- [34] Johannes Lutz Schönberger and Jan-Michael Frahm. Structure-from-motion revisited. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2016. 1
- [35] David Schubert, Thore Goll, Nikolaus Demmel, Vladyslav Usenko, Jörg Stückler, and Daniel Cremers. The TUM VI benchmark for evaluating visual-inertial odometry. In *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 1680–1687. IEEE, 2018. 8
- [36] Ken Shoemake. Animating rotation with quaternion curves. In *Int. Conf. on CGIT*, pages 245–254, 1985. 1
- [37] Christiane Sommer, Vladyslav Usenko, David Schubert, Nikolaus Demmel, and Daniel Cremers. Efficient derivative computation for cumulative B-splines on Lie groups. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR20)*, June 2020. 1, 2, 4, 8
- [38] Michael Unser. Splines – a perfect fit for signal and image processing. *IEEE Signal Processing Magazine*, 16(6):22–38, 1999. 2, 3
- [39] Xin Wang, Fei Xue, Zike Yan, Wei Dong, Qiuyuan Wang, and Hongbin Zha. Continuous-time stereo visual odometry based on dynamics model. In *14th Asian Conference on Computer Vision (ACCV18)*, volume 11366 of *Lecture Notes in Computer Science*, pages 388–403. Springer, 2018. 2, 6
- [40] Xianghui Yuan, Chongzhao Han, Zhansheng Duan, and Ming Lei. Comparison and choice of models in tracking target with coordinated turn motion. In *2005 7th International Conference on Information Fusion*, volume 2, pages 6 pp.–, 2005. 6

PAPER E

GOOD EDGELS TO TRACK: BEATING THE APERTURE PROBLEM WITH EPIPOLAR GEOMETRY

T. Piccini, M. Persson, K. Nordberg, M. Felsberg, and R. Mester, “Good edgels to track: Beating the aperture problem with epipolar geometry”, in *Computer Vision - ECCV 2014 Workshops*, 2014, pp. 652–664, ISBN: 978-3-319-16181-5

E

Good Edgels to Track: Beating the Aperture Problem with Epipolar Geometry

Tommaso Piccini¹(✉), Mikael Persson¹, Klas Nordberg¹, Michael Felsberg¹,
and Rudolf Mester^{1,2}

¹ CVL, ISY, Linköping University, Linköping, Sweden
`tommaso.piccini@liu.se`

² VSI Lab, C.S. Department, Goethe University, Frankfurt, Germany

Abstract. An open issue in multiple view geometry and structure from motion, applied to real life scenarios, is the sparsity of the matched key-points and of the reconstructed point cloud. We present an approach that can significantly improve the density of measured displacement vectors in a sparse matching or tracking setting, exploiting the partial information of the motion field provided by linear oriented image patches (edgels). Our approach assumes that the epipolar geometry of an image pair already has been computed, either in an earlier feature-based matching step, or by a robustified differential tracker. We exploit key-points of a lower order, *edgels*, which cannot provide a unique 2D matching, but can be employed if a constraint on the motion is already given. We present a method to extract edgels, which can be effectively tracked given a known camera motion scenario, and show how a constrained version of the Lucas-Kanade tracking procedure can efficiently exploit epipolar geometry to reduce the classical KLT optimization to a 1D search problem. The potential of the proposed methods is shown by experiments performed on real driving sequences.

Keywords: `Densification · Tracking · Epipolar geometry · Lucas-Kanade · Feature extraction · Edgels · Edges`

1 Introduction

Most methods for finding image-to-image correspondences by tracking or matching are applied on selected *key-points*, i.e., image locations which are unique in appearance and can easily be re-identified. While providing a coarse outline of the motion structure in a scene, a drawback of this approach is that the feature points are distributed sparsely, and cannot produce a dense 3D point cloud.

A natural next step is to consider a scenario where the relative motion between the camera and the scene/object already has been determined with high accuracy, e.g., by means of sparse feature matching and windowed bundle adjustment, and is represented by the epipolar structure. After this step, it is possible to increase the density of the motion field, aiming for a dense 3D reconstruction. This can be done by stereo matching on rectified image pairs,

Fig. 1. Close up of an image patch showing a situation where the *GETT* keypoints strongly outnumber *GFTT*. **Left:** GFTT. **Right:** GETT.

and gives generally very good results in the case of sideways camera motion and relatively small rotations, but it is not a feasible approach for a general motion, such as forward/backward camera motion combined with significant rotations.

As an alternative, we instead extract edge pixels that are likely to track well given a known epipolar geometry, and perform a local search for the correspondence only on the physically plausible segment of the epipolar line. To do this, we modify the Kanade-Lucas-Tomasi (**KLT**) tracker to only operate along the epipolar line, thus allowing to also track several edge points (Fig. 1). Relevant applications of this method include:

- densification of the partial reconstruction for object detection in the context of autonomous robots.
- increase of the density of the reconstructed 3D point cloud as a final step of a multi-view structure from motion.

To summarize, this paper presents two novel contributions:

- We extract edgels that are likely to track well under the given relative motion. These edge points are called *Good Edgels To Track* (**GETT**).
- We densify the motion field by tracking these new edgel features, using a modified version of the KLT tracker that can deal with the aperture problem, given that the epipolar geometry is known.

2 Related Work

Many applications in computer vision, e.g., structure from motion and visual odometry, have as an initial step the computation of optical flow. This can be done in two ways: computing a global optical flow for the whole image plane [7, 13] or by sparsely computing the displacement of a limited number of (feature) points in the image. The first approach provides a dense flow field, but has a high computational complexity. The sparse approach is more computationally efficient, but the sparsity of the motion field can be a limiting factor when a dense reconstruction is desired. The sparsity is a consequence of applying these

methods only on selected feature points, with a structure in their surroundings that allows them to be re-identified in subsequent images [1, 10, 22, 24]. Such feature points can be found on a second image, depicting a slightly modified version of the same scene, either by matching or by tracking procedures. Matching procedures extract feature points in both images, and try to match the most similar pairs using a specifically designed descriptor [3, 6, 17, 18, 21]. Tracking is instead implemented generally as a search, in the second image, for a point that minimizes a cost function which measures the difference between small patches of the image surrounding the two points. The most common approach to tracking is based on the Lucas-Kanade tracker [19], which approximately minimizes a cost function calculated as the sum of the squared differences in the intensities of the pixels belonging to the patches. The KLT tracker has been shown to work reliably only on “corner points”, known as *Good Features to Track* (GFTT), and although efforts have been made to improve the performance of the tracker on said points [2, 8, 23], not many papers in the literature deal with the sparsity of such features. GFTT-points can be identified by a structure tensor with large values for both its eigenvalues [22]. The 2D motion of these points can be identified, in both directions, with a gradient descent method on the matching criterion (e.g. the SSD). A natural next step would be to track points having only one large eigenvalue for their structure tensor. Intuitively, these points lie mainly on linear edges. At these points, however, a local analysis can only provide the motion component in a direction perpendicular to the edge, corresponding to the eigenvector for the largest eigenvalue of the structure tensor. This is the well-known *aperture problem*.

A framework for matching edgels is proposed in [16], and is shown to outperform matching based on, e.g., SIFT or SURF, when a planar object is tracked. The limitation to planar objects restricts, however, the application of this approach. Another attempt to solve the aperture problem is made in [4], by jointly tracking edge points and nearby corner points with a method that combines the KLT tracker and the global Horn-Schunck method. In this framework, the motion of corner points helps in solving for the second degree of freedom of nearby edge points thanks to a regularization term inserted in the optimization process.

A similar, but more generalized approach is taken in [26] where a semi-global matching method is adapted to work exclusively on fractions of the epipolar line. Also in this case, a regularization term is included in the optimization process to allow the matching of weaker points (edgels or even pixels lying on planar, textureless areas). The optimization problem is, however, NP-hard and non parallelizable so the dynamic programming approach used to solve it takes several seconds to compute.

In [15] the authors propose a method to obtain a dense optical flow which does not include a regularization term allowing each point to be treated individually. In this approach a Delaunay triangulation is performed over the motion field generated by a sparse matching framework to produce a prior on the motion field for all the points in the convex hull of the sparse features. This information is then used in combination with the estimated epipolar geometry and the trifocal

tensor to steer a maximum-a-posteriori estimate for the best matching candidate for each pixel while also cutting down the number of possible candidates significantly

In our work, a different approach is taken. Corner points are often sufficient in number to produce a useful inter-frame motion estimate, which can be made even more accurate by the means of a global or local bundle adjustment, but are just too sparse to produce a dense reconstruction. Hence, there is no need to include edgels at this early stage. In most cases, including them at this stage would just make the egomotion estimate more computationally complex without a significant gain in accuracy and robustness. Instead, if we are only interested in making the motion flow in an image pair denser, the corresponding epipolar geometry is already available to a high degree of accuracy, and it is possible to formulate the KLT tracker as a 1-dimensional problem by constraining its optimization procedure exclusively on an epipolar line. Thus, edgels that are not parallel to the corresponding epipolar line can be tracked. We refer to this modified version of the KLT tracker as *Epipolar KLT*.

The idea of epipolar KLT has recently been proposed by Trummer et al [25], applied to the scenario of a camera mounted on a robotic arm for which the motion parameters are known. That work, however, does not fully exploit this tool for the tracking of specifically extracted edgels and, in fact, they reject the idea of completely constraining the tracker to the epipolar lines due to possible uncertainty in the epipolar geometry. Instead, they formulate a biased 2-dimensional tracker that favors steps in the direction of the epipolar line and reduces the freedom in the perpendicular direction with empirically chosen weights. Not completely trusting the epipolar geometry can be reasonable in high precision applications, but there is no reason to ignore already established camera poses when just aiming at making the motion field denser.

3 Methods

3.1 Background

The KLT tracker The classical KLT tracker has been repeatedly derived in literature, and we will only present parts of the derivation which are of interest for our modifications. For a complete derivation, see [2, 5, 19] among others. Let $W'_{\mathcal{J}}$ be a small window in the second image around a feature point, $\mathcal{I}(\mathbf{x})$ and $\mathcal{J}(\mathbf{x})$, respectively intensity value of the first and second images at position $\mathbf{x}$. In the simplest case, the change in the position of a point from $\mathcal{I}$ to $\mathcal{J}$ consists in a 2D translation, represented by the 2 values of the translation vector $\mathbf{v}$. Also, in practice, the inverse warping function is often used since it makes the procedure computationally more efficient.

Fig. 2. Schematics of some geometric entities involved in two view geometry

The expression for the cost function is:

$$G(\Delta \mathbf{v}) := \sum_{\mathbf{x}'_i \in W'_J} (\mathcal{I}(\mathbf{x}'_i - (\mathbf{v} + \Delta \mathbf{v})) - \mathcal{J}(\mathbf{x}'_i))^2 \quad (1)$$

to be minimized w.r.t. $\Delta \mathbf{v}$. To solve the equation, a first order Taylor expansion is needed. Let $x_i = x'_i - (\mathbf{v} + \Delta \mathbf{v})$, setting, then, the first order derivative of the cost function to zero to find the stationary point we obtain:

$$\sum_{\mathbf{x}'_i \in W'_J} \nabla \mathcal{I}(\mathbf{x}_i) \nabla \mathcal{I}(\mathbf{x}_i)^T \Delta \mathbf{v} = \sum_{\mathbf{x}'_i \in W'_J} (\mathcal{I}(\mathbf{x}_i) - \mathcal{J}(\mathbf{x}'_i)) \nabla \mathcal{I}(\mathbf{x}_i) \quad (2)$$

In matrix form we can write it as $\mathbf{A} \Delta \mathbf{v} = \mathbf{b}$. Solving for $\Delta \mathbf{v}$, the update rule for the iteration scheme is $\mathbf{v} = \mathbf{v} + \Delta \mathbf{v}$, and $\mathbf{x}'_i = \mathbf{x}_i + \mathbf{v}$. The procedure is repeated until convergence or until some breaking criterion is met (for example, when the displacement is smaller than a threshold).

Epipolar Geometry This section contains a short review of the geometrical entities involved in epipolar geometry which are necessary to derive our algorithms. A more complete presentation is made, e.g., in [11]. With reference to Figure 2, for a given image pair $\mathcal{I}$ and $\mathcal{J}$ produced by two cameras, or the same camera in two different positions, having their center of projection in $\mathbf{CoP}$ and $\mathbf{CoP}'$ respectively, we can make the following observations (assuming lens distortion is absent or the images are rectified):

1. The projection of $\mathbf{CoP}$ in the image plane of $\mathcal{J}$ is the *epipole* $\mathbf{ep}$.
2. For every 3D point $\mathbf{P}_k$ observed by both the cameras, the projection of the $\mathbf{P}_k$ in $\mathcal{J}$, $\mathbf{p}'_k$, must lie on a line in $\mathcal{J}$, given as the projection of the optic ray through $\mathbf{p}_k$ in $\mathcal{I}$, i.e., the 3D line connecting $\mathbf{CoP}$ and $\mathbf{p}_k$, onto $\mathcal{J}$. This line is the *epipolar line* generated by $\mathbf{p}_k$ in $\mathcal{J}$.
3. All the epipolar lines on an image plane, for a certain camera pair, meet in the corresponding epipole, $\mathbf{ep}$.

Given the images $\mathcal{I}$ and $\mathcal{J}$, the corresponding epipolar geometry is represented by the fundamental matrix $\mathbf{F}$. The epipolar line in $\mathcal{J}$ corresponding to a point of pixel coordinates $\mathbf{x}$ in $\mathcal{I}$ is given by $\tilde{\mathbf{e}} = \mathbf{F}\tilde{\mathbf{x}} = [e_1 \ e_2 \ e_3]^\top$, where $\tilde{\mathbf{x}}$ is the column vector of the homogeneous pixel coordinates of the point $\mathbf{x}$ and $\tilde{\mathbf{e}}$ is the dual homogeneous coordinates of the epipolar line. The 2-dimensional unity vector representing the direction of the epipolar line is then $\hat{\mathbf{e}} = [e_2 \ -e_1]^\top / \sqrt{e_1^2 + e_2^2}$.

Epipolar KLT We now have all the tools to derive the Epipolar KLT. Given an initialization on the epipolar line for the translation vector (i.e. $\mathbf{v}$ such that $\mathbf{x} + \mathbf{v}$ lies on $\tilde{\mathbf{e}}$), we can substitute $\hat{\mathbf{e}}$ in (1) to obtain a 1-dimensional cost function

$$G(\alpha) := \sum_{\mathbf{x}'_i \in W'_\mathcal{J}} (\mathcal{I}(\mathbf{x}'_i - (\mathbf{v} + \alpha\hat{\mathbf{e}})) - \mathcal{J}(\mathbf{x}'_i))^2 \quad (3)$$

to be minimized w.r.t. the scalar value α .

After the first order Taylor expansion and solving for the stationary point, we obtain the following expression to be iteratively minimized to converge toward the solution:

$$\alpha \sum_{\mathbf{x}'_i \in W'_\mathcal{J}} \nabla \mathcal{I}(\mathbf{x}_i) \nabla \mathcal{I}(\mathbf{x}_i)^T \hat{\mathbf{e}} = \sum_{\mathbf{x}'_i \in W'_\mathcal{J}} (\mathcal{I}(\mathbf{x}_i) - \mathcal{J}(\mathbf{x}'_i)) \nabla \mathcal{I}(\mathbf{x}_i). \quad (4)$$

In matrix form we can write the last expression as

$$\alpha \mathbf{A} \hat{\mathbf{e}} = \mathbf{b}, \quad (5)$$

which is an over-determined 2 equation system. By pre-multiplying both sides by $\hat{\mathbf{e}}^T$ (i.e. projecting the 2D problem on the direction of the epipolar line), we project the system into one dimension: $\alpha \hat{\mathbf{e}}^T \mathbf{A} \hat{\mathbf{e}} = \hat{\mathbf{e}}^T \mathbf{b}$. Solving for α , the update rule for the iteration scheme is $\mathbf{v} = \mathbf{v} + \alpha \hat{\mathbf{e}}$ and $\mathbf{x}'_i = \mathbf{x}_i + \mathbf{v}$. The procedure is repeated until convergence or until some breaking criterion is met (for example, when the displacement is smaller than a threshold).

3.2 Good Edgels to Track

As already mentioned, assuming a static scene and a reliable estimate of the relative camera motion between two frames, we can track two different kinds of features:

- Corner features
- Edge features non parallel to the motion

Similarly to the case of corner features, edge features are identified from the eigenvalues of their structure tensor: they are associated with a structure tensor with at least one eigenvalue over a certain threshold. However, not all edge features are useful for our method: edges parallel to their own epipolar line cannot be tracked reliably.

Let $\nabla\mathcal{I}_u(\mathbf{x})$ and $\nabla\mathcal{I}_v(\mathbf{x})$ be the horizontal and vertical gradient of the image calculated in $\mathbf{x}$ respectively. The structure tensor $T(\mathbf{x})$ for the point $\mathbf{x}$ is:

$$T(\mathbf{x}) = \begin{bmatrix} \nabla\mathcal{I}_u(\mathbf{x})^2 & \nabla\mathcal{I}_u(\mathbf{x})\nabla\mathcal{I}_v(\mathbf{x}) \\ \nabla\mathcal{I}_u(\mathbf{x})\nabla\mathcal{I}_v(\mathbf{x}) & \nabla\mathcal{I}_v(\mathbf{x})^2 \end{bmatrix}. \quad (6)$$

Given a pixel $\mathbf{x}$, its structure tensor T and its corresponding epipolar line $\tilde{\mathbf{e}}$ in the matching image, its score in the GETT sense is

$$\text{score}(\mathbf{x}) = \hat{\mathbf{e}}^T T(\mathbf{x}) \hat{\mathbf{e}}, \quad (7)$$

where $\hat{\mathbf{e}}$ is the unit vector representing the direction of the epipolar line in $\mathcal{J}$ for $\mathbf{x}$. Note that the value of the score is bounded by the larger and smaller eigenvalues of the structure tensor and corresponds, intuitively, to measuring the structure tensor along the direction of the optimization process.

3.3 Epipolar KLT Initialization

To assure convergence to a reasonable solution it is critical to initialize the tracker on the epipolar line. In our tests we assume that no prior information on the depth of the points is available. We therefore assume that every point has an infinite depth, in this case we can find a starting point on the epipolar line that is also a hard limit for our procedure as only one of the 2 segments of the epipolar line defined by this point is physically reasonable.

Let $\mathbf{K}$ be the intrinsic parameter matrix for the camera and $\mathbf{R}$ the inter-camera rotation between the 2 views. For a point $\tilde{\mathbf{x}} \in \mathcal{I}$ in homogeneous coordinates, its infinity projection on $\mathcal{J}$ is given by

$$\text{start}(\tilde{\mathbf{x}}) = \mathbf{K} \mathbf{R} \mathbf{K}^{-1} \tilde{\mathbf{x}}. \quad (8)$$

We refer to this initialization procedure as *initialization at infinity*.

Depending on the scene structure and the camera motion, this initialization can fail, in particular if the scene has large variation in depth and the translational motion component is significant relatively to the rotational component. This is the case for most driving sequences, such as those offered by the KITTI dataset [9], where this initialization is sensitive to repeating patterns and large displacements. This simple initialization, however, works in practice for the majority of the points. To increase the number of good matches, we do however perform an initialization in multiple steps as outlined in Algorithm 2. The details are given below.

4 Experiments

We tested our algorithm against the OpenCV ¹ standard KLT implementation. For a fair comparison, the epipolar constraint has been imposed to the output

¹ <http://opencv.org>

Fig. 3. Sample tracking output image from Sequence 1. **Top:** Tracking performed on GFTT with the standard KLT procedure. **Bottom:** Tracking performed on GETT with the epipolar KLT.

Algorithm 1. Testing pseudocode for standard KLT procedure

```

1: procedure TRACKGOODFEATURESTOTRACK( $I, J, K, R, t$ )
2:    $p \leftarrow \text{extractGoodFeaturesToTrack}(I)$ 
3:    $q \leftarrow \text{standardKLT}(I, J, p)$ 
4:    $r \leftarrow \text{standardKLT}(J, I, q)$ 
5:    $\text{corr} \leftarrow \{(p_i, q_i) \mid \|p_i - r_i\| < \tau\}$ 
6:    $\text{corr} \leftarrow \text{epipolarFilter}(\text{corr}, F)$ 
7:   return  $\text{corr}$ 
8: end procedure

```

of the standard tracker to reduce outliers. Both trackers have been fed with the same parameters in term of windows size (5×5), pyramid level (2nd level) and termination criteria (maximum 10 iterations, minimum displacement length of 0.1 pixels). The two testing schemes are outlined in Algorithms 1 and 2.

4.1 Implementation Details

In this subsection we go into the details of the testing scheme outlined in Algorithm 2.

Extraction of corners and edges We extract the corner and edge keypoints respectively according to the classical GFTT scheme and the hereby presented GETT scheme. The procedure works in the following way:

1. Extract the structure tensor for each pixel in the image.
2. Calculate the GFTT and GETT score for each pixel. The following steps are computed independently for GFTT and GETT points.

Algorithm 2. Testing pseudocode for our approach

```

1: procedure TRACKMIXEDFEATURES( $I, J, K, R, t$ )
2:    $F \leftarrow K^{-T}[t]_x R K^{-1}$ 
3:    $p \leftarrow \text{extractCornersEdges}(I, F)$ 
4:    $\text{start}_p \leftarrow K R K^{-1} p$ 
5:    $q \leftarrow \text{epipolarKLT}(I, J, p, \text{start}_p, F)$ 
6:    $\text{start}_q \leftarrow K R^T K^{-1} q$ 
7:    $r \leftarrow \text{epipolarKLT}(J, I, q, \text{start}_q, F^T)$ 
8:    $\text{corr} \leftarrow \{(p_i, q_i) \mid \|p_i - r_i\| < \tau\}$ 
9:    $\text{clusters} \leftarrow \text{clusterize}(p)$ 
10:   $c_{\text{MEAN}} \leftarrow \text{clustermeans}(\text{clusters}, \text{corr})$ 
11:   $\text{start}_p \leftarrow \text{moveStartingPoints}(\text{start}_p, c_{\text{MEAN}})$ 
12:   $q \leftarrow \text{epipolarKLT}(I, J, p, \text{start}_p, F)$ 
13:   $\text{corr} \leftarrow \{(p_i, q_i)\}$ 
14:   $c_{\text{MEAN}} \leftarrow \text{clustermeans}(\text{clusters}, \text{corr})$ 
15:   $\text{corr} \leftarrow \text{filterOutliers}(\text{corr}, c_{\text{MEAN}})$ 
16:  return  $\text{corr}$ 
17: end procedure

```

3. An Non-Maximum Suppression (**NMS**) filter is applied to the score images to obtain a better distribution of the keypoints. A sliding window is applied to each score image suppressing all the points which are not a local maximum. The window size is set at the same size of the tracking window at the lowest pyramid level.
4. A threshold τ is computed as a fraction of the highest score found in the image and the points with a score $> \tau$ are used as keypoints.

Tracker initialization The first initialization is given by the *initialization at infinity* presented in Section 3.3.

Tracking The tracking is done with the Epipolar KLT in Section 3.1, including a pyramidal *coarse-to-fine* scheme similar to the one presented in [5]. At the end of the tracking procedure, features presenting a large error (see [8]) or that moved on the wrong segment of the epipolar line are rejected as outliers.

Backtracking As suggested in [12], a backtracking step is performed to further remove outliers. Features are tracked backwards from image $\mathcal{J}$ to image $\mathcal{I}$ and when the procedure converges to a point different from the original feature, the feature is considered an outlier. Note that this step is proven particularly useful in the case of repeating patterns due to the naivety of the initialization.

Clusterization and tracker reinitialization The tracks surviving the first two steps are in general of good quality, but are not dense due to the naive initialization step performed. Therefore, we compute a new initialization based on region-wise local mean displacement for the available tracks. The image is subdivided in macro-regions (in our tests we use a 3×7 grid to determine the

Method	Sequence 1	Sequence 2	Sequence 3	Total
GETT + EpiKLT	3542 ± 464	4439 ± 848	4603 ± 484	4196 ± 779
GFTT + KLT	2537 ± 425	3593 ± 881	3908 ± 551	3347 ± 874

Table 1. Average number of features extracted over the 3 sequences $\pm$ standard deviation

Method	Sequence 1	Sequence 2	Sequence 3	Total
GETT + EpiKLT	1700 ± 324	1656 ± 470	2121 ± 373	1818 ± 448
GFTT + KLT	509 ± 250	412 ± 238	909 ± 337	610 ± 352

Table 2. Average number of features tracked over the 3 sequences $\pm$ standard deviation

regions) and the mean displacement along the epipolar line is robustly computed for each region, based on the available data of the surviving tracks belonging to the region. The displacement mean for each cluster of the image is robustly computed using the algorithm presented in [14]. This method works on 1-dimensional data, it orders the data and determines the mean giving the maximum amount of inliers, using a sliding window. The region-wise mean so computed is then used to reinitialize the tracker by moving the starting position of the tracker, away from the infinity projection of the feature, along the epipolar line.

Outlier removal The last tracking step has proven to provide a much higher inlier ratio than the initialization at infinity, making a new backtracking step unnecessary. To remove the remaining outliers, we perform a filtering based on a re-computed region based mean, and remove points that do not behave according to the majority of the points in the region (we assume a Gaussian distribution and set the filter threshold at twice the standard deviation for the region).

Note that this complicated procedure is only necessary when no prior information on the depth structure of the scene is known. For image sequences, features can in general be tracked more than once, thus providing a depth estimate and a better initialization of the tracker. For new features, even accounting for reasonable depth discontinuities, the initialization can be performed by using the already available depth information of similar nearby points.

4.2 Results

We tested our method on sequences extracted from the KITTI dataset [9], consisting of driving scenes recorded by a calibrated stereo setup. Each of the extracted sequences consists of 199 image pairs and present different settings:

- Sequence 1 shows an urban scenario: mainly buildings on the sides of the road.
- Sequence 2 is set in a suburban scenario. Mostly trees surround the road

Fig. 4. Distribution of extracted GFTT (**top-left**) and GETT (**bottom-left**). Distribution of successfully tracked GFTT (**top-right**) and GETT (**bottom-right**).

- Sequence 3 also has a suburban setting and shows a variety of buildings, vegetation and parked cars on the side of the road.

In our tests, we disregard the stereo information, focusing on a monocular scenario and making use of the given camera calibration. To show the robustness of the method, we do not use the ground truth egomotion provided with the KITTI dataset, we take instead the estimates produced by an implementation of [20]. The approach consists in a matching procedure performed on FAST keypoints [24] and BRIEF descriptors [6], the epipolar geometry estimation is made robust with RANSAC, and stabilized with a windowed bundle adjustment.

Tables 1 and 2 show, as expected, the higher density of GETT compared to GFTT which, combined with a better inlier ratio granted by the proposed tracking procedure, allows to sensibly increase density of the motion field. Notice that, as shown in Figure 4 and 3 the increase in density is particularly evident in areas of the image closer to the camera and on the road plane. This is a very desirable feature for many applications since closeby objects are generally of more interest and can be measured more precisely.

5 Conclusions

In this work we presented a complete framework for the extraction and tracking of edge elements in an image pair. Such edge elements would normally suffer from the aperture problem and cannot be tracked successfully. By exploiting a known estimate of the epipolar geometry of the scene, our algorithm allows to extract and successfully track specific edgels that are likely to behave well with the given egomotion. We have shown that such keypoints (*GETT*) consistently outnumber the standard *GFTT* in different settings, have a higher inlier ratio when tracked with the procedure we presented and are also more uniformly spread on the image plane. These are all very desirable qualities that allow to produce a much denser point cloud in any structure from motion application.

Acknowledgments. This work has been supported by ELLIIT, Strategic Area for ICT research, and CADICS, funded by the Swedish Government, and by iQMatic, funded by VINNOVA.

References

1. Agrawal, M., Konolige, K., Blas, M.R.: CenSurE: Center Surround Extremas for Realtime Feature Detection and Matching. In: Forsyth, D., Torr, P., Zisserman, A. (eds.) ECCV 2008, Part IV. LNCS, vol. 5305, pp. 102–115. Springer, Heidelberg (2008)
2. Baker, S., Matthews, I.: Lucas-Kanade 20 years on: A unifying framework. *International Journal of Computer Vision* **56**(3), 221–255 (2004)
3. Bay, H., Tuytelaars, T., Van Gool, L.: SURF: Speeded Up Robust Features. In: Leonardis, A., Bischof, H., Pinz, A. (eds.) ECCV 2006, Part I. LNCS, vol. 3951, pp. 404–417. Springer, Heidelberg (2006)
4. Birchfield, S.T., Pundlik, S.J.: Joint tracking of features and edges. In: IEEE Conf. on Computer Vision and Pattern Recognition (CVPR 2008) (2008)
5. Bouguet, J.Y.: Pyramidal implementation of the affine Lucas Kanade feature tracker: description of the algorithm. Intel Corporation, Tech. rep. (2001)
6. Calonder, M., Lepetit, V., Strecha, C., Fua, P.: BRIEF: Binary Robust Independent Elementary Features. In: Daniilidis, K., Maragos, P., Paragios, N. (eds.) ECCV 2010, Part IV. LNCS, vol. 6314, pp. 778–792. Springer, Heidelberg (2010)
7. Farnebäck, G.: Two-Frame Motion Estimation Based on Polynomial Expansion. In: Bigun, J., Gustavsson, T. (eds.) SCIA 2003. LNCS, vol. 2749, pp. 363–370. Springer, Heidelberg (2003)
8. Fusiello, A., Trucco, E.: Improving feature tracking with robust statistics. *Pattern Analysis & Applications* pp. 312–320 (1999)
9. Geiger, A., Lenz, P., Urtasun, R.: Are we ready for autonomous driving? the KITTI vision benchmark suite. In: IEEE Conf. on Computer Vision and Pattern Recognition (CVPR 2012) (2012)
10. Harris, C., Stephens, M.: A combined corner and edge detector. In: Alvey Vision Conference, pp. 23.1–23.6 (1988)
11. Hartley, R.I., Zisserman, A.: *Multiple View Geometry in Computer Vision*. Cambridge University Press (2004)
12. Hedborg, J., Forssén, P.-E., Felsberg, M.: Fast and Accurate Structure and Motion Estimation. In: Bebis, G., Boyle, R., Parvin, B., Koracin, D., Kuno, Y., Wang, J., Wang, J.-X., Wang, J., Pajarola, R., Lindstrom, P., Hinkenjann, A., Encarnação, M.L., Silva, C.T., Coming, D. (eds.) ISVC 2009, Part I. LNCS, vol. 5875, pp. 211–222. Springer, Heidelberg (2009)
13. Horn, B., Schunck, B.: Determining optical flow. In: SPIE 0281, Techniques and Applications of Image Understanding, vol. 319 (1981)
14. Jonsson, E., Felsberg, M.: Efficient robust mean value computation of 1D features. In: Proceedings of Svenska Sällskapet för Automatiserad Bildanalys. SSBA-2005 (2005)
15. Kitt, B., Latgahn, H.: Trinocular optical flow estimation for intelligent vehicle applications. In: International IEEE Conference on Intelligent Transportation Systems (ITSC), pp. 300–306. IEEE, September 2012
16. Lee, T., Soatto, S.: Fast planar object detection and tracking via edgel templates. In: IEEE Workshop on the Applications of Computer Vision (WACV), pp. 473–480. IEEE, January 2012
17. Leutenegger, S.: BRISK: Binary robust invariant scalable keypoints. *IEEE Int. Conf. on Computer Vision (ICCV)* **2011**, 2548–2555 (2011)
18. Lowe, D.G.: Distinctive Image Features from Scale-Invariant Keypoints. *International Journal of Computer Vision* **60**(2), 91–110 (2004)

19. Lucas, B., Kanade, T.: An iterative image registration technique with an application to stereo vision. In: International Joint Conference on Artificial Intelligence (IJCAI) (1981)
20. Persson, M.: Online Monocular SLAM. Master's thesis, Computer Vision Laboratory, Linköping University, Sweden (December 2013)
21. Rublee, E., Rabaud, V., Konolige, K., Bradski, G.: ORB: an efficient alternative to SIFT or SURF. In: IEEE Int. Conf. on Computer Vision (ICCV), pp. 2564–2571 (2011)
22. Shi, J., Tomasi, C.: Good features to track. In: IEEE Conf. on Computer Vision and Pattern Recognition CVPR 1994, pp. 593–600 (1994)
23. Tommasini, T., Fusiello, A.: Making good features track better. IEEE Conf. on Computer Vision and Pattern Recognition, pp. 178–183 (1998)
24. Trajković, M., Hedley, M.: Fast corner detection. *Image and Vision Computing* **16**(1998), 75–87 (1998)
25. Trummer, M., Denzler, J., Munkelt, C.: KLT tracking using intrinsic and extrinsic camera parameters in consideration of uncertainty. International Conference on Computer Vision Theory and Applications (VISAPP) (2008)
26. Yamaguchi, K., McAllester, D., Urtasun, R.: Robust monocular epipolar flow estimation. In: IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp. 1862–1869. IEEE, June 2013

PAPER F

ROBUST ACCURATE EXTRINSIC CALIBRATION OF STATIC NON-OVERLAPPING CAMERAS

A. Robinson, M. Persson, and M. Felsberg, “Robust accurate extrinsic calibration of static non-overlapping cameras”, in *CAIP*, 2017

F

Robust Accurate Extrinsic Calibration of Static Non-overlapping Cameras

Andreas Robinson, Mikael Persson, and Michael Felsberg

Linköping University, 581 83 Linköping, Sweden
firstname.lastname@liu.se,
<https://liu.se/organisation/liu/isy/cvl>

Abstract. An increasing number of robots and autonomous vehicles are equipped with multiple cameras to achieve surround-view sensing. The estimation of their relative poses, also known as extrinsic parameter calibration, is a challenging problem, particularly in the non-overlapping case. We present a simple and novel extrinsic calibration method based on standard components that performs favorably to existing approaches. We further propose a framework for predicting the performance of different calibration configurations and intuitive error metrics. This makes selecting a good camera configuration straightforward. We evaluate on rendered synthetic images and show good results as measured by angular and absolute pose differences, as well as the reprojection error distributions.

1 Introduction

Autonomous vehicles and robots benefit greatly from visual surround view sensing for both spatial and semantic understanding [15]. Surround view in turn requires multiple cameras with highly accurate extrinsics. Achieving the latter is an issue in camera configurations with limited or non-overlapping fields-of-view, as the standard methods for overlapping cameras cannot be applied. Since calibration errors cause biased estimates in crucial tasks such as visual odometry and spatial reconstruction, highly accurate estimates are required. Unfortunately non-overlapping configurations are common due to monetary and computational cost considerations and existing applicable methods rely on complicated tools and software.

Two approaches to minimal camera surround view sensing exist: either maximize the field-of-view per camera, with fisheye lenses or a catadioptric mirror, or allow more cameras with narrower field-of-view but rectilinear wide-angle lenses. While both fisheye lenses and catadioptric mirrors have excellent field-of-view, they can be costly and suffer from distortion that is difficult to calibrate well, compared to rectilinear lenses. In addition, with very few cameras it is hard avoid the body of the vehicle obstructing the view. Hence, this work will focus on the rectilinear type.

The intrinsic parameters of each lens in a camera configuration is straightforward to estimate independently [20]. We address the extrinsic estimation prob-

lem, under the assumption that intrinsic calibration has been achieved to sufficient accuracy.

Fig. 1. Left: Camera pair without overlap seen from above. Extrinsic calibration not possible in a static setting. Right: A temporarily placed additional camera enables extrinsic calibration.

Fig. 2. Calibrating two marginally overlapping cameras on a truck, with the addition of a third camera.

We propose adding intermediate cameras during the extrinsic calibration process, as exemplified by the schematic in figure 1, for the purpose of calibrating cameras on vehicles such as the one shown in figure 2. This strategy creates or increases the overlap between fields-of-view and allows the use of any standard stereo calibration toolbox, with minimal development effort. Since the extra cameras are temporary, the cost, weight and performance limitations of the permanently installed cameras do not apply. Thus, better-performing cameras can be used to further improve the accuracy, if required. We show that greater

overlap is beneficial and analyze the trade-off between additional cameras and propagated calibration errors.

In this paper we contribute

- a simple extrinsic calibration procedure based on applying the standard method through the novel use of additional temporary intermediate cameras.
- an evaluation framework for determining the expected quality of a given setup. This framework can also be used to identify good calibration configurations.
- a geometrically intuitive extrinsic error metric - the reprojection error distribution caused by the extrinsic error in a given camera setup.

2 Related Work

Approaches to calibrating non-overlapping cameras can be sorted into two broad categories, static and dynamic: Static methods either use mirrors to allow all cameras to see the same calibration object or large calibration objects that are only partially visible in each camera. Dynamic methods use structure-from-motion to capture the structure of a scene and to subsequently infer rigid relationships between cameras.

In the first category, a fairly recent method by Sturm et al. [18] recovers the poses of virtual cameras reflected in three or more planar mirrors, in order to find the pose of a "true" camera. Later work by several other authors [10, 9, 11, 17, 19, 14] present extensions and alternative approaches that also use planar mirrors. In contrast, Agrawal et al. [1] show that calibration with a spherical mirror is advantageous; it lacks degeneracies and only one mirror is required, although the accuracy is comparably low. Additionally, methods using calibration objects that are only partially visible in each camera have been suggested although this seems less common. Liu et al. [13] performs extrinsic calibration with a long stick, with the ends visible in each of the two cameras. In [12], this stick is substituted by lasers.

In the second category, calibration with structure-from-motion or photogrammetry, Esquivel et al. [6] and Carrera et al. [4] capture sequences of the surrounding environment on vehicles with rigidly coupled cameras, finding the relative camera poses after 3D reconstruction. Pagel et al. [16] implements online calibration based on a system for visual odometry and more recently Dong et al. [5] places easily identifiable calibration objects in a scene, uses photogrammetry to pinpoint their locations and then relate the cameras to be calibrated to these objects. Note that structure-from-motion approaches require additional information to determine an absolute scale. This is typically achieved with a calibration object of known size.

There are several ways to verify and compare camera intrinsic/extrinsic calibration quality. One choice is to verify that the reprojection errors on the calibration features is sensible, i.e. less than one pixel on average with no severe outliers.

Another reasonable metric for comparison is the difference between the true and the estimated pose, as they map to intuitive physical properties. Since our target application is structure-from-motion, we propose that the reprojection error distribution provides an intuitive understanding of both error severity and acceptable limits.

Both static and dynamic methods can yield good results but have their downsides. Mirrors must have the reflective surface on the front to avoid chromatic aberrations, which adds to their fragility. Placing them to ensure the calibration object is reflected into the camera can be complicated. Large calibration objects warp under their own weight, while lasers have little pixel coverage and are hard to spot in cameras equipped with wide-angle lenses. Structure-from-motion approaches can be labor intensive to execute well in uncontrolled environments. We have also found that the estimated metric scale is very sensitive to noise. In addition, the perhaps most important aspect of these methods is that they require significant software development efforts to get up and running.

In contrast, with our method a few additional cameras makes the stereo calibration tools in the OpenCV software library [3] sufficient. The performance of the proposed hardware extension based approach has to our knowledge not been investigated previously.

3 Method

This section presents a general model of the extrinsic camera calibration problem, the proposed method, the imaging model and concludes with the error metrics.

3.1 The Extrinsic Graph

Consider the extrinsic camera configuration problem for N cameras as an acyclic, un-weighted and un-directed graph. Each node corresponds to a camera pose and each edge to an observed relative pose. A connected graph implies that all poses are constrained and can be determined. Since the graph is acyclic, the relative poses can be found separately per constraint. General camera configurations need not result in a connected graph, but by adding cameras we can always create one. Each extra camera adds two new edges to the graph. Since acyclic connected graphs are sufficient, there is no need to add any cycle. Adding cycles and appropriate weights could improve accuracy, but would require joint optimization.

3.2 Calibration Procedure

Given the relative poses, any camera can be selected as origin and the poses of each other camera in relation to it are trivially computed by chaining the transformations. We use unit quaternion based poses to avoid compounding numerical errors. Thus we create an acyclic connected graph and estimate the relative poses in an interleaved manner as follows:

Estimating Relative Transforms The metric relative transform between two overlapping cameras with known intrinsics can be estimated using a chessboard pattern of known proportions and a small number, (here $N = 5$), of images. The chessboard pattern is found by OpenCV `findChessBoardCorners()` and the relative pose is computed using `stereoCalibrate()` which implements a homography based solver. Note that the signal-to-noise ratio of the estimation is related to the detection noise over the pixel distance between corner projections [8]. This suggests it is a good idea to have a large overlap between cameras and for the chessboard to cover most of it. Thus we require a lower bound of overlap to consider two cameras connected, how the overlap relates to the error is explored in section 4.

Adding Cameras The goal is to create a fully connected acyclic graph by adding cameras. Finding the optimal configuration is both difficult and unnecessary. This motivates the following simple greedy scheme:

Iterate until the graph is connected:

- Find the two closest, in terms of angular distance, unconnected, cameras.
- Place an evenly distributed sequence of cameras with sufficient overlap along the shortest path.

The suitable number of cameras can be found by simulation similar to the one in section 4. Note that regardless of the number of intermediate camera positions, at most two extra physical cameras are required since they can be moved.

3.3 Camera Noise Model

The image capture and feature extraction processes contain three distinct sources of noise:

In the optical stage, light enters the camera and is focused by the lens before hitting the sensor. Imperfections due to both lens design and manufacturing variability, attenuates (vignetting), diffuses (blurring) and distorts the light. We model the first two effects directly as

$$I_1(\mathbf{x}) = \cos^4(k_1|\mathbf{x}|) \circ (H_\sigma * I_0)(\mathbf{x}) \quad (1)$$

where $|\mathbf{x}|$ is the distance from the camera's optical axis, $H_\sigma(\mathbf{x})$ is a small point spread (blur) Gaussian function of width σ , and k_1 controls the falloff rate of the vignetting function. In addition $(\cdot \circ \cdot)$ and $(\cdot * \cdot)$ denote point-wise multiplication and convolution, respectively. In the experiments, the blur kernel is fixed to 5×5 pixels, with $\sigma = 0.5$. k_1 is chosen so that the maximum intensity at the left and right image edges are 25% of the maximum in the center. The third effect, distortion, is modeled below.

In the electronic stage, light is converted into electric charge in the sensor, is read out, amplified and digitized to form a digital image. Here, a significant

source of error is the shot noise. We model this with a Poisson process approximation, specifically Gaussian noise with variance proportional to the light intensity:

$$I_2(\mathbf{x}) = \mathcal{N}(I_1(\mathbf{x}), b + k_2 \sqrt{I_1(\mathbf{x})}) \quad (2)$$

where b is the minimum noise variance and k_2 a scale factor. We found that with $I(x) \in [0, 255]$, setting the parameters to $b = 2$ and $k_2 = 0.1$ produced noise that looked "reasonably realistic" as is shown in figure 4. Estimating the parameters of a specific camera sensor would further improve the model accuracy.

In addition, pixel intensities are clamped to the range $[0, 255]$, i.e

$$I_3(\mathbf{x}) = \min(\max(I_2(\mathbf{x}), 0), 255) \quad (3)$$

In the digital stage, a detector locates the calibration pattern landmarks with subpixel-precision. This operation does not have to be modeled explicitly since either the OpenCV function `findChessboardCorners()` or `cornerSubPix()` can be applied directly. The output from the detector is a set of 2D points $\mathbf{y}_k$. $k \in [1, K]$ where K is the number of calibration pattern landmarks.

In a real-world setting, these coordinates will have rather large errors due to lens distortion. However, for the purpose of the simulation we assume that distortion is mostly corrected by a function $U(\mathbf{y})$ and model the residual error with a Gaussian noise process. The final coordinates are thus

$$\mathbf{z}_k = U(\mathbf{y}_k) + \epsilon_d \quad (4)$$

with $\epsilon_d \sim \mathcal{N}(\mathbf{0}, \sigma_d \mathbf{I})$, where $\mathbf{I}$ denotes the 2×2 identity matrix.

3.4 Error metrics

As mentioned in section 2, we consider two quality measures: the pose (rotational and translational) error and the reprojection error distribution. The latter provides a intuitive understanding of what impact the former is expected to have, on a structure-from-motion system.

Rotation and Translation Errors Let the 4×4 matrix $\mathbf{P}$ represent a 3D rigid transform, composed of a rotation matrix $\mathbf{R}$ and translation vector $\mathbf{t}$. Let $\mathbf{P}$ denote the ground truth and $\hat{\mathbf{P}}$ the associated estimate. $\mathbf{P}_i$ is the transform from world coordinates to the local coordinate system of camera i and $\mathbf{P}_{ji}$ is the relative transform from the local coordinate system of camera i to that of camera j .

We define the translation error of $\hat{\mathbf{P}}$ relative to $\mathbf{P}$ as $\epsilon_t = \|\hat{\mathbf{R}}^{-1}\hat{\mathbf{t}} - \mathbf{R}^{-1}\mathbf{t}\|_2$. Similarly, the rotation error is defined as $\epsilon_R = |\mathbf{R}\hat{\mathbf{R}}^{-1}|$, where $|\cdot|$ is the magnitude of the angle around the axis of rotation in $\mathbf{R}\hat{\mathbf{R}}^{-1}$.

Expected Reprojection Error The distribution of reprojection errors is approximated by sampling points $\mathbf{y}$ and computing the error as follows. Let $\mathbf{y} = (x, y, z, 1)^T$ be a homogeneous 3D point in the local coordinate system of camera i and that $\mathbf{x} = \mathbf{P}_i^{-1}\mathbf{y}$ is the same point in the world coordinate system. With the camera projection operator defined as $\text{Proj} : (x, y, z, 1)^T \mapsto (x/z, y/z, 1)^T$, the reprojection error (in pixels) of $\mathbf{x}$ in camera i is $\epsilon_p = f\|\text{Proj}(\hat{\mathbf{P}}_i\mathbf{x}) - \text{Proj}(\mathbf{P}_i\mathbf{x})\|_2$, where f is the focal length.

4 Experiments

The following experiments on synthetic imagery will show how the calibration error as measured by our chosen metrics varies with the camera configuration and the noise. Care has been taken to simulate realistic noise, as simpler models may hide interesting behaviors.

Our use-case, shown in figure 2, is a mobile platform (truck) with two 1600 x 1200 pixel cameras at 90 degree relative yaw angle but with very wide-angle lenses (focal length 1.67mm). Due to the wide fields-of-view, there is an overlap of approximately 10 degrees between the cameras. However, this image area is small and calibration patterns must be placed a significant distance away to be simultaneously visible in both cameras. The procedure has been performed on the mobile setup but the accuracy cannot be determined without ground truth or additional sensors. Thus, the experiments are performed on synthetic data.

4.1 Setup

To evaluate the impact of additional cameras providing significant overlap, a synthetic calibration pipeline is constructed. The pipeline generates noise-free images, applies noise, and finds the extrinsic camera parameters. We experiment with two cameras with a 90 degree interval, three cameras at 45 degrees, and five cameras at 22.5 degrees.

First, images are generated with the Blender 3D modeling software [7]. Pair-wise camera configurations and associated pattern placements are shown in figure 3. The cameras are outward facing on a circle with 1.5 meter radius and relative rotations of either 22.5, 45, or 90 degrees. In each case, five checkerboard calibration patterns (7-by-9 squares, 84 x 108 cm) are manually placed to maximally cover the joint field of view. As is shown in the figure, larger relative rotations provide less overlap and require the patterns to be placed farther away from the cameras. Note that cases such as 45-to-90 degree or 45-to-67.5 degree rotations are omitted, as they are equivalent to simultaneously rotating all objects in any of the existing setups.

In each configuration one calibration pattern at a time is placed inside the joint field-of-view of the camera pair. Images are rendered and the associated ground-truth image 2D coordinates of all pattern landmarks are stored.

Second, errors caused by the camera are simulated and added to the images. An example image with blur, vignetting and shot noise applied, is shown in figure 4.

Fig. 3. Camera and pattern setups with 22.5, 45 and 90 degree rotations between cameras. Insets show the pattern placements in the viewport of the right camera in the pair. Their appearance in the left camera are mirror-symmetric. The ground-plane grid lines are 1 meter apart.

Fig. 4. Example of a rendered image with added vignetting, blur and shot noise. Inset: Closeup of camera shot noise - best viewed on-screen.

Third, the calibration pattern landmarks are located with sub-pixel precision (`findChessboardCorners()` in OpenCV). Since a coarse alignment can and should be verified manually, we only perform the subpixel refinement (`cornerSubPix()`) with ground-truth landmarks as input. Gaussian noise is then added, simulating the effects of the residual camera distortion error. This is in line with other work, such as [1] and is in effect the main source of noise in the calibration pipeline.

Finally, these noisy landmark coordinates are used to estimate the relative transform between the two cameras in a pair (`stereoCalibrate()`).

For each of the camera configurations, we generate $M = 1000$ calibration runs, with different noise added each time. This provides a reasonable sampling of the error distribution. N-view camera setups are simulated by linking the relative poses of pairs of cameras $\hat{\mathbf{P}}_{N,1} = \prod_{k=1}^{N-1} \hat{\mathbf{P}}_{k+1,k}$. For example, in a three-view setup, $\hat{\mathbf{P}}_{31} = \hat{\mathbf{P}}_{32}\hat{\mathbf{P}}_{21}$. In addition we compute the reprojection errors of 10,000 random points $\mathbf{y} = (x, y, z, 1)^T$, uniformly distributed across the image plane at uniformly random depths $z \in [0.1, 100]$.

4.2 Results

The mean errors ϵ_R and ϵ_t in $\hat{\mathbf{P}}_{N,1}$ are shown in figure 5. The distribution of reprojection errors in the presence of varying levels σ_d of distortion noise ϵ_d , are shown in figure 6.

Fig. 5. Expected pose rotation errors and expected pose translation errors as functions of added ϵ_d noise of magnitude σ_d .

5 Discussion

It is clear from figure 5 that the calibration is most sensitive to noise when no cameras have been added ($N = 2$) and the overlap is small. In contrast, additional cameras ($N = 3$ or $N = 5$) and greater overlap significantly improves the resilience to noise and is likely to compensate for the error accumulation along the chain of transforms. The difference between $N = 3$ and $N = 5$ is small. Depending on the assumed error, it is better to use one rather than three additional cameras. This trade-off may change if we expect significantly higher noise but that could also indicate poor intrinsic estimation quality. Presumably this generalizes to similar configurations, but should be confirmed using the provided toolbox to analyze the configuration on a case by case basis.

While it is difficult to compare the expected accuracy under the radically different setups and scenarios, we compare our results with those from other papers in table 1. When possible, the values corresponding to a noise level of $\sigma_d = 0.5$ are used.

Subject to differences in noise models, setup, cameras, and evaluation, we conclude that the performance of the proposed system is favorable or at least comparable to the baselines. Note that the rotation error represents a lower bound on projection accuracy since it will affect distant points which are otherwise unaffected by translation error.

Fig. 6. Distribution of reprojection errors with varying noise magnitude σ_d , computed for the relative pose between outermost cameras at 90 degrees, with $N - 2$ cameras in between.

Table 1. Comparison of rotation errors.

Method	Rotation error
Ours	0.04°
Esquivel et al. [6]	0.5°
Antone et al. [2]	0.1°
Agrawal et al.[1]	1°

The accuracy of the calibration in terms of the absolute pose error is good and is likely to exceed the precision of tools like tape measures and protractors. However, the reprojection error distributions in figure 6 indicate that the calibration error is not negligible but should be accounted for in a structure-from-motion system. In particular, while the error mode is relatively moderate, the heavy tail of the two-camera calibration setup is remarkable and motivates the use of additional cameras during calibration, even for limited-overlap configurations.

The calibration code and calibration quality estimation toolbox, along with the dataset and evaluation code, is available on GitHub ¹.

6 Conclusion

We have presented a simple and novel extrinsic calibration method and an evaluation framework for determining the expected quality using synthetic data. We have shown that the system achieves good results with a predictable impact on the intended application in terms of reprojection error distributions. The method is based on off-the-shelf components and is intended for multi-camera setups with small or no overlapping fields-of-view. The procedure is robust and simple to implement which makes it especially suited for industrial applications. Acknowledgement: This work was funded in part by Vinnova, Sweden’s innovation agency and Daimler AG.

References

1. Agrawal, A.: Extrinsic camera calibration without a direct view using spherical mirror. In: Proceedings of the IEEE International Conference on Computer Vision. pp. 2368–2375 (2013)
2. Antone, M., Teller, S.: Scalable extrinsic calibration of omni-directional image networks. International Journal of Computer Vision 49(2), 143–174 (2002)
3. Bradski, G., et al.: The opencv library. Doctor Dobbs Journal 25(11), 120–126 (2000)
4. Carrera, G., Angeli, A., Davison, A.J.: Slam-based automatic extrinsic calibration of a multi-camera rig. In: Robotics and Automation (ICRA), 2011 IEEE International Conference on. pp. 2652–2659. IEEE (2011)

¹ <https://github.com/midjji/non-overlapping-extrinsic-cameracalibration.git>

5. Dong, S., Shao, X., Kang, X., Yang, F., He, X.: Extrinsic calibration of a non-overlapping camera network based on close-range photogrammetry. *Applied Optics* 55(23), 6363–6370 (2016)
6. Esquivel, S., Woelk, F., Koch, R.: Calibration of a multi-camera rig from non-overlapping views. In: *Joint Pattern Recognition Symposium*. pp. 82–91. Springer (2007)
7. Foundation, B.: Blender version 2.78c (2017), <https://www.blender.org/>
8. Hedborg, J., Forssén, P.E., Felsberg, M.: Fast and accurate structure and motion estimation. *Advances in Visual Computing* pp. 211–222 (2009)
9. Hesch, J., Mourikis, A., Roumeliotis, S.: Extrinsic camera calibration using multiple reflections. *Computer Vision–ECCV 2010* pp. 311–325 (2010)
10. Kumar, R.K., Ilie, A., Frahm, J.M., Pollefeys, M.: Simple calibration of non-overlapping cameras with a mirror. In: *Computer Vision and Pattern Recognition, 2008. CVPR 2008. IEEE Conference on*. pp. 1–7. IEEE (2008)
11. Lébraly, P., Deymier, C., Ait-Aider, O., Royer, E., Dhome, M.: Flexible extrinsic calibration of non-overlapping cameras using a planar mirror: Application to vision-based robotics. In: *Intelligent Robots and Systems (IROS), 2010 IEEE/RSJ International Conference on*. pp. 5640–5647. IEEE (2010)
12. Liu, Q., Sun, J., Liu, Z., Zhang, G.: Global calibration method of multi-sensor vision system using skew laser lines. *Chinese Journal of Mechanical Engineering* 25(2), 405–410 (2012)
13. Liu, Z., Zhang, G., Wei, Z., Sun, J.: Novel calibration method for non-overlapping multiple vision sensors based on 1d target. *Optics and Lasers in Engineering* 49(4), 570–577 (2011)
14. Long, G., Kneip, L., Li, X., Zhang, X., Yu, Q.: Simplified mirror-based camera pose computation via rotation averaging. In: *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*. pp. 1247–1255 (2015)
15. Maddern, W.: Industry solutions: Autonomous vehicle driven by vision. *Vision Systems Design* 22(2) (2 2017), <http://www.vision-systems.com/articles/print/volume-22/issue-2/features/industry-solutions-autonomous-vehicle-driven-by-vision.html>
16. Pagel, F.: Extrinsic self-calibration of multiple cameras with non-overlapping views in vehicles. In: *IS&T/SPIE Electronic Imaging*. pp. 902606–902606. International Society for Optics and Photonics (2014)
17. Rodrigues, R., Barreto, J., Nunes, U.: Camera pose estimation using images of planar mirror reflections. *Computer Vision–ECCV 2010* pp. 382–395 (2010)
18. Sturm, P., Bonfort, T.: How to compute the pose of an object without a direct view? In: *Asian Conference on Computer Vision*. pp. 21–31. Springer (2006)
19. Takahashi, K., Nobuhara, S., Matsuyama, T.: A new mirror-based extrinsic camera calibration using an orthogonality constraint. In: *Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on*. pp. 1051–1058. IEEE (2012)
20. Zhang, Z.: A flexible new technique for camera calibration. *IEEE Transactions on pattern analysis and machine intelligence* 22(11), 1330–1334 (2000)

FACULTY OF SCIENCE AND ENGINEERING

Linköping Studies in Science and Technology, Dissertation No. 2201
Department of Electrical Engineering

Linköping University
SE-581 83 Linköping, Sweden

www.liu.se